

PRODUCT CATALOG

PRICE LIST | CZECH REPUBLIC



inakustik

KABEL | LAUTSPRECHER | MUSIK



PREMIUM
HIGH SPEED HDMI®
KABEL MIT ETHERNET | 180°

10 L (ULTRA HD) BY 1.500P



inakustik

1,20m

PREMIUM
HIGH SPEED HDMI®
KABEL MIT ETHERNET

10 L (ULTRA HD) BY 1.500P



inakustik

0,75m

PREMIUM
HIGH SPEED HDMI®
KABEL MIT ETHERNET

10 L (ULTRA HD) BY 1.500P



inakustik

0,75m

PREMIUM
STEREO AUDIOKABEL
STEREO AUDIO CABLE




PREMIUM
STEREO AUDIOKABEL
STEREO AUDIO CABLE



inakustik

3,00m


PREMIUM
Y-SUBWOOFERKABEL
Y-SUBWOOFER CABLE



inakustik

3,00m

PREMIUM
ANTENNENKABEL | KOAX
ANTENNA CABLE | COAX



PREMIUM
ANTENNENKABEL | KOAX
ANTENNA CABLE | COAX

IN-AKUSTIK

CABLE GUIDE	04
QUALITY LEVELS	06

HOME VIDEO

HDMI CABLE	08
HDMI WIRELESS	12
HDMI SWITCH	12
HDMI SPLITTER	14
ANTENNA CABLE	15
VIDEO CABLE	17
S-VIDEO CABLE	17
DISPLAYPORT CABLE	17
SCART CABLE	17
RGB/YUV	17
ACCESSORIES	18

HOME HIFI

SPEAKER CABLE	20
MINI SPOOLS	23
ACCESSORIES FOR SPEAKER CABLES	24
AUDIO CABLE	26
SUBWOOFER CABLE	27
DIGITAL COAX	28
DIGITAL OPTO	29
PHONO CABLE	30
ACCESSORIES	31

POWER

POWER FILTER	37
POWER BAR	37
MAINS CABLE	38
POWER CABLE	38

HEADPHONE & „MOBILE“

PHONE PLUG CABLE & HEADPHONE EXTENSION	40
PHONE PLUG ADAPTER	41
IPLUG CABLE	41
HEADPHONE AMP	42
USB CHARGING ADAPTER	42

MULTIMEDIA

WIFI BLUETOOTH	43
DLNA STICK & MHL ADAPTER	44
USB & CAT CABLE	44
FIREWIRE CABLE	47

INSTALLATION

HDMI OPTICAL FIBRE PLUG TESTER	52
ANTENNA	54
CAT CABLE	54
SPEAKER CABLE	55
AV PANELS	55
AV TERMINALS	56
HDMI SPLITTER SWITCH MATRIX	58
HD BASE-T TRANSMITTER	61
HD BASE-T RECEIVER	61
HD BASE-T EXTENDER	62
HD BASE-T MATRIX	62
HDMI REPEATER	62
PROFESSIONAL CAT CABLE	62
HDMI DIGITAL ANALOG AUDIO CONVERTER	63

AMBIENTECH

AMBIENTRACK	64
AMBIENART	67
AMBIENTONE	70

REFERENZ SELECTION

SPEAKER CABLE	72
AUDIO CABLE	78
DIGITAL CABLE	79
PHONO CABLE	79
MAINS CABLE	80

STOIC

WALL MOUNTS & ABSORBER BASES (FREE-STANDING)	82
--	----

MUSIC & MEDIA

HIGHLIGHTS CD	86
HIGHLIGHTS LP	88
HIGHLIGHTS BLU RAY & DVD	89

WORTH KNOWING

WHITELINE SERIES	48
LEGAL NOTICE	90

TECHNOLOGY LEXICON

BANDWIDTH



Bandwidth is the frequency scope of a transmission. The bandwidth of a typical audio signal ranges from 20Hz to 20,000 Hz. A narrower bandwidth transmits fewer frequencies, a telephone typically transmits around 300 Hz to 3,000 Hz, a larger one will transmit more. Even with digital signals, we still speak of bandwidth, when the transmission of data per second is meant.

CAPACITANCE

Capacitance is the measure of the capacity to store electrical charges. However, cables should be able to transmit 100% of the signal without temporarily storing it. The less capacitance a cable has, the better.

CONSUMER ELECTRONICS CONTROL



CEC enables several devices, such as TV or DVD player, to be operated with only one remote control. Several devices from any manufacturer can be controlled, provided all the connected components are CEC compatible.

CROSS SECTION

The cross section is the size of the face surface of the conductor in a cable and is specified in square millimetres. The greater the cross section, the lower the losses. It should not be confused with the diameter.

DAMPING

The weakening of a signal transferred in a cable is called damping and it is specified in dB (decibels). I.e. it is a measure of signal loss. The damping of a cable depends on frequency and increases with rising transmission frequency. This specification is important for planning antenna cables for antenna systems. It should not be confused with the shielding dimension, which is also specified in dB.

DIAMETER

The diameter specifies the overall diameter of the cable in millimetres. This information is necessary for example when selecting the plug or calculating the spatial requirement of an overall installation (diameter of the conduits, etc.).

DATA RATE



The data rate specifies how many data units (bits) are transferred per second. The maximum data rate with an HDMI 2.0 interface is up to 18 Gbps. That is 18 billion bits or 2.25 billion characters per second (1 bit = 8 bytes).

EXTENDED DISPLAY IDENTIFICATION DATA (EDID)



With the EDID function, the display (e.g. LCD monitor) transmits information via the HDMI cable to the source (e.g. DVD player) as to which resolution formats it supports. The source, in turn, sends back the highest suitable format.

FINELY STRANDED

Many individual wires are twisted into a braid to make the cable more flexible. The sum of the individual wires makes the total cross-section. The thinner the wires, the more flexible the cable.

FULL-HD



Full-HD or 1080p has established itself as the term for the maximum HDTV resolution of 1920x1080 pixels. Full HD enables the use of larger screens or far better picture quality with the same screen size.

GOLD-PLATED CONTACTS



The 24 carat gold-plated plug contacts considerably reduce contact resistance and transfer signals optimally. The quality of the connection can be expressed in the contact resistance. Poor contacts have a high contact resistance and cause signal losses. Special surface treatment such as gold-plating contact surfaces considerably reduce resistance, improve contact and therefore the sound and picture quality.

HDTV



HDTV stands for high definition television. All new TV and video formats belong to the HDTV family. The assignment of the HDTV resolutions is simple and clear: The resolution in video lines gives the names to the American HDTV formats 720p (p = progressive, i.e. 720 full lines per picture) and 1,080i (i = interlaced, i.e. 2 x 540 line half-pictures). In addition, a horizontal resolution that matches the vertical resolution was selected that forms the picture format factor in the following simple manner: $720 \times 16:9 = 1,280$ and $1,080 \times 16:9 = 1,920$ horizontal pixels.

HIGH-BANDWIDTH DIGITAL CONTENT PROTECTION



As the HDMI interface sound and picture content is available in absolutely perfect resolution, the film and software industry have instructed that data may only be released as copy-proof. This is the reason for using HDCP.

HDR (HIGH DYNAMIC RANGE)



HDR (High Dynamic Range, HDMI 2.0a or higher) increases the contrast range of the picture. This makes more detailed resolution possible, particularly in dark areas of the picture, and increases the colour spectrum that can be displayed. Depending on the technique used, along with the increased colour depth this requires (30 bit), additional metadata for picture control are transmitted.

IMPEDANCE (75 OHMS)



The wave resistance, or impedance, is an important key figure for cables, calculated from the ratio of inductivity to capacity.

INDUCTIVITY

Each conductor that is flowed through forms a magnetic field around it. If the flow of current changes, the strength of the magnetic field also changes. This in turn results in an inductive current which counteracts the change of current in the conductor. A frequency-dependent resistance develops (also called inductive resistance) which has a negative impact on the transmission. Special designs reduce the inductivity of a cable.

JITTER



When serially transmitting A/V data, "one" and "zero" are coded by different impulse durations. Cable properties affect these impulse durations so that the data is not received perfectly. In the case of pronounced jitters, the D/A converter has to frequently correct the error and consequently the quality of playback for pictures and sound suffers.

INSULATION (DIELECTRIC)

The conductors are covered in a non-conductive material to protect against short circuits, corrosion and damage. As these materials still store electrical energy (capacitance), which is undesirable for audio and video cables, in-akustik has developed the Exzellenz Atmos Air – the first and only loudspeaker cable with the best insulation of all: air.

OFC COPPER



The transmission of picture and sound signals is highly complex and susceptible to interference. Any contamination in the conductor material prevents the flow of current, impairing the conductance and increasing the background noise. Therefore, we only use especially pure-grade, oxygen-free copper (OFC) with an especially high conductance.

POLYETHYLENE (PE)

PE is a high-quality insulating material (dielectric) which is ideal as an insulator. It reduces the capacitance of a cable by a factor of two compared with PVC (polyvinylchloride). The electrical loss of PE is also very low.

ROHS



Each of our cables complies with the RoHS directive. RoHS (Restriction Of Hazardous Substances) is an EU directive (2002/95/EG) with the aim of reducing substances damaging to health and the environment in electronic devices.

SHIELDING



To protect against electromagnetic interference such as from mobile devices or wireless networks, cables are shielded with one or more layers (e.g. a wire braid and/or an aluminium coated Mylar film). The impact of the screening is measured in dB and describes the reduction of any interference.

SILVER-PLATING



High frequencies are mainly transmitted on the surface of the conductor (skin effect). As silver is the best conductor, the high frequencies are transmitted better via silver-plated conductors. On audio and speaker cables silver-plated cables boost the high-frequency range. On HDMI connections the silver-plated conductors also ensure optimum signal transfer even on long cables.

SOLID CONDUCTORS



On standard cables the many fine wires are bundled, meaning the electrons can „jump“ from one wire to another. The signals travel for different lengths of time, fast impulses are „braked“. Solid conductors prevent this by providing the same transit times and clear, strong contours. Solid conductors also provide another benefit for digital and video quality: The smooth surface allows the impedance to be precisely adjusted and the high signal frequencies which mainly move on the surface of the conductor can be transmitted perfectly.

S/Z STRANDING

Loudspeaker cables with the wires arranged in the same direction tend to get twisted. This makes laying the cable and installation difficult. Cables with S/Z stranding have wires with opposite stranding to avoid this effect. Laying the cable is then much easier.

TWISTED PAIR



With symmetrically designed cables, two exactly identical wires are used for the initial and return conductors. This counteracts the level of electro-magnetic interference and provides an extremely high immunity to interference. In addition, separate shielding protects the signal.

UHQ-CD



UHQCD stands for Ultimate High Quality Compact Disc and is a development of the Japanese CD replication company Memory-Tech and the Audio Quality CD Company from Hong Kong. Unlike conventional CDs, UHQCDs are not pressed from polycarbonate but cast from a photopolymer and cured with UV light. To protect the softer photopolymer, a further layer of high-purity polycarbonate is applied as scratch-protection. The combination results in a significantly reduced reflection of the laser light inside the CD and an unmatched precise edge transitions between pits and lands of the CD. UHQCDs are 100% compatible with regular CD players. Musically, there is a sound image reminiscent of analog master tapes

ULTRA HD




Ultra high definition TV abbreviated to Ultra HD or UHD. An ultra high-resolution, digital video format introduced in 2013 that incorporates two resolutions (4K and 8K). In Japan, the 8K format is also known as super hi-vision (SHV). The UHD standard introduced in Europe in 2013 has a calculated pixel resolution of 3,840 x 2,160 pixels (4k) and is also known as UHD 2160p.

QUALITY LEVELS


REFERENZ – THE BENCHMARK FOR PICTURE AND SOUND – SIMPLY CAN'T BEAT IT!




EXZELLENZ – FOR THE LOVERS OF PERFECT PICTURE AND SOUND EXPERIENCES.



PREMIUM – PICTURE AND SOUND FOR ADVANCED USERS.



STAR – THE BEST GATEWAY TO THE WORLD OF PICTURE AND SOUND.



REFERENZ – THE BENCHMARK FOR PICTURE AND SOUND – SIMPLY CAN'T BEAT IT!



■ CAT ■ USB ■ POWER

EXZELLENZ – FOR THE LOVERS OF PERFECT PICTURE AND SOUND EXPERIENCES.



■ HDMI ■ ANTENNA CABLE ■ CAT CABLE ■ USB CABLE ■ POWER BAR ■ HDMI SWITCH ■ HDMI WIRELESS



PREMIUM – PICTURE AND SOUND FOR ADVANCED USERS.



■ HDMI ■ HDMI MINI | MICRO ■ VIDEO CABLE ■ ANTENNA CABLE ■ IPLUG ■ CAT ■ USB ■ MHL ADAPTER ■ HDMI SWITCH

STAR – THE BEST GATEWAY TO THE WORLD OF PICTURE AND SOUND.



■ HDMI ■ ANTENNA CABLE ■ YUV ■ S-VIDEO CABLE ■ VIDEO CABLE ■ HDMI SWITCH ■ DAC






100 METER

PROFESSIONAL HDMI CABLE
WITH OPTICAL FIBRE | ARMoured

Professional HDMI cable with fibre optic technology for data rates of up to 18 Gbps with a transmission distance of up to 100 m. The cable therefore supports high-resolution 4K formats with 50 or 60 Hz, 4:4:4 chroma subsampling as well as HDR, and is the solution for connecting devices with an HDMI 2.0 interface over large distances. Thanks to the solid armouring made of a steel helix and Kevlar threads, the cable is very resistant and can withstand tensile loads of up to 100 kg and even 200 kg for a short time. In addition, the solid metal connectors are protected by a plastic sleeve with a screw cap during transport and assembly/disassembly. The cable is therefore suitable for rough use with recurring assembly and disassembly cycles, e.g. in show and stage applications.

Important: Due to the electronics in the plugs, the running direction of this cable must be observed!

Special feature: Reinforcement made of Stend coil and Kevlar threads





ITEM NO		LENGTH	MOC Kč S DPH
009244001	HDMI 2.0 optical fibre 24 Gbps	1 m	6.545
009244002	HDMI 2.0 optical fibre 24 Gbps	2 m	7.082
009244003	HDMI 2.0 optical fibre 24 Gbps	3 m	7.297
009244005	HDMI 2.0 optical fibre 24 Gbps	5 m	8.155
009244008	HDMI 2.0 optical fibre 24 Gbps	8 m	9.335
009244010	HDMI 2.0 optical fibre 24 Gbps	10 m	9.872
009244015	HDMI 2.0 optical fibre 24 Gbps	15 m	11.589
009244020	HDMI 2.0 optical fibre 24 Gbps	20 m	12.125
009244030	HDMI 2.0 optical fibre 24 Gbps	30 m	14.379
009244050	HDMI 2.0 optical fibre 24 Gbps	50 m	18.349
009244070	HDMI 2.0 optical fibre 24 Gbps	70 m	22.641
009244100	HDMI 2.0 optical fibre 24 Gbps	100 m	27.684



KEY-FEATURES

- Fibre optic technology
- Robust design
- Reinforcement made of a steel helix and Kevlar threads
- Plastic sleeve with screw cover to protect the plugs
- Supports HDMI 2.0B up to 24 Gbps
- Supports HDCP 2.2
- Supports EDID
- Supports High Dynamic Range (HDR)
- Supports 4K@50/60 Hz 4:4:4 up to 100 m
- Solid metal connectors
- Plug & play
- Power supply via the HDMI interface
- Low power consumption (<0.25 watts)
- No separate power supply unit required
- Transmission direction marked
- Cable diameter: approx. 5.8 mm
- CE, REACH, RoHS compliant


HDMI CABLE

PROFESSIONAL HDMI 2.0 OPTICAL FIBRE CABLE

EXZELLENZ



INAKUSTIK PROFI HDMI LWL € 440+
Testurteil: überragend
 Preis/Leistung: befriedigend
 VIDEO Magazin | 12-2017



ITEM NO	LENGTH	MOC KČ S DPH
009241001	HDMI 2.0 optical fibre 24 Gbps	1m 5.043
009241002	HDMI 2.0 optical fibre 24 Gbps	2m 5.365
009241003	HDMI 2.0 optical fibre 24 Gbps	3m 5.902
009241005	HDMI 2.0 optical fibre 24 Gbps	5m 6.545
009241008	HDMI 2.0 optical fibre 24 Gbps	8m 7.082
009241010	HDMI 2.0 optical fibre 24 Gbps	10m 7.619
009241015	HDMI 2.0 optical fibre 24 Gbps	15m 8.799
009241020	HDMI 2.0 optical fibre 24 Gbps	20m 9.013
009241030	HDMI 2.0 optical fibre 24 Gbps	30m 10.194
009241050	HDMI 2.0 optical fibre 24 Gbps	50m 12.662
009241070	HDMI 2.0 optical fibre 24 Gbps	70m 14.915
009241100	HDMI 2.0 optical fibre 24 Gbps	100m 17.490

PROFESSIONAL HDMI-MICRO 2.0 OPTICAL FIBRE CABLE

EXZELLENZ



ITEM NO	LENGTH	MOC KČ S DPH
0092431010	HDMI 2.0 optical fibre 24 Gbps *	10m 9.335
0092431015	HDMI 2.0 optical fibre 24 Gbps *	15m 10.194
0092431020	HDMI 2.0 optical fibre 24 Gbps *	20m 10.730
0092431030	HDMI 2.0 optical fibre 24 Gbps *	30m 11.911
0092431050	HDMI 2.0 optical fibre 24 Gbps *	50m 14.164
0092431070	HDMI 2.0 optical fibre 24 Gbps *	70m 16.954
0092431100	HDMI 2.0 optical fibre 24 Gbps *	100m 19.529
0092432010	HDMI 2.0 optical fibre 24 Gbps **	10m 9.872
0092432015	HDMI 2.0 optical fibre 24 Gbps **	15m 10.730
0092432020	HDMI 2.0 optical fibre 24 Gbps **	20m 11.267
0092432030	HDMI 2.0 optical fibre 24 Gbps **	30m 12.447
0092432050	HDMI 2.0 optical fibre 24 Gbps **	50m 14.701
0092432070	HDMI 2.0 optical fibre 24 Gbps **	70m 17.490
0092432100	HDMI 2.0 optical fibre 24 Gbps **	100m 20.066

* 2 x adapter HDMI-D -> HDMI-A
 ** 1 x adapter HDMI-D -> HDMI-A | 1 x adapter HDMI-D -> DVI-D

HIGH SPEED HDMI CABLE WITH ETHERNET

EXZELLENZ



ITEM NO	LENGTH	MOC KČ S DPH
0062443015	High Speed HDMI <> High Speed HDMI	1,5m 1.985
006244303	High Speed HDMI <> High Speed HDMI	3,0m 2.848
006244305	High Speed HDMI <> High Speed HDMI	5,0m 4.429
0062443075	High Speed HDMI <> High Speed HDMI	7,5m 7.623
006244310	High Speed HDMI <> High Speed HDMI	10,0m 8.888
006244312	High Speed HDMI <> High Speed HDMI	12,5m 10.183
006244315	High Speed HDMI <> High Speed HDMI	15,0m 11.477

HIGH SPEED HDMI CABLE WITH ETHERNET

PREMIUM



ITEM NO	LENGTH	MOC KČ S DPH
00423007	High Speed HDMI <> High Speed HDMI	0,75m 805
00423015	High Speed HDMI <> High Speed HDMI	1,5m 970
0042302	High Speed HDMI <> High Speed HDMI	2,0m 1.035
0042303	High Speed HDMI <> High Speed HDMI	3,0m 1.156
0042305	High Speed HDMI <> High Speed HDMI	5,0m 1.469
0042308	Standard HDMI <> Standard HDMI	8,0m 2.074
0042310	Standard HDMI <> Standard HDMI	10,0m 3.164



HIGH SPEED HDMI CABLE WITH ETHERNET | „PIGGYBACK“



ARC AUDIO RETURN CHANNEL	ABSCHIRMUNG SHIELDING	ADDITIONAL COLOR SPACE	DEEP COLOR	OFC COPPER HÖCHSTEN HIGH PURITY	
HDCP 2.2 COMPATIBLE	HDR-SUPPORT High Dynamic Range	CEC-HDPC EDID COMPATIBLE	smartTV COMPATIBLE	3D	
VERZINNT TIN PLATED	X.V. COLOR	HD AUDIO	RoHS Compliant		

ITEM NO		LENGTH	MOC KČ S DPH
00425015	High Speed HDMI <> High Speed HDMI	1,5m	946
0042502	High Speed HDMI <> High Speed HDMI	2,0m	1.003
0042503	High Speed HDMI <> High Speed HDMI	3,0m	1.145
0042505	High Speed HDMI <> High Speed HDMI	5,0m	1.469
0042508	Standard HDMI <> Standard HDMI	8,0m	2.019

PROFESSIONAL HDMI CABLE



High-quality, 3 fold shielded HDMI cable with stable and compact HDMI plugs (approx. 19.5x11.0x33.0 mm incl. kink protection) for professional installation. Item check on the basis of the HDMI1.4 or HDMI2.0 specifications. Construction fully compliant to CE and RoHS regulation.

- **0,75m - 5m:** HDMI2.0 Cable
- Data rate: 18 Gbps
- Supports 4K60Hz 4:4:4 HDR
- AWG28 Cable
- Diameter: 7mm
- **8,0m - 10,0m:** HDMI1.4 Cable
- Data rate: 10.2 Gbps
- Supports 4K30Hz 4:4:4 bzw. 4K60Hz 4:2:2
- AWG26 Cable
- Diameter: 8mm

ITEM NO		LENGTH	MOC KČ S DPH
0092420075	High Speed HDMI <> High Speed HDMI	0,75m	402
009242015	High Speed HDMI <> High Speed HDMI	1,5m	460
00924203	High Speed HDMI <> High Speed HDMI	3,0m	575
00924205	High Speed HDMI <> High Speed HDMI	5,0m	719
00924208	Standard HDMI <> Standard HDMI	8,0m	1.412
00924210	Standard HDMI <> Standard HDMI	10,0m	1.596

STANDARD MINI HDMI CABLE | XS



ARC AUDIO RETURN CHANNEL	ABSCHIRMUNG SHIELDING	3D	DEEP COLOR	CEC-HDPC KOMPATIBEL	FULL HD 1080p	OFC COPPER HÖCHSTEN HIGH PURITY
VERZINNT TIN PLATED	X.V. COLOR	ADDITIONAL COLOR SPACE	smartTV COMPATIBLE	RoHS Compliant		

ITEM NO		LENGTH	MOC KČ S DPH
0042462015	Standard HDMI <> HDMI Mini C	1,5m	643
004246203	Standard HDMI <> HDMI Mini C active	3,0m	1.133
004246205	Standard HDMI <> HDMI Mini C active	5,0m	1.470
0042463015	Standard HDMI <> HDMI Micro D	1,5m	643
004246303	Standard HDMI <> HDMI Micro D active	3,0m	1.159
004246305	Standard HDMI <> HDMI Micro D active	5,0m	1.470

- ultra thin (3,6mm)
- active chip (3m/5m)
- highly flexible

STANDARD MINI HDMI CABLE



ARC AUDIO RETURN CHANNEL	ABSCHIRMUNG SHIELDING	3D	ADDITIONAL COLOR SPACE	DEEP COLOR	CEC-HDPC EDID COMPATIBLE	OFC COPPER HÖCHSTEN HIGH PURITY
X.V. COLOR	smartTV COMPATIBLE	RoHS Compliant	FULL HD 1080p			

ITEM NO		LENGTH	MOC KČ S DPH
00423215	Standard HDMI <> HDMI Mini C	1,5m	1.399
0042323	Standard HDMI <> HDMI Mini C	3,0m	1.695
00423307	Standard HDMI <> HDMI Micro D	0,75m	862
00423235	Standard HDMI <> HDMI Micro D	1,5m	1.023



HDMI CABLE

HIGH SPEED HDMI CABLE WITH ETHERNET




ITEM NO		LENGTH	MOC Kč S DPH
00324507	High Speed HDMI <=> High Speed HDMI	0,75m	338
00324515	High Speed HDMI <=> High Speed HDMI	1,5m	409
00324530	High Speed HDMI <=> High Speed HDMI	3,0m	523
00324550	Standard HDMI <=> Standard HDMI	5,0m	805
00324575	Standard HDMI <=> Standard HDMI	7,5m	1.072
003245100	Standard HDMI <=> Standard HDMI	10,0m	1.241

HDMI WIRELESS

WIRELESS HDMI KIT



- Additional HDMI output on the transmitter
- Transmission up to 30m
- WiFi 5 GHz band
- 128-/256-bit encryption
- Compact design
- Power supply via Micro USB socket
- Latency < 0.5 s
- Dimensions: approx. 85 x 83 x 14mm
- Weight: approx. 400 g (set)



ITEM NO		UNIT	MOC Kč S DPH
00912003	Exzellenz Wireless HDMI Kit	1 Set	18.365

HDMI SWITCH

HDMI MATRIX 4 X 2 HIGH SPEED | SP-DIF | 4K



- EDID Generator
- Bandwidth: 10.2 Gbps (340 MHz)
- EDID generator
- Digital audio output
- HDMI input on the front for mobile devices
- HDCP 2.0- compatible
- Deep Color multi-bit
- Optical and coaxial S/P-DIF audio output in parallel to output A
- Remote control
- Eight different EDID modes

ITEM NO		UNIT	MOC Kč S DPH
0062450424	HDMI Matrix 4x2 High Speed SP-DIF 4k	1 Set	8.061

HDMI SWITCH 3 > 1 HIGH SPEED



- Supports uncompressed audio formats like LPCM
- Supports compressed audio formats such as DTS, Dolby Digital
- Supports HD audio formats such as DTS-HD or Dolby True HD
- Plug & Play
- Weight: 100 g
- Compact size (80 x 50 x 20 mm)

ITEM NO		UNIT	MOC Kč S DPH
0042450313	HDMI Switch 3 > 1 High Speed 4k HDMI 2.0	1 Set	3.217



HDMI SWITCH 4 > 1 HIGH SPEED | MHL



The inputs can be switched directly on the device or using the remote control supplied with it. PIP (picture-in-picture) function is provided for easier use. It shows a preview of all the connected sources on the TV or projector.



ITEM NO	UNIT	MOC KČ S DPH
0042450413	HDMI Switch 4 >1 High Speed MHL	1 Set 4.030

HDMI SWITCH 4 > 1 HIGH SPEED



- EDID management (Extended Display Identification Data)
- LED display
- Operated from the device or by remote control
- 24c gold-plated contacts
- Dimensions: 187x79x30 mm

ITEM NO	UNIT	MOC KČ S DPH
0042450412	HDMI Switch 4 > 1 High Speed	1 Set 3.914

MHL-HDMI SWITCH 3 -> 1



- 1 MHL and 3 HDMI inputs
- Range up to 750MHz / 7,5Gbps (HDMI)

ITEM NO	UNIT	MOC KČ S DPH
00424505	HDMI-MHL- Switch 3 >1	1 Set 4.668

HDMI SWITCH 3 >1 HIGH SPEED



- Output with HDMI cable (50 cm)
- Automatic switching
- Downwardly compatible
- Supports uncompressed audio such as LPCM
- Supports compressed audio such as DTS Digital, Dolby Digital
- Supports HD audio formats such as DTS-HD and Dolby True HD

ITEM NO	UNIT	MOC KČ S DPH
0032450314	HDMI Switch 3 >1 High Speed 4k HDMI 2.0	1 Set 2.052




HDMI SPLITTER 1 >2 HIGH SPEED



- Supports uncompressed audio formats like LPCM
- Supports compressed audio formats such as DTS, Dolby Digital
- Supports HD audio formats such as DTS-HD or Dolby True HD
- Plug & Play
- Compact size (80 x 50 x 20 mm)
- Weight: 100 g

ITEM NO	UNIT	MOC KČ S DPH
004245012	HDMI Splitter 1 > 2 High Speed 4K HDMI 2.0	1 Set 4.627

HDMI SPLITTER 1->2 SCALER HIGH SPEED



ITEM NO	UNIT	MOC KČ S DPH
0042451142	HDMI Splitter 1 > 2 Scaler High Speed	1 Set 5.936

HDMI SPLITTER 1 -> 8 HIGH SPEED



- Data rate: 10,2 Gbps
- 230VAC respectively 5V / 12W
- 257 x 25 x 120mm
- Cable length IN: 20m; OUT: 20m

ITEM NO	UNIT	MOC KČ S DPH
004245118	HDMI Splitter 1 > 8 High Speed	1 Set 11.589

HDMI SPLITTER 1 -> 2 HIGH SPEED



- Data rate: 3 x 2,25 Gbps / 225 MHz
- 230VAC respectively 5V or via HDMI
- 63 x 18 x 54mm
- Cable length OUT: 20m

ITEM NO	UNIT	MOC KČ S DPH
003247012	HDMI Splitter 1 > 2 High Speed	1 Set 3.197



UHD ANTENNA CABLE
120 DB



ITEM NO		LENGTH	MOC KČ S DPH
0062630098	On Spool Price/m	from 1m	288
006263015	Coax (m) > Coax (f)	1,5m	1.467
00626303	Coax (m) > Coax (f)	3,0m	1.725
00626305	Coax (m) > Coax (f)	5,0m	2.215
006263075	Coax (m) > Coax (f)	7,5m	3.481
00626310	Coax (m) > Coax (f)	10,0m	3.941
006264015	F-Plug	1,5m	1.669
00626403	F-Plug	3,0m	1.898
00626405	F-Plug	5,0m	2.510

HDTV ANTENNA CABLE A++
DIN EN 50117-2-4 | 120 DB



ITEM NO		UNIT	MOC KČ S DPH
006260036	Professional Antenna cable A++ Price/m	250m	55
00652123	Professional F-Plug	Bulk	49
00652124	Coax-Tool	Bulk	833

- Recommended and approved by Deutschen Telekom
- Suitable for return channel (Internet)
- Expanded PE dielectric
- Inner conductor: 1.0 mm bare copper
- Exterior diameter: 6.8 mm +/- 0.2 mm
- Bonded film -> suitable for compression connectors etc.
- Small bending radius (50 mm)
- Capacitance: (pF/m) 55
- Velocity factor (v/c): 0.85
- Low signal attenuation
- Weight: 52 kg/km
- Descending metre imprint

HDTV ANTENNA CABLE
120 DB | HALOGEN FREE



ITEM NO		UNIT	MOC KČ S DPH
006260006	HDTV Antenna cable halogen free Price/m	100m	91

- Cable diameter: 7,0 mm

HDTV ANTENNA CABLE
120 DB



ITEM NO		UNIT	MOC KČ S DPH
00626000	Exzellenz HDTV Antenna cable Price/m	100m	89
0062600098	Exzellenz HDTV Antenna cable Price/m	500m	89

- Cable diameter: 7,0 mm



HDTV ANTENNA CABLE
100 DB



ITEM NO		LENGTH	MOC Kč S DPH
004261015	Coax (m) > Coax (f)	1,5m	607
00426103	Coax (m) > Coax (f)	3,0m	706
00426105	Coax (m) > Coax (f)	5,0m	848
004261075	Coax (m) > Coax (f)	7,5m	1.044
00426110	Coax (m) > Coax (f)	10,0m	1.230
004262015	F-Plug	1,5m	663
00426203	F-Plug	3,0m	749
00426205	F-Plug	5,0m	905
004262075	F-Plug	7,5m	1.087
00426210	F-Plug	10,0m	1.243

HDTV ANTENNA CABLE
100 DB | 90°



ITEM NO		LENGTH	MOC Kč S DPH
004263015	Coax (m) > Coax (f) 90°	1,5m	607
00426303	Coax (m) > Coax (f) 90°	3,0m	706
00426305	Coax (m) > Coax (f) 90°	5,0m	848
004263075	Coax (m) > Coax (f) 90°	7,5m	1.099
00426310	Coax (m) > Coax (f) 90°	10,0m	1.230
004264015	F-Plug 90°	1,5m	761
00426405	F-Plug 90°	5,0m	1.062
00426410	F-Plug 90°	10,0m	1.482

HDTV ANTENNA CABLE
90 DB



ITEM NO		LENGTH	MOC Kč S DPH
003263015	Coax (m) > Coax (f)	1,5m	343
00326303	Coax (m) > Coax (f)	3,0m	382
00326305	Coax (m) > Coax (f)	5,0m	504
003264015	F-Plug	1,5m	494
00326403	F-Plug	3,0m	578
00326405	F-Plug	5,0m	678

ANTENNA PLUG



New high end antenna plug made of solid metal with gold plated contacts. Simple, safe and time-saving „twist-on assembly“.


- suitable e.g. for the Excellence Antenna Cable Art.-No. : 0062630098
- For 7.0 mm cable extension

ITEM NO		UNIT	MOC Kč S DPH
009250005	Exzellenz Antenna plug Coax (m)	bulk	209
006990081	Exzellenz Antenna plug Coax (f)	bulk	209
006990091	Exzellenz Antenna plug F-Plug	bulk	235




VIDEO CABLE

VIDEO CABLE



ITEM NO	LENGTH	MOC KČ S DPH
0041401	1,0m	649
0041403	3,0m	1.044

VIDEO CABLE



ITEM NO	LENGTH	MOC KČ S DPH
00316207	0,75m	279
00316215	1,5m	324
0031623	3,0m	418
0031625	5,0m	539
00316275	7,5m	746
00316310	10m	879
00316315	15m	1.145

S-VIDEO CABLE

S-VIDEO CABLE



ITEM NO	LENGTH	MOC KČ S DPH
01051101	1,0m	477
01051102	2,0m	630
01051103	3,0m	778
01051105	5,0m	1.071
01051110	10,0m	1.825

S-VIDEO CABLE



ITEM NO	LENGTH	MOC KČ S DPH
0101175 Price/m	100m	64
01011751	1,0m	269
01011753	3,0m	392
01011755	5,0m	525
010117575	7,5m	662
010117510	10,0m	829
010117515	15,0m	1.125

DISPLAYPORT

DISPLAYPORT



DisplayPort is an interface defined by the VESA (Video Electronics Standards Association). The Excellence DisplayPort cable is fully-wired and has 4 data ducts. Each data duct is designed for a bandwidth of 2.7 Gbit/s. It handles the highest specified data rate of 10.8 Gbit/s.

ITEM NO	LENGTH	MOC KČ S DPH
00628015	1,5m	1.769
0062803	3,0m	2.360

SCART CABLE

SCART



ITEM NO	LENGTH	MOC KČ S DPH
0042201	1,0m	696
0042203	3,0m	1.287
0042205	5,0m	1.973
00422075	7,5m	2.789


YUV CABLE

YUV



ITEM NO	LENGTH	MOC KČ S DPH
006202007	0,75m	1.048
00620203	3,0m	2.066
00620205	5,0m	2.924
006202075	7,5m	3.970
00620210	10,0m	5.070
00620212	12,0m	5.955
00620215	15,0m	7.350

YUV



ITEM NO	LENGTH	MOC KČ S DPH
00320007	0,75m	503
00320015	1,5m	724
0032003	3,0m	986
01012755	5,0m	1.340
010127575	7,5m	1.769
010127510	10,0m	2.220
010127515	15,0m	3.089



HDMI 2.0 REPEATER

EXCELLENZ



- Supports 4K@60Hz 4:4:4 up to 25m
- 4K@30Hz up to 30m
- 1080p up to 50m
- Supports HDCP2.2 & 1.4
- downwardly compatible to HDMI1.4 & 1.3
- No separate power supply required

ITEM NO	UNIT	MOC KČ S DPH
00912004	1 pc	2.746

HDMI <> DVI ADAPTER

PREMIUM



- HDMI (m) > DVI-D (w)

ITEM NO	UNIT	MOC KČ S DPH
0083241	1 pc	1.059

HDMI ANGLE ADAPTER 90°

PREMIUM



ITEM NO	UNIT	MOC KČ S DPH
0090201002	1 pc	348

HDMI ANGLE ADAPTER 360°

PREMIUM



This premium HDMI adapter can be bent in any direction you wish. It is ideal for connecting an HDMI cable in narrow spaces, for example behind an LED-TV on the wall, or other components. With gold-plated contacts.

ITEM NO	UNIT	MOC KČ S DPH
0045217	1 pc	563

HDMI MICRO ADAPTER

PREMIUM



This HDMI adapter allows mobile devices, such as cameras with a micro HDMI connector, to be linked up to a TV using a standard HDMI cable. With gold-plated contacts.

ITEM NO	UNIT	MOC KČ S DPH
0045218	1 pc	456

ANTENNA PLUGS

EXCELLENZ



New high end antenna plug made of solid metal with gold plated contacts. Simple, safe and time- saving „twist-on assembly“.

- suitable e.g. for the Excellence Antenna Cable Art.-No. : 0062630098
- For 7.0 mm cable extension

ITEM NO		MOC KČ S DPH
006990071	Coax (m)	209
006990081	Coax (f)	209
006990091	F-Plug	235




DISPLAYPORT ADAPTER



- 15cm cable length
- Supports Mini DP 1.1
- Supports 1080p
- Supports 225MHz / 2,25Gbps (6,75Gbps total)
- Supports 36 Bit deep color (3 x 12 Bit)
- Power supply over Mini DisplayPort

ITEM NO	UNIT	MOC KČ S DPH
006285003	1 pc	1.263

S-VIDEO PLUG



ITEM NO	UNIT	MOC KČ S DPH
0083409	bulk	814

SCART ADAPTER



- Scart <-> RCA/S-Video; switchable

ITEM NO	UNIT	MOC KČ S DPH
008323	1 pc	494

PROFESSIONAL ANTENNA PLUG



- Professional F-Plug
- Very short and space-saving design
- Easy mounting without screws or crimping
- Suitable for cable #006260036 or other 4.9 / 6.8mm coaxial cable with bonded foil

- Coax tool: suitable for cable #006260036 and plug #00652123
- Coax tool: with wrench to tighten the plug on the devices.

ITEM NO	UNIT	MOC KČ S DPH
00652123	Bulk Plug	49
00652124	Bulk Tool	833

ANTENNA PLUG



- Exzellenz antenna plug for antenna cable #0062630098
- For 7.0 mm cable extension
- Simple, safe and time- saving „twist-on assembly“.

ITEM NO	UNIT	MOC KČ S DPH
00652104	Coax (f)	160
00652102	Coax (m)	160
00652122	F-Plug	160

SCREEN CLEANER



Environment-friendly special and biodegradable cleaner for TFT/LCD/PLASMA screens, PDA screens and all treated and untreated glass surfaces. Spray on a cloth and clean. Wipe dry with a lint-free dry cloth. Before application, please refer to the manufacturer's cleaning instructions. Contains no alcohol (not flammable). Contents: 250 ml TFT/LCD/PLASMA Screen Cleaner + 1 Vileda Micro-fibre cloth (size 38 x 40 mm)

- 250 ml; Vileda micro-fiber cloth

ITEM NO	UNIT	MOC KČ S DPH
006528001	1 pc	621

SCREEN CLEANER



The surface of TFT | LCD | PLASMA displays consists of a sensitive plastic that can be easily scratched. Most flat-panel displays are also coated with an anti-reflective coating. This cleaner guarantees effective and gentle cleaning of the screen surfaces. Simply spray the screen cleaner onto the included microfibre cloth and clean the display. The cleaner is suitable for maintenance of flat-panel displays, TFT displays, digital cameras, smart phones, tablet PCs and laptops.

- 50ml; micro-fiber cloth

ITEM NO	UNIT	MOC KČ S DPH
004528002	1 pc	275

EYEGASSES KIT



The user benefits from exceptional cleaning power. The anti-fogging effect also significantly minimises fogging of the lenses. The lenses are sprayed from both sides with some eyeglasses cleaner and wiped with the included microfibre lens cloth. The eyeglasses cleaner also produces an anti-static, dirt-shedding sealant.

- 50ml; micro-fiber cloth

ITEM NO	UNIT	MOC KČ S DPH
004528003	1 pc	208

LS-803



The little brother of the LS-1203 has an 8-fold multicore design. The tightlypacked PE-Network Jacket holds the wires together and reduces micro-vibrations (High Power Management), which occur in the cable from the changing magnetic fields in the beat of the music. The cable therefore also transmits high level and extreme dynamic peaks with absolute precision. As the frequency rises, the signal increasingly flows on the conductor surface. The higher the frequency, the lower the effective cross-section, and the greater the resistance. The cable sounds „bass-heavy“. The conductors from the Referenz loudspeaker cable have a core made of polyethylene. In this way a circular waveguide is formed and the actual cross-section used is the same for all sound frequencies. The result: a homogeneous, balanced loudspeaker cable with a wide-ranging sound spectrum.

- 8-fold Multicore
- High Speed waveguide technology
- Concentric Copper
- DUO-PE II insulation around each conductor
- High Power Management
- PE-Network Jacket

ITEM NO		LENGTH	MOC KČ S DPH
0077008	Referenz LS-803 On Spool; Price/m	50m	2.682
007700832	Referenz LS-803 BFA; SW	2x3,0m	21.610
0077008321	Referenz LS-803 BFA; SBW	2x3,0m	23.029
007700835	Referenz LS-803 BFA 45°; SW	2x3,0m	23.841
0077008351	Referenz LS-803 BFA 45°; SBW	2x3,0m	26.946
007700833	Referenz LS-803 Spade Lug; SW	2x3,0m	22.320
0077008331	Referenz LS-803 Spade Lug; SBW	2x3,0m	24.303

LS-603



The Referenz LS-603 with its 6-fold multicore design has considerable electrical and tonal characteristics. The large cable section provides an excellent and controlled low frequency response and high efficiency.

- 6-fold Multicore
- High Speed waveguide technology
- Concentric Copper
- DUO-PE II insulation around each conductor
- High Power Management
- PE-Network Jacket

ITEM NO		LENGTH	MOC KČ S DPH
007700632	Referenz LS-603 BFA; SW	2x3,0m	15.593
007700635	Referenz LS-603 BFA 45°; SW	2x3,0m	17.295
007700633	Referenz LS-603 Spade Lug; SW	2x3,0m	17.250

LS-1102



- Hexa CC-187 Design; 6 x 1,87 mm²
- 3-fold symmetrical design
- 37 wires concentrically stranded per conductor
- DUO-PE II insulation around each conductor
- Low induction for homogeneous reproduction
- PE-Network Jacket

ITEM NO		LENGTH	MOC KČ S DPH
00781102	Referenz LS-1102; Price/m	50m	1.031

LS-1002



- Quatro CC-297 Design; 4 x 2,97 mm²
- Double-symmetrical design
- 37 wires concentrically stranded per conductor
- DUO-PE II insulation around each conductor
- Low induction for homogeneous reproduction
- PE-Network Jacket

ITEM NO		LENGTH	MOC KČ S DPH
00781002	Referenz LS-1002; Price/m	50m	776



LS-602



LS-502



The Referenz LS-602 is a double-symmetrical cable design. The high density reduces the inductance factor to the benefit of the middle and high-frequency ranges.

- Quatro CC-187 Design; 4 x 1,87 mm²
- Double-symmetrical design
- 37 wires concentrically stranded per conductor
- DUO-PE II insulation around each conductor
- Low induction for homogeneous reproduction
- PE-Network Jacket

The LS-502 has two symmetrically arranged strands, each containing 37 concentrically stranded wires. The thick wires demonstrate its class even when used with high-performance systems. AUDIO (LS-502): "... the sound is so warm, just as you would expect from in-akustik Referenz – direct, honest, straightforward."

- Duo CC-297 Design; 2 x 2,97 mm²
- Symmetrical design
- 37 wires concentrically stranded per conductor
- DUO-PE II insulation around each conductor
- Low induction for homogeneous reproduction
- PE-Network Jacket

ITEM NO	LENGTH	MOC KČ S DPH
00780602 Referenz LS-602; Price/m	50m	578

ITEM NO	LENGTH	MOC KČ S DPH
00780502 Referenz LS-502; Price/m	50m	472

LS-40



LS-20



The speaker cable Exzellenz LS-40 is based on the technical principles of the legendary Referenz Series. It consists of four twisted wires. The PE Network Jacket holds the wires tightly together. The insulation is made of high quality, solid PE (Polyethylene). The elaborately finished cable offers a powerful, dynamic and very clear sound. The 4-wire construction allows the use as a single bi-wire cable.


- 2 x 5,0mm² (4 x 2,5mm²)
- Low-loss PE insulation
- Copper wires with 50 x 0.25 mm strands
- Additional support elements made of PE
- Double symmetrical, 4-wire construction
- Low induction for homogeneous high-frequency reproduction

Das Speaker Cable Exzellenz LS-20 basiert auf den technischen Grundlagen der legendären Referenz-Serie. Es besteht aus zwei miteinander verseilten Adern. Das PE Network Jacket hält die Adern kompakt zusammen. Die Kupferlitzen sind mit hochwertigem, massivem PE (Polyethylen) isoliert. Das aufwendig verarbeitete Cable besticht durch einen straffen, dynamischen und sehr klaren Klang.

- 2 x 2,5mm²
- Low-loss PE insulation
- Copper wires with 50 x 0.25 mm strands
- Additional support elements made of PE
- Symmetrical, 2-wire construction
- Low induction for homogeneous high-frequency reproduction


ITEM NO	LENGTH	MOC KČ S DPH
00602740 Exzellenz LS-40 2,5mm ² ; Price/m	50m	482
00602743 Exzellenz LS-40 2,5mm ² ; Easy-Plug SW	2x3,0m	5.642
006027431 Exzellenz LS-40 2,5mm ² ; Easy-Plug SBW	2x3,0m	5.755

ITEM NO	LENGTH	MOC KČ S DPH
00602720 Exzellenz LS-20 2,5mm ² ; Price/m	50m	321
00602723 Exzellenz LS-20 2,5mm ² ; Easy-Plug SW	2x3,0m	5.229





SPEAKER CABLE MSR




- MSR®-Technology
- Pure grade (oxygen free) copper
- Finest stranded (diameter 0,07 mm)
- 1302 /2100 / 3150 strands
- Highly flexible!



Cable with MSR-Technology with regulated current distribution

ATMOS AIR



- Rich in sound concentric copper conductor
- Loss-free air insulation
- Precise, concentric conductor design
- Additional air dielectric
- Plus/minus recognition

SPEAKER CABLE SILVER



- High frequency range optimised, silver-plated concentric copper conductor (15 g/kg)
- Low-loss PE insulation
- Additional PE dielectric
- Finest 0.07 mm wire design
- Opposing S/Z stranding (easy to install)

ITEM NO		LENGTH	MOC KČ S DPH
0060242	MSR 2,5mm ²	100m	181
0060244	MSR 4,0mm ²	80m	263
0060246	MSR 6,0mm ²	50m	324

ITEM NO		LENGTH	MOC KČ S DPH
0060223	Atmos Air 2,97mm ²	50m	208

ITEM NO		LENGTH	MOC KČ S DPH
0060214	LS Silver 4,0mm ²	60m	618
0060212	LS Silver 2,5mm ²	70 m	403

SPEAKER CABLE FLAT



- Finely-stranded: 0.10 mm (1.5 mm²) / 0.07 mm (2.5 mm²)
- "Invisible" to lay under carpets or behind skirting boards
- Flat, compact design
- Plus/minus recognition

SPEAKER CABLE SILVER



- High frequency range optimised, silver-plated concentric copper conductor (5 g/kg)
- Opposing S/Z stranding (easy to install)
- Resistant insulation
- Plus/minus recognition

SPEAKER CABLE CU



- Finely-stranded: 0.15 mm wire design
- Opposing S/Z stranding (easy to install)
- Resistant insulation
- Plus/minus recognition

ITEM NO		LENGTH	MOC KČ S DPH
00402326	LS Flat 2,5mm ²	130m	163

ITEM NO		LENGTH	MOC KČ S DPH
0040214	LS Silver 4,0mm ²	100m	252
0040212	LS Silver 2,5mm ²	120m	164
0040211	LS Silver 1,5mm ²	180m	107

ITEM NO		LENGTH	MOC KČ S DPH
004024	4,0mm ² Trans	100m	181
0040246	4,0mm ² White	100m	181
00402498	4,0mm ² Trans	400m	181
004022	2,5mm ² Trans	120m	112
00402298	2,5mm ² Trans	500m	112
004021	1,5mm ² Trans	180m	73



SPEAKER CABLE
FLAME RETARDANT



- Cross section: 1,5mm² & 2,5mm²
- Structure 30 x 0.25 mm CU & 50 x 0.25 mm CU
- High flexibility due to transposed wires
- Extruded sheathing simplifies removal of the insulation
- Insulation: PVC
- Diameter: approx. 6,5mm & 9.5mm
- Flame-retardant, conforms to IEC 60332-1-2 Class E
- Conforms to RoHS Directive 2011/65/EU



ITEM NO	LENGTH	MOC KČ S DPH
00402709	2x1,5mm ²	150m 95
00402718	2x2,5mm ²	100m 138

SPEAKER CABLE CU



- Universal speaker cable for any application
- Flexible and easy to install with opposing S/Z stranding
- Plus/minus recognition

ITEM NO	LENGTH	MOC KČ S DPH
003022	2,5mm ² Trans	150m 92
00302298	2,5mm ² Trans	500m 92
0030226	2,5mm ² White	150m 92
003021	1,5mm ² Trans	200m 59
00302198	1,5mm ² Trans	1000m 59
0030216	1,5mm ² Weiß	200m 59
0030218	1,5mm ² Anthracite	200m 59
003020	0,75mm ² Trans	400m 32
0030206	0,75mm ² White	400m 32

CABLE UNWINDER



An innovative solo unwinder for dealing with metre goods professionally:

- Allows metre goods to be stored easily on the peg-board in any combination with any number of spools.
- Uses the sales area extremely efficiently.
- Ideal for secondary placement.
- Easy to handle when replacing spools.
- Useful winding spools for convenient use

ITEM NO	UNIT	MOC KČ S DPH
0102711	Cable Unwinder	1 pc -

SPEAKER CABLE CU



- Finely-stranded: 0.15 mm wire design
- Opposing S/Z stranding (easy to install)
- Resistant insulation
- Plus/minus recognition

ITEM NO	LENGTH	MOC KČ S DPH
00402410	4,0mm ² Trans	10m 2.159

SPECIAL EDITION



- Flexible, easy to install
- Universal speaker cable for any application
- Plus/minus recognition
- Mini spool with pamel for easy handling*

ITEM NO	LENGTH	MOC KČ S DPH
01002430	1,5mm ² Trans	30m 1.738
01002436	1,5mm ² White	30m 1.738
010024369	1,5mm ² White*	30m 1.776
01004425	2,5mm ² Trans	25m 2.348

CABLE RING



- Flexible, easy to install
- Universal speaker cable for any application
- Plus/minus recognition

ITEM NO	LENGTH	MOC KČ S DPH
003020006	0,75mm ² Trans	6m 232
003020010	0,75mm ² Trans	10m 356
003021010	1,5mm ² Trans	10m 602
0030216102	1,5mm ² White	10m 602
003021020	1,5mm ² Trans	20m 1.158
003022010	2,5mm ² Trans	10m 984

BANANA BFA-103

REFERENZ



- Rhodium-coated
- Dimensions: 45 x 15 mm (L x D)
- Cable cross-section: 10 mm²
- Cable diameter: 8.2 mm max.
- Cable diameter: 7,5 mm max (BFA 45°)
- Full-surface contact
- Fully insulated connector with screws

ITEM NO	UNIT	MOC Kč S DPH
00719001	Set of 4	1.985
007891800	bulk	342
0078918011	Set of 4 45°	2.850
007891801	Bulk 45°	575

SCREW TYPE

REFERENZ



The BFA, flexible pin and spade lug adapter all provide several connection options, for instance, if the amplifier or speaker is replaced and different connections are required.

ITEM NO	UNIT	MOC Kč S DPH
00971100	Basic Adapter	127
00789168BW	BFA	192
009711018	Spade Lug	175
009711048	Flexible Pin	158

BANANA BFA

EXZELLENZ



- Dimensions: 45 x 15 mm (L x D)
- Cable cross-section: 6 mm²
- Cable diameter: 8.2 mm max.
- Full-surface contact
- Fully insulated connector with screws
- 24c gold plated or silver plated
- Red/Black or White/Black coding

ITEM NO	UNIT	MOC Kč S DPH
00789169BW	bulk (b/w)	201
008169	bulk (r/b)	215
0081691	Set of 4 (r/b)	905

BANANA BFA

EXZELLENZ



- Cable cross-section: 6 mm²
- Cable diameter: 8.2 mm max.
- Full-surface contact
- 24c gold plated
- Red/Black coding

ITEM NO	UNIT	MOC Kč S DPH
006500021	Set of 4	1.441

BANANA MULTI CONTACT

PREMIUM



- Cable cross-section: up to 16 mm²
- Red/Black coding
- With screw connection
- 24c gold plated

ITEM NO	UNIT	MOC Kč S DPH
008147	bulk	200
0081471	Set of 4	873

BANANA MULTI TIP

PREMIUM



- Cable cross-section: up to 16 mm²
- Red/Black coding
- With soldered connection
- 24c gold plated

ITEM NO	UNIT	MOC Kč S DPH
0081483	bulk; 6mm ²	86
00814831	Set of 4; 6mm ²	403
0081484	bulk; 10mm ²	91
00814841	Set of 4; 10mm ²	403

FLEXIBLE PIN

PREMIUM



- Cable cross-section: up to 6 mm²
- For safe and easy connections on clip terminals
- For crimping or soldering
- 24c gold plated

ITEM NO	UNIT	MOC Kč S DPH
008155	bulk	88
0081551	Set of 4	438

HOLLOW TIP

PREMIUM



- Cable cross-section: 6 mm²
- Full-surface contact
- For crimping or soldering
- 24c gold plated or silver plated

ITEM NO	UNIT	MOC Kč S DPH
008149	bulk	65
0081492	bulk; silver plated	68



SPADE LUG KS-103



- Rhodium-coated
- Spade Lug in one piece
- Cable cross-section: 10 mm²
- Cable diameter: 9.2 mm max.
- Spring-loaded for better contact
- Staged spade lug 8 mm/6 mm

SPADE LUG KS-60



- 24c gold plated contacts
- Cable cross-section: up to 6 mm²
- For crimping or soldering
- Black/White coding
- Staged spade lug 8 mm/6 mm

SPADE LUG



- 24c gold plated contacts
- Cable cross-section: up to 4 mm²
- For crimping or soldering
- Black/Red coding
- Staged spade lug 8 mm/6 mm

SOLDER



RoHS compliant special solder with high silver content. This ensures perfect and corrosion-free connections

ITEM NO	UNIT	MOC KČ S DPH
00719101	Set of 4; 8,2mm	3.102
007890802	bulk; 7,0mm	564
007890800	bulk; 8,2mm	564
007890801	bulk; 9,2mm	564

ITEM NO	UNIT	MOC KČ S DPH
007896	bulk	248

ITEM NO	UNIT	MOC KČ S DPH
00450022	bulk	49

ITEM NO	UNIT	MOC KČ S DPH
010291	bulk	1.254

BI-WIRE JUMPER



High-end bi-wire jumper based on the LS-1603. Fitted with the KS-103 Referenz spade lug or BFA Banana. The rhodium surface treatment is extremely durable. The contact surfaces and the screw connection are manufactured from a single piece, allowing contact resistance to be avoided. The contact surface of the spade, which is slitted on the side, changes to a concave shape when the screw connections are tightened, thus preventing the spade lug from sliding out.

- Length: 20cm; Set of 2

ITEM NO	MOC KČ S DPH
00719302	LS-803; Spade Lug 5.201
00719303	LS-803; BFA 4.248
00719306	LS-1603; Spade Lug 5.434
00719307	LS-1603; BFA 4.469

BI-WIRE JUMPER



High-end bi-wire jumper based on the LS-1002. Fitted with the KS-60 Referenz spade lug (6/8 mm)

- Length: 15cm; Set of 2

ITEM NO	MOC KČ S DPH
00719301	LS-1002; Spade Lug 3.337

NF-803 | RCA & XLR



The audio cable NF-803 from the in-akustik Referenz series convinces with outstanding clarity, precision and accuracy. Two high speed signal conductors provide the signal transport. At the same time, the DUO-PE II insulation and the air-filled PE tubes reduce unwanted capacitance and enable the signal source to work "comfortably". The PE-Network Jacket also prevents micro-vibrations. Another highlight are the Referenz GAP II RCA plugs which take the symmetrical design to the limit.

GAP II RCA-STECKER

This high end plug enables a symmetrical connection to be made up to the terminals of the equipment. Thanks to its two-piece earth ring, this RCA plug has three contacts, exactly like an XLR plug. The screening and negative conductors are only brought together again when at the terminals of the equipment.

HIGH SPEED SIGNALLEITER

The NF-803 has fine stranded signal wires, with each individual wire having a lacquer coating. This coating insulates the wires from each other which creates a larger effective conductor surface. It also prevents eddy currents between the wires. A conductor that can also transmit extremely dynamic signal sequences very quickly and precisely.

ITEM NO		LENGTH	MOC Kč S DPH
007184007	Referenz Audio Cable NF-803 RCA	0,75m	6.697
007184010	Referenz Audio Cable NF-803 RCA	1,0m	7.529
007184015	Referenz Audio Cable NF-803 RCA	1,5m	9.748
0071840073	Referenz Audio Cable NF-803 XLR	0,75	7.996
0071840103	Referenz Audio Cable NF-803 XLR	1,0m	8.830
0071840153	Referenz Audio Cable NF-803 XLR	1,5m	10.512

NF-202 | RCA



Precisely because audio signals are so sensitive, we have equipped our Referenz NF-202 audio cable with some highly-effective technology: optimum DUO-PE II insulation with air-filled PE tubes, an innovative GAP plug, but also in particular an extremely sophisticated, solid conductor made of high-purity OFC copper, which all ensure uniform transit times and crystal-clear signal transmission. The earth and signal conductors are the same size and arranged symmetrically. The PE network jacket prevents micro-vibrations.

- Symmetrical design (two solid conductors)
- PE network jacket against micro-vibrations
- Wires made of high-purity OFC copper
- Foil shielding and weave sleeve made of OFC copper
- DUO-PE II insulation around each conductor
- Polyethylene tubes filled with air (best insulator) reduce unwanted capacitance

ITEM NO		LENGTH	MOC Kč S DPH
0078202	Referenz Audio Cable NF-202 RCA; Price/m	50m	794
00718106	Referenz Audio Cable NF-202 RCA	0,6m	5.737
00718112	Referenz Audio Cable NF-202 RCA	1,2m	6.302

EXZELLENZ | RCA



- 2 fold coaxial construction | Double Mono Design
- 2 x 2 fold shielding
- Silver plated
- Solide conductor
- High-purity OFC copper
- Low-loss PE insulation
- 24k gold plated contacts

ITEM NO		LENGTH	MOC Kč S DPH
0060410098	Exzellenz Audio Cable Coax Mono Price/m	from 1,0m	784
006041007	Exzellenz Audio Cable RCA	0,75m	2.877
006041015	Exzellenz Audio Cable RCA	1,5m	3.625
00604103	Exzellenz Audio Cable RCA	3,0m	5.206

EXZELLENZ | XLR



- Doublesymmetrical Design | Double mono construction
- 2 x 2-fold shielding
- Silver plated
- Very low capacity
- High-purity OFC copper
- Low-loss PE insulation
- 24c gold-plated contacts

ITEM NO		LENGTH	MOC Kč S DPH
0060500098	Exzellenz Audio Cable Sym. Mono Price/m	from 1,0m	863
006050007	Exzellenz Audio Cable XLR	0,75m	4.429
006050015	Exzellenz Audio Cable XLR	1,5m	5.465
00605003	Exzellenz Audio Cable XLR	3,0m	8.227



AUDIO CABLE | RCA



ABSCHIRMUNG SHIELDING
 VERGOLDET GOLD-PLATED
 OFC COPPER HOCHREIN HIGH PURITY
 ((STEREO))
 SYMMETRICAL CONSTRUCTION
 RoHS Compliant

ITEM NO		LENGTH	MOC KČ S DPH
00404007	Premium RCA	0,75m	931
00404015	Premium RCA	1,5m	1.102
0040403	Premium RCA	3,0m	1.406
0040405	Premium RCA	5,0m	1.780

AUDIO CABLE | XLR



ABSCHIRMUNG SHIELDING
 VERGOLDET GOLD-PLATED
 OFC COPPER HOCHREIN HIGH PURITY
 ((STEREO))
 SYMMETRICAL CONSTRUCTION
 RoHS Compliant

ITEM NO		LENGTH	MOC KČ S DPH
00405007	Premium XLR	0,75m	1.501
00405015	Premium XLR	1,5m	1.801
0040503	Premium XLR	3,0m	2.400
0040505	Premium XLR	5,0m	3.000

AUDIO CABLE | RCA



ABSCHIRMUNG SHIELDING
 VERGOLDET GOLD-PLATED
 OFC COPPER HOCHREIN HIGH PURITY
 ((STEREO))
 RoHS Compliant

ITEM NO		LENGTH	MOC KČ S DPH
00304000	On Spool Stereo	50m	130
00304107	Star RCA	0,75m	559
00304115	Star RCA	1,5m	682
0030413	Star RCA	3,0m	905
0030415	Star RCA	5,0m	1.238

SUBWOOFER CABLE


SUB CABLE | MONO



ABSCHIRMUNG SHIELDING 2x2
 2-FACH | 2-GOLD COAXIAL
 VERSILBERT SILVER PLATED
 Massivleiter Solid Conductor
 VERLUSTARME PE-ISOLATION LOW-LOSS PE-ISOLATION
 VERGOLDET GOLD-PLATED
 Metallstecker Solid Metal Plug
 LFE MONO
 OFC COPPER HOCHREIN HIGH PURITY
 TEXTILE JACKET
 RoHS Compliant

ITEM NO		LENGTH	MOC KČ S DPH
0060410098	On Spool Price/m	from 1,0m	784
00604202	Exzellenz Mono-Sub	2,0m	2.244
00604203	Exzellenz Mono-Sub	3,0m	2.733
00604205	Exzellenz Mono-Sub	5,0m	3.768
006042075	Exzellenz Mono-Sub	7,5m	6.040
00604210	Exzellenz Mono-Sub	10,0m	7.623
00604212	Exzellenz Mono-Sub	12,0m	10.010


SUB CABLE | Y-SUB



ABSCHIRMUNG SHIELDING
 VERGOLDET GOLD-PLATED
 OFC COPPER HOCHREIN HIGH PURITY
 RoHS Compliant

ITEM NO		LENGTH	MOC KČ S DPH
0040802	Premium Y-Sub	2,0m	805
0040803	Premium Y-Sub	3,0m	905
0040805	Premium Y-Sub	5,0m	1.087

SUB CABLE | MONO



ABSCHIRMUNG SHIELDING
 VERGOLDET GOLD-PLATED
 OFC COPPER HOCHREIN HIGH PURITY
 RoHS Compliant


ITEM NO		LENGTH	MOC KČ S DPH
00408021	Premium Mono-Sub	2,0m	700
00408031	Premium Mono-Sub	3,0m	824
00408051	Premium Mono-Sub	5,0m	1.071

SUB-CABLE | Y-SUB



ITEM NO		LENGTH	MOC KČ S DPH
0030822	Star Y-Sub	2,0m	494
0030823	Star Y-Sub	3,0m	593
0030825	Star Y-Sub	5,0m	776
00308275	Star Y-Sub	7,5m	960
00308310	Star Y-Sub	10,0m	1.060
00308312	Star Y-Sub	12,0m	1.313

SUB-CABLE | MONO



ITEM NO		LENGTH	MOC KČ S DPH
00308221	Star Mono-Sub	2,0m	392
00308231	Star Mono-Sub	3,0m	454
00308251	Star Mono-Sub	5,0m	576
003082751	Star Mono-Sub	7,5m	833
003083101	Star Mono-Sub	10,0m	991
003083121	Star Mono-Sub	12,0m	1.106

A TASTY SOUND COLLECTION




Tracks as blue as the kind of atmosphere you can only really get through with a good single malt in your hand. Songs from singers and songwriters to savour like fine wine. Relaxing music to unwind with a nice, hot cup of tea. Latin American rhythms. From salsa to Latin jazz – a mix of coffee, Cuba and Caribbean. That is the Tasty Sound Series from in-akustik.

ITEM	TITEL	ITEM	TITEL
0167961	Coffee & Latin	0167965	Champagne & Songs
0167962	Tea & Tones	0167966	Cocktails & Guitars
0167963	Wine & Vocals	0167967	Cigars & Sounds
0167964	Whisky & Blues	0167968	Absinthe & Voices
		0167969	Beer & Rock

DIGITAL COAX


COAX DIGITAL CABLE



The Excellence digital cable has two separately routed shields. This means that the sensitive audio data is optimally protected from external interferences. The digital music signal is precisely transmitted through the silver-plated conductor and the perfectly adapted impedance (Low Jitter). This enables a natural and dynamic sound for high resolution audio formats. The solid 24 carat gold-plated metal connectors constantly ensure maximum contact and minimal contact resistance.

ITEM NO		LENGTH	MOC KČ S DPH
0060410098	Exzellenz Audio Cable Coax Mono Price/m	from 1,0m	784
006044007	Exzellenz Digital Cable	0,75m	1.698
006044015	Exzellenz Digital Cable	1,5m	2.071
00604403	Exzellenz Digital Cable	3,0m	2.848

XLR AES/EBU DIGITAL CABLE



This Excellence digital cable is specially designed for the professional 110 Ohm AES/EBU standard. The symmetrical structure and double shielding minimise interferences and provide the sensitive audio data with the best possible protection. The digital music signal is precisely transmitted through silver-plated conductors and the perfectly adapted impedance (Low Jitter). This enables a natural and dynamic sound especially for high resolution audio formats.

ITEM NO		LENGTH	MOC KČ S DPH
0060500098	Exzellenz Audio Cable Sym. Mono Price/m	from 1,0m	863
006051007	Exzellenz Digital Cable XLR AES/EBU	0,75m	2.589
006051015	Exzellenz Digital Cable XLR AES/EBU	1,5m	2.992
00605103	Exzellenz Digital Cable XLR AES/EBU	3,0m	4.487



COAX DIGITAL CABLE




ITEM NO		LENGTH	MOC KČ S DPH
0041401	Video/Digital	1,0m	649
0041403	Video/Digital	3,0m	1.044

COAX DIGITAL CABLE



ITEM NO		LENGTH	MOC KČ S DPH
00316207	Video/Digital	0,75m	279
00316215	Video/Digital	1,5m	324
0031623	Video/Digital	3,0m	418
0031625	Video/Digital	5,0m	539
00316275	Video/Digital	7,5m	746
00316310	Video/Digital	10m	879
00316315	Video/Digital	15m	1.145

AUDIOPHILE HIGHLIGHT:
REFERENCE SOUND EDITION



RESO Mastering (Reference Sound Mastering), the new high definition mastering procedure, provides significant acoustic improvements in transparency, dynamics, bass reproduction and depth differentiation. The music is gaining more atmosphere and emotion. To best transmit this musical experience, a UHQ-CD is used as sound carrier. A newly developed disc manufacturing process masks the sound quality of UHQ-CD closer to the master quality.

ITEM NO	
01675015	Great Voices (U-HQCD)
0167501	Great Voices (HQCD)
01675011	Great Voices (2 LP)

DIGITAL OPTO

DIGITAL CABLE | OPTICAL



ITEM NO		LENGTH	MOC KČ S DPH
00604501	TOS-Link	1,0m	1.700
00604502	TOS-Link	2,0m	1.987

DIGITAL CABLE | OPTICAL



ITEM NO		LENGTH	MOC KČ S DPH
0041201	TOS-Link	1,0m	1.469
0041202	TOS-Link	2,0m	1.667
0041203	TOS-Link	3,0m	1.837
0041205	TOS-Link	5,0m	2.232
0041210	TOS-Link	10,0m	3.249

DIGITAL CABLE | OPTICAL



ITEM NO		LENGTH	MOC KČ S DPH
00312107	TOS-Link	0,75m	363
00312115	TOS-Link	1,5m	455
0031213	TOS-Link	3,0m	537
003121071	TOS-Link > Mini Plug	0,75m	363
003121151	TOS-Link > Mini Plug	1,5m	455
00312131	TOS-Link > Mini Plug	3,0m	537


PHONO CABLE NF-803



The phono cable NF-803 convinces with outstanding clarity, precision and accuracy. Two high speed signal conductors provide the signal transport. At the same time, the DUO-PE II insulation and the air-filled PE tubes reduce unwanted capacitance and enable the signal source to work "comfortably". The PE-Network Jacket also prevents micro-vibrations. Another highlight are the Referenz GAP II RCA plugs which take the symmetrical design of this connection to the limit.

„Conclusion: Both cables (NF-803 & NF-202) should be used in sophisticated systems. This is where they belong. If you're willing to spend 100€ more for the NF-803 it's a good investment in even better quality. You'll get more out of it in every situation, which is certainly due to the higher quality materials. In the end it is pleasant to see that in a HiFi world, where nobody seems to be afraid of high numbers anymore, in-akustik holds products for lovers of analog music at really great value for money. They are therefore very much in line with the trend" (Hörerlebnis | 92)

- High Speed signal conductor
- Symmetrical design
- High-purity OFC copper
- Braided shielding
- DUO-PE II Insulation
- PE-Network Jacket
- 2-fold PE-Tube Isolation



ITEM NO		LENGTH	MOC KC S DPH
0071840215	Phono Cable NF-803 RCA -> RCA	1,5m	11.222
0071840315	Phono Cable NF-803 SME -> RCA	1,5m	12.540

PHONO CABLE NF-202




- Symmetrical design
- High-purity OFC copper
- Foil shielding and weave sleeve
- DUO-PE II Insulation
- PE-Network Jacket
- PE-Tube Insulation



Precisely because audio signals are so sensitive, we have equipped our Reference phono cable NF-202 with some highly-effective technology: optimum DUO-PE II insulation with air-filled PE tubes, an innovative GAP plug, but also in particular an extremely sophisticated, solid conductor made of high-purity OFC copper, which all ensure uniform transit times and crystal-clear signal transmission. The earth and signal conductors are the same size and arranged symmetrically. The PE network jacket prevents micro-vibrations.

PHONO CABLE



Special phono cable for record players with the MM/MC system. With a separate ground cable to ground the drive. The symmetrical structure and double shielding protect the sensitive signal from external interference factors. The properties of the high-quality PE insulation and the high copper content ensure a detailed, dynamic and powerful sound.

ITEM NO		LENGTH	MOC KC S DPH
007181215	Phono Cable NF-202 RCA -> RCA	1,5m	9.163
007181315	Phono Cable NF-202 SME -> RCA	1,5m	10.284

ITEM NO		LENGTH	MOC KC S DPH
00405107	Phono Cable Premium RCA -> RCA	0,75m	1.700
00405115	Phono Cable Premium RCA -> RCA	1,5m	1.856
00405120	Phono Cable Premium RCA -> RCA	2,0m	1.987



PHONO PRE-AMP



The Premium Phono Pre-Amp is also suitable for the digitisation of record collection or the digitisation of other analogue audio sources, such as cassette decks in conjunction with a PC.

- Switchable from Line In to Line Out
- Compatible with MM and MC systems
- Compatible with Win98/ME/2000/XP7/8
- Compatible with Mac OS 2.1 / 10.2 / 10.4
- Sampling rate up to 48 kHz
- Dimensions: approx. 129 x 75 x 31 mm
- Incl. power supply and USB/Phono/RCA cable

ITEM NO	UNIT	MOC Kč S DPH
00415004	1 pc	2.201

RECORD BRUSH



This antistatic carbon-fibre brush, with more than a million extremely fine fibres, is especially effective at removing even the tiniest grains of dust and particles of dirt from the record grooves. The static charge is also greatly reduced. The result is an audibly improved sound experience and a longer life for your record collection.

- Antistatic
- Eliminates static discharge on both sides
- More than a million conductive carbon fibres
- Protective guard with stripping edge for cleaning the fibres
- Reduces crackling noises

ITEM NO	UNIT	MOC Kč S DPH
004528001	1 pc	321

RECORD COVER PROTECTION & SLIPCOVER



The slipcovers are made of anti-static HDPE (high density polyethylene) that prevents electrostatic charge on the vinyl. This decreases the attraction of new dust particles and reduces crackling during play back. The special format offers a particular advantage. One side is rounded off meaning the record inner sleeves easily slide into LP covers and paper sleeves. This is particularly interesting for collectors who want to preserve the original inside cover.

ITEM NO	UNIT	MOC Kč S DPH
004528005	Slip Cover Set of 50	986
004528006	Cover Protection Set of 50	1.029

ACCESSORIES HOME HIFI

SLITTED CABLE CONDUIT



Hi-fi, TV and computer devices have to be connected with a great many signal and power cables. These cables can often impair the appearance or become trip hazards. This high-quality fabric cable conduit allows cables to be bundled together in an attractive manner. The conduit is slitted and rolls together in an overlapping manner of its own accord. This means that the cables do not need to be pushed through the conduit but can be conveniently inserted in the conduit over its entire length. This means that it can also accommodate power cables with large (Schuko) plugs.



ITEM NO	LENGTH	MOC Kč S DPH
009210719	Premium slitted cable conduit 19 mm Price/m 38m	451

CABLE CONDUIT



Hi-fi, TV and computer devices have to be connected with a great many signal and power cables. These cables can often impair the appearance or become trip hazards. This high-quality fabric cable conduit allows cables to be bundled together in an attractive manner. The conduit has been designed so that it can accommodate power cables with large (Schuko) plugs. It can be cut to the required length conveniently with a pair of scissors. One notable feature is that the fabric at the ends does not fray as easily as other conduits.

- Simple to cut
- Stabilised braid
- Reduced fraying at the ends
- Diameter: 25-38 mm

ITEM NO	LENGTH	MOC Kč S DPH
009210032	25-38mm Price/m 38m	278



DAC CONVERTER | USB POWER



The converter can be used, for example, for the faint sound of a new flat-screen television on an older but sound quality hi-fi player. The stereo output provides to the usual line-level and can be connected, for example, to the AUX or ,TV input of the amplifier. Power supply using AC adapter or through USB.

- Power supply using AC adapter or through USB
- Audio formats LPCM 44/48/96 kHz
- Supports up to 24 Bit
- Stereo Line Out
- Two inputs (optical I coaxial)
- Universal range of application
- compact design (79x50x25mm)
- S/N ratio > 100dB
- Harmonic distortion: 0.05% max.
- Wolfson-Chip

ITEM NO	UNIT	MOC Kč S DPH
00315002 Star DAC	1 pc	1.814

OPTO SPLITTER



The Premium Toslink splitter distributes two optical outputs to one input and vice versa. For instance, if the AV receiver only has one optical input but needs to be connected to a CD player as well as a DVD player with optical output.

ITEM NO	UNIT	MOC Kč S DPH
01040100 Opto Splitter	1 pc	578

OPTO CONVERTER



Converter for adjusting devices with optical digital outputs to devices with coaxial input or vice versa. For instance, this allows a DVD player with an optical output to be connected to the coaxial input of an AV receiver.

ITEM NO	UNIT	MOC Kč S DPH
01040101 Coax > Toslink	1 pc	1.639
01040102 Toslink > Coax	1 pc	1.780

DIE STEREO HÖRTEST CD, VOL. IX



Listen and enjoy the most popular test tracks of the STEREO editors! In order to put HiFi and High End products through their paces, high quality music is required. In collaboration with STEREO - the magazine for HiFi, High End and Music - this compilation presents 15 titles as a listening recommendation of the editors. All titles were remastered extensively by Stockfisch.

MEDIUM	ITEM NO	TITEL
U-HQCD	01679345	Die Stereo Hörtest CD, Vol. IX
CD	0167934	Die Stereo Hörtest CD, Vol. IX
LP Audiophile	01679341	Die Stereo Hörtest CD, Vol. IX

EXZELLENZ RCA



- Metal housing
- 24c gold-plated contacts
- 8 mm cable extension
- suitable e.g. for the Excellence digital, audio or sub cable
- Each 1 pc color coding ring yellow, white, gray included in delivery

ITEM NO	UNIT	MOC Kč S DPH
006990061 Exzellenz RCA	bulk	209

STAR RCA



- Cable extension: 8,0 mm; 6,0 mm
- Solid metal plug
- Red/Black coding
- 24c gold-plated contacts
- Kink protection and strain relief

ITEM NO	UNIT	MOC Kč S DPH
008110 Star RCA	bulk	145



RCA F & Y ADAPTER



- Red/Black coding
- Solid metal plug
- 24c gold-plated contacts

RCA PHONE PLUG ADAPTER



- 24c gold plated contacts
- 3,5mm Klinke -> 2 x RCA (w)

RCA DOUBLE COUPLING



- Red/Black coding
- Solid metal plug
- 24c gold-plated contacts

ITEM NO	UNIT	MOC KČ S DPH
0080421	RCA F Adapter	Set of 2 734

ITEM NO	UNIT	MOC KČ S DPH
0081381	Phone Plug Adapter	1 pc 263

ITEM NO	UNIT	MOC KČ S DPH
0080951	RCA Double Coupling	Set of 2 348

EXZELLENZ XLR



- Solid metal plug
- 24c gold-plated contacts
- suitable e.g. for the Excellence XLR Audio or Digital Cable (item no. : 0060500098)

PREMIUM XLR



- Cable extension: 8,0 mm; - Tülle 10,0 mm
- Solid metal plug
- Solid XLR plug/coupling for perfectly symmetrical connections.

SOLDER



RoHS conform silver solder with a high content of silver and excellent flow capacities. A perfect electrical connection and corrosion prone contact is achieved.

ITEM NO	UNIT	MOC KČ S DPH
006990111	Exzellenz XLR (f)	bulk 340
006990101	Exzellenz XLR (m)	bulk 340

ITEM NO	UNIT	MOC KČ S DPH
0083331	XLR (m)	bulk 292
0083332	XLR (f)	bulk 292

ITEM NO	UNIT	MOC KČ S DPH
010291	Premium Solder	bulk 1.254



HIGH TECH GEL ABSORBER



High-end and hi-fi systems are a combination of highly precise and delicate devices. Perfectly attuned to each other, they allow music to be played back in outstanding quality. So that all components can work without interference, just like sensitive measuring equipment, they need to be kept free of vibrations and shocks as far as possible. Vibrations are caused in different ways and they can be transmitted by structure-borne and airborne noise. The combination of airborne and structure-borne noise causes all of the components of the hi-fi system to vibrate mechanically. Experiments have shown that this has a considerable impact on the sound. This Reference absorber set provides a solid sound basis. The absorbers have a special gel at their core that absorbs vibration energy. This set contains 12 gel pads for various weight classes for the optimum tuning and decoupling of the devices and loudspeakers.



In order to set up components optimally and decouple them, different gel pads are included in this set. In the table you can find the assignment to the respective weight classes. The values are recommendations based on measurements made by in-akustik.

- Gel pad device weight (per set of 4)
- Green*: up to 5 kg (up to 1.25 kg / absorber)
- Blue: 5–10 kg (1.25–2.5 kg / absorber)
- Green: 10–20 kg (2.5–5.0 kg / absorber)
- Black: 20–40 kg (5.0–10.0 kg / absorber)
- 3 x 4 Hightech-Absorber-Gel
- Top and bottom part made from stainless steel
- Covers four weight classes from 5 to 40 kg
- Felt pads and adhesive pads included
- Dimensions approx. 45 x 11.5 mm (D x H)

ITEM NO	UNIT	MOC	KČ	S	DPH
00719220 Referenz High-Tech Gel-Absorber	Set				6.078

*Due to the resonance response, we recommend this gel pad for use in two weight classes.



GEL ABSORBER



Hi-fi systems are a combination of highly precise devices. So that they can work without interference, just like sensitive measuring equipment, they need to be kept free of shocks. These gel absorbers provide a solid sound basis without vibrations. They have a special gel at their core that absorbs vibration energy.



- Plates made of stainless steel
- 4 pcs gel absorber
- Withstands up to 20 kg
- Felt pads and adhesive pads
- Dimensions approx. 45 x 5 mm (D x H)

ITEM NO	UNIT	MOC Kč S DPH
008560	Gel-Absorber Set of 4	1.959

PIC & PLATE MAXI



The solid sub-frequency absorber for linking devices and speakers to one place and reducing vibration. They are adjustable with adhesive pads as well as protective discs for sensitive surfaces.

- Withstands up to 40 kg/Set of 4 -> 10 kg/pc

ITEM NO	UNIT	MOC Kč S DPH
008480	Pic 36x30mm Gold Set of 4	1.285
008481	Pic 36x24mm Gold Set of 4	1.019
008484	Plate 30x5mm Gold Set of 4	530
0084847	Plate 30x5mm Black Set of 4	584

PLATE MINI



The simple sub-frequency protection plates for linking devices and speakers to one place reduces vibrations.

- Withstands up to 8 kg/pc

ITEM NO	UNIT	MOC Kč S DPH
008499	Star Plate Mini bulk	49

XL ABSORBER



Shock absorber made of a specially developed rubber compound for effective and wide-ranging vibration damping of sensitive hi-fi equipment such as CD players, turntables or shelf speakers. In addition, the damping feet are also ideally suited for acoustic decoupling of computers or game consoles, as drive noises are no longer transmitted to the surface on which the devices are standing.

- Special rubber compound for effective resonance damping
- A non-slip surface profile guarantees a stable grip on all surfaces
- Diameter 60 mm | Hight: 5mm
- Withstands up to 50 kg / set

ITEM NO	UNIT	MOC Kč S DPH
0085010	Star XL Absorber Set of 4	266

BOLIDE ABSORBER



The Exzellenz bolide shock absorber consists of a special rubber compound and a sophisticated in design for optimum damping of vibration between the devices and the standing position.

- Withstands up to 50 kg / set of 4 -> 12,5 kg/pc

ITEM NO	UNIT	MOC Kč S DPH
008550	Bolide Shock Absorber Set of 4	2.119

ABSORBER DOUBLETEN



The Premium doublette in sandwich design consists of metal discs and special rubber for optimum vibration damping between the devices and the standing position.

- Withstands up to 20 kg / set of 4

The sub-absorber made from a special rubber compound for optimum damping of vibration between the devices and the standing position.

- Withstands up to 8 kg / set of 4

ITEM NO	UNIT	MOC Kč S DPH
008509	Premium Doublette Set of 4	1.042
008508	Star Mini Absorber Set of 4	741




REFERENZ CABLE BASES




The Referenz Cable bases are specifically designed cabling-support systems for the finest stereo systems. The base incorporates absorber gel, too, plus extra rubber bands accommodating the freely suspended cables. This way, Referenz Cable Bases not only absorb vibrations but consistently isolate your cables from the floor, reducing unwanted capacitance and minimizing the load of the electronic system.

Referenz Cable Bases are highly versatile because they support various cabling diameters and floor gaps as well as open and closed cable suspension. With open suspension, the cable rests on a rubber band and allows for mounting at three different heights; with closed suspension, cables are fixed using two rubber bands above and below. This approach is advantageous in that minor movements (for example, when aligning your speakers) will not result in the cable falling from the Base—it is fixed in a defined position. The innovative cable supports thus ensure effective mechanical and capacitive decoupling of your RCA, XLR, and phono cables from the floor. A particularly interesting application of Referenz Cable Bases is the decoupling of your phono cables. This is essential because otherwise vibrations would travel to your tone arm and on to your sensitive pick-up system.

CABLE ROUTED ON THE FLOOR =
HIGH CAPACITANCE



CABLE AT A DISTANCE TO THE FLOOR =
LOW CAPACITANCE



FEATURES

- For mechanical and capacitive isolation of cables
- For cable diameters from 10 to 25 mm
- Hi-tech gel pad in the base
- Natural rubber strips for cable routing
- Open or fixed cable routing
- Diameter: 47 mm
- Total height: 48 mm
- Height levels: 25 / 33 / 44 mm

ITEM NO	UNIT	MOC Kč s DPH
00719223 Referenz Cable-Base silver satined	Set of 10	11.479
00719222 Referenz Cable-Base silver satined	Set of 6	7.165



**stereoplay
Highlight**

Price/performance:
outstanding

REFERENZ AC-3500 POWER STATION



Where does fine sound begin? Where does it end? Audio enthusiasts have kept asking those questions for ages. As a matter of fact, physical conditions have a considerable impact on the sound quality produced by audio systems. In this, power supply is one of the key factors. In principle, we listen to domestic current modulated by a music signal.

The Referenz Power Station AC-3500P reliably suppresses all unwanted interference from the power system. The Active Power Distributor implements a highly efficient parallel filter perfectly attuned to the audiophile's needs. The filter leads off all interference from both the power system and the connected devices themselves without restricting the supply. Add to this the dampened sub chassis that reduces mechanical vibrations of the filter components caused by the 50-Hz grid frequency. In addition, the star-shaped distribution topology ensures uniform supply of all connected units. This way, the Referenz Power Station AC-3500P becomes a key factor to a fine yet powerful sound.

The technical design is housed in a stout metal enclosure with a front panel of silver or black anodized brushed aluminum. Six high-quality power sockets are available at the rear panel. The centrally placed high-current power inlet (IEC C20) allows for easy replacement of the supply cable – for example, with a longer one.

The built-in surge suppressor protects your precious devices from voltage peaks, and you can conveniently switch all power sockets on and off using the power key on the front panel. An indirect LED light located at the front-panel bottom shows the current operational status: white is for the standby mode while blue indicates that the Power Station is on and the power sockets are active.

- Highly efficient centralized parallel filter
- Dampened sub chassis
- Balanced power distribution
- High-quality type-F (Schuko) sockets
- High-current power inlet (IEC C20)
- Brushed-aluminum front panel
- With black finish or untreated aluminum
- All-pole disconnection
- Surge protection
- Made in Germany
- Power inlet: IEC C20 socket
- Supply voltage: 230 V AC, 50–60 Hz
- Operating current (max.): 16 A
- Input power (max.): 3,680 W (230 VAC, 16 A)
- Dimensions (W x D x H): approx. 450x370x160 mm
- Weight: approx. 12.8 kg



ITEM NO		MOC Kč S DPH
00763500	Referenz AC-3500P Silver	63.083
007635007	Referenz AC-3500P Black	63.083
00763500US	Referenz AC-3500P Silver US-Version	75.382
07635007US	Referenz AC-3500P Black US-Version	75.382

POWER BAR AC-2502-SF8




The in-akustik mains cables and power strips filter the current and deliver "clean" currents for your HiFi system. Use of the best materials and excellent workmanship guarantee maximum dynamics, even for extreme loads. Complete screening and a special filter prevent radio frequencies from being received which would turn the cable into an aerial. Solid line bars in the power strips distribute the power homogeneously to all outlets.

Furthermore, the sockets are divided into two groups with the AC-2502-SF8 power strip. Groupe 1: The two grey sockets are directly and permanently connected to the mains supply. This means that power amplifiers, active subwoofers or other power-hungry devices that should not be disconnected from the mains, can remain connected. Groupe 2: The six black sockets can be separated from the mains supply using a switch. The additional mains filter makes this group especially suitable for source devices such as CD players, preamplifiers, phono pre-amps and other precision electronics.


3 X 2,5 MM² CABLE | FOIL SHIELDED

So that no new interference occurs because of the antenna effect of the cables, the power cable and the power bar are fully screened and shielded. Thus, a cleaned current is supplied to the appliances. The electronics can once more deliver the highest precision entirely unhampered.



IN-PLUG FILTER

A ferrite filter is integrated in the plug of the power bar. This In-Plug Filter blocks interference from the network directly at the socket. The filter is manufactured from a special high-density ferrite that works extremely effectively in the smallest of spaces. A further advantage is that oth the live wires of the power cords are led directly through this ferrite. Power losses through additional nips or solder points are eliminated.



ITEM NO		LENGTH	MOC Kč S DPH
00716402	Referenz Power Bar AC-2502-SF8	1,5m	17.238
00716403	Referenz Power Bar AC-2502-SF8	3,0m	18.489

POWER BAR AC-2502-P8 & AC-1502-P6



The Referenz power bars filter unwanted interference out of the power supply, without introducing additional source impedance. Thanks to the use of high-quality materials and excellent workmanship, they provide maximum dynamics, even for extreme loads. Their full shielding and special filters prevent radio frequencies from being received. Solid power bars in the power strips distribute the power homogeneously to all outlets.

- Fully shielded metal housing
- Foil shielding and additional shielding wire
- In-Plug Filter in the AC plug; 2Y-Filter in the power bar
- Power bar (8 mm²) for even power distribution
- Phase marking
- VDE- und CE conform
- 3 x 2,5 mm² (P8); 3 x 1,5 mm² (P6)
- 8 sockets (P8); 6 sockets (P6)
- Safety protection
- PE-Network Jacket
- Includes phase tester

ITEM NO		LENGTH	MOC Kč S DPH
00716302	Referenz Power Bar AC-2502-P8	1,5m	13.645
00716303	Referenz Power Bar AC-2502-P8	3,0m	14.884
00716202	Referenz Power Bar AC-1502-P6	1,5m	11.492
00716203	Referenz Power Bar AC-1502-P6	3,0m	13.520

POWER BAR AC-25.6



A stable power supply forms the basis of good quality pictures and sound. Unfortunately, a great deal of quality is often lost due to high contact resistance when using cheap power bars. This is characterised by limited dynamics and slurred bass even at low and medium volumes. The Excellence AC 25.6 power bar consists of high quality, perfectly matched materials such as the solid power plug and the 3 x 2.5 mm² strong power cord. In connection with the solid 4 mm² copper power bars in the strip, the setup ensures low contact resistance and enables the system to reach maximum performance. The strip is complemented by its solid aluminium housing which also has a shielding effect. Power bar in accordance with DIN VDE 0620-2-1.

- 3 x 2,5 mm² cable | 1,65m
- Aluminium housing
- 4mm² copper busbar
- 16A nominal current
- 3680 Watts max.
- Childproof
- 230 V AC nominal voltage

ITEM NO		LENGTH	MOC Kč S DPH
006170615	Exzellenz Power Bar AC - 25.6	1,65m	5.269

MAINS CABLE AC-1502 | AC-1502F | AC-2502F



The Referenz mains cable ensures a stable and clean supply of power. The shielding provides reliable protection from interference and the innovative in-plug filter provides additional decoupling for the equipment.

- Additional shielding wire (CU tin-plated; 1 x 1.5 mm²)
- Phase markings
- Foil shielding
- Ferrite filter in the plug (in-plug filter)
- PE-Network Jacket
- Conforms to VDE and CE

ITEM NO		LENGTH	MOC Kč S DPH
00716101	Schuko > rubber connector; 3 x 1,5 mm ²	1,0m	5.172
00716102	Schuko > rubber connector; 3 x 1,5 mm ²	1,5m	5.352
00716103	Schuko > rubber connector; 3 x 1,5 mm ²	3,0m	6.592
00762552	AC-2502F; on spool 13,0 mm; 3 x 2,5 mm ² ; (Price/m)	50m	615
00762512	AC-2502F; 10m ring 13,0 mm; 3 x 2,5 mm ²	10m	6.498
00762522	AC-2502F; 20m ring 13,0 mm; 3 x 2,5 mm ²	20m	12.653
00761512	AC-1502F; 10m ring 11,0 mm; 3 x 1,5 mm ²	10m	4.097
00761522	AC-1502F; 20m ring 11,0 mm; 3 x 1,5 mm ²	20m	8.165

POWER CABLE AC-2503M



Electrical installations in buildings are usually carried out expertly, but at the minimum expense. This means that the cables from the fuse box usually pass through a number of junction boxes and terminals before reaching the sockets. Each terminal means additional contact resistance and additional load from other appliances in the room. This leads to losses and disturbances in the power supply. Ideally, there should be a separate cable from the fuse box to the socket of the hi-fi system. The Referenz AC-2503M is perfect for this application. In addition to its large conductor cross-section of 3 x 2.5 mm², it has a shield which protects the components from electromagnetic interference from the fuse box onwards.


- Large cross-section 3 x 2.5 mm²
- Pure copper conductor
- Foil shield
- Auxiliary wire for easily connecting the shield
- Flame retardant as per EN 60332-1-2
- CE compliant
- Rated voltage: 300 / 500 V
- Test voltage: 2000 V
- Bending radius: min. 50 mm.
- Temperature range: -40 to + 70 °C

ITEM NO		LENGTH	MOC Kč S DPH
007622503	Referenz AC-2503M Price/m	50m	243



REFERENCE SOUND EDITION

The samplers of our Reference Sound Edition have been assembled with a love of musical detail. RESO Mastering (Reference Sound Mastering), the high definition mastering procedure, provides significant acoustic improvements in transparency, dynamics, bass reproduction and depth differentiation. The music is gaining more atmosphere and emotion. To best transmit this musical experience, instead of a normal CD, a HQCD respectively to get even closer to the master quality, a UHQ-CD is used as sound carrier and instead of normal LP vinyl, 180g audiophile Virgin Vinyl.



ITEM-NO	TITEL	MEDIUM
01675015	Reference Sound Edition – Great Voices Vol.1	U-HQCD
0167501	Reference Sound Edition – Great Voices Vol.1	HQCD
01675011	Reference Sound Edition – Great Voices Vol.1	Audiophile Doppel-LP
0167502	Reference Sound Edition – Great Voices Vol.2	HQCD
01675021	Reference Sound Edition – Great Voices Vol.2	Audiophile Doppel-LP
01675085	Reference Sound Edition – Great Voices Vol.3	U-HQCD
0167508	Reference Sound Edition – Great Voices Vol.3	HQCD
01675081	Reference Sound Edition – Great Voices Vol.3	Audiophile Doppel-LP
0167503	Reference Sound Edition – Great Cover Versions	HQCD
01675031	Reference Sound Edition – Great Cover Versions	Audiophile Doppel-LP
0167504	Reference Sound Edition – Great Guitar Tunes	HQCD
01675041	Reference Sound Edition – Great Guitar Tunes	Audiophile Doppel-LP
0167505	Reference Sound Edition – Soundcheck	HQCD
01675051	Reference Sound Edition – Soundcheck	Audiophile Doppel-LP
0167506	Reference Sound Edition – Great Women Of Song	HQCD
01675061	Reference Sound Edition – Great Women Of Song	Audiophile Doppel-LP
0167507	Reference Sound Edition – Great Men Of Song	HQCD
01675071	Reference Sound Edition – Great Men Of Song	Audiophile Doppel-LP



HEADPHONE EXTENSION CABLE

6,3 | HEADPHONE EXTENSION CABLE



- Doppel | Double SYMMETRICAL
- ABSCHIRMUNG SHIELDING
- VERLUSTARME PE-ISOLATION LOSSLESS PE INSULATION
- OFC COPPER HOCHREIN HIGH PURITY
- VERSILBERT SILVER PLATED
- Metallstecker Solid Metal Plug
- VERGOLDET GOLD-PLATED
- TEXTILE JACKET
- ((STEREO))
- RoHS Compliant

The highly complex, dual symmetrical structure of the Excellence headphones extension cable in conjunction with the very densely woven shielding protects the intricate audio signals optimally against external interference that is emitted from smartphones or other electrical devices, for instance. The silver-plated conductors transmit the analogue music signal precisely and enable exceptionally crystal clear and dynamic sound even for high-resolution audio formats. The 24-carat gold-plated contacts ensure optimum contact and minimal transition resistance for low-loss transmission of the music signal.

3,5 | HEADPHONE EXTENSION CABLE



- ABSCHIRMUNG SHIELDING
- VERGOLDET GOLD-PLATED
- OFC COPPER HOCHREIN HIGH PURITY
- ((STEREO))
- RoHS Compliant

3,5 | HEADPHONE EXTENSION CABLE



- FOLIENSCHIRM FOIL SHIELDING
- VERGOLDET GOLD-PLATED
- ((STEREO))
- RoHS Compliant



* inkl. 6,3 adapter

ITEM NO	LENGTH	MOC KČ S DPH
006046015	6,3 Phone Plug (m) <-> 6,3 Phone Plug (f) 1,5m	1.883
00604603	6,3 Phone Plug (m) <-> 6,3 Phone Plug (f) 3,0m	2.275
00604605	6,3 Phone Plug (m) <-> 6,3 Phone Plug (f) 5,0m	2.849

ITEM NO	LENGTH	MOC KČ S DPH
00410202	2,0m	668
00410203	3,0m	804
00410205	5,0m	1.023
004102075	7,5m	1.154
00410210	10,0m	1.285

ITEM NO	LENGTH	MOC KČ S DPH
003105015	1,5m	255
00310503	3,0m	303
00310505	5,0m	335

PHONE PLUG CABLE

3,5 | PHONE PLUG



- ABSCHIRMUNG SHIELDING
- VERGOLDET GOLD-PLATED
- OFC COPPER HOCHREIN HIGH PURITY
- ((STEREO))
- RoHS Compliant

3,5 | PHONE PLUG



- FOLIENSCHIRM FOIL SHIELDING
- VERGOLDET GOLD-PLATED
- ((STEREO))
- RoHS Compliant

3,5 | PHONE PLUG



- ABSCHIRMUNG SHIELDING
- VERGOLDET GOLD-PLATED
- OFC COPPER HOCHREIN HIGH PURITY
- ((STEREO))
- RoHS Compliant

3,5 | PHONE PLUG



- FOLIENSCHIRM FOIL SHIELDING
- VERGOLDET GOLD-PLATED
- ((STEREO))
- RoHS Compliant

ITEM NO	LENGTH	MOC KČ S DPH
004101005	0,5m	496
0041010075	0,75m	526
004101015	1,5m	578
00410103	3,0m	734

ITEM NO	LENGTH	MOC KČ S DPH
003101005	0,5m	217
0031010075	0,75m	224
003101015	1,5m	248
00310103	3,0m	295

ITEM NO	LENGTH	MOC KČ S DPH
004104005	0,5m	496
0041040075	0,75m	526
004104015	1,5m	578
00410403	3,0m	699

ITEM NO	LENGTH	MOC KČ S DPH
003104005	0,5m	227
0031040075	0,75m	243
003104015	1,5m	256




PHONE PLUG ADAPTER



- 3,5 mm Phone Plug -> 2 x RCA

ITEM NO	LENGTH	MOC KČ S DPH
004100015	1,5m	578
00410003	3,0m	734
00410005	5,0m	993

PHONE PLUG ADAPTER



- 3,5 mm Phone Plug -> 2 x RCA

ITEM NO	LENGTH	MOC KČ S DPH
003100005	0,5m	211
0031000075	0,75m	220
003100015	1,5m	244
00310003	3,0m	291
00310005	5,0m	350
00310007	7,0m	428
00310010	10,0m	508

PHONE PLUG ADAPTER



- 3,5 mm Phone Plug -> 2 x 3,5mm Phone Plug (f)

ITEM NO	LENGTH	MOC KČ S DPH
00410212	20cm	644

PHONE PLUG ADAPTER



- 3,5 mm Phone Plug -> 2 x 3,5mm Phone Plug (f)

ITEM NO	LENGTH	MOC KČ S DPH
00310302	10cm	285

iPLUG CABLE

iPLUG LIGHTNING CABLE CHARGING & DATA SYNC



iPlug cable for data exchange between Apple devices and PCs, laptops, etc., and charging cable for Apple mobile components. Due to large conductor cross sections, also especially suitable for the high charging currents of the iPad. The double shielding (foil and mesh braiding) protects against outside interference and ensures unhindered signal transport.

ITEM NO	LENGTH	MOC KČ S DPH
00440201	Apple Lightning > USB-A	1,0m 750
00440202	Apple Lightning > USB-A	2,0m 863
00440203	Apple Lightning > USB-A	3,0m 1.004

iPLUG CABLE | AV & USB




iPlug cable for data exchange between Apple devices and PCs, laptops, TVs or hi-fi systems, and charging cable for Apple mobile components. Due to large conductor cross sections, also especially suitable for the high charging currents of the iPad. Foil shielding protects against outside interference and provides for unhindered signal transport.

ITEM NO	LENGTH	MOC KČ S DPH
00440101	Apple <> USB RCA Audio & Video	1,0m 2.120
00440102	Apple <> USB RCA Audio & Video	2,0m 2.386
00440002	Apple <> USB	2,0m 909



HEADPHONE AMP

HEADPHONE AMP NO. 1



The headphone outputs of mobile devices such as smartphones, tablets and laptops are not usually very powerful. This often impairs audio quality. The Premium Headphone Amp No. 1 takes the strain off of the device outputs. Its high-quality analogue amplifiers are optimally tuned to each other. They drive and control the connected headphones with exceptional accuracy and provide greater volume, dynamics and precision.

In addition, the unit also protects the battery of the mobile device and increases its service life. The Premium Headphone Amp No. 1 also has a high-quality digital/analogue converter to replace the integrated, usually basic, sound cards of devices such as PCs and laptops. This further boosts the sound quality. The analogue volume controller with integrated on/off switch makes the amplifier very easy to use.

- Two headphones jacks
- Integrated USB Digital Analog Converter
- Latest chip technologies
- Black brushed alu optic housing
- Can operate for up to 60 hours
- Also suitable for high-impedance headphones
- Large dynamic scope
- Compatible with Windows XP, Vista, 7/8
- Output rating: maximum 2 x 320 mW
- Impedance: 16–300 ohms
- Input impedance: 5 kohms
- Signal-to-noise ratio: 96 dB
- Crosstalk attenuation: 60 dB
- Amplification: 10 dB
- Distortion factor: < 0.008 % (10 mW)
- Frequency range: 22 Hz – 65 kHz
- Battery: 3.7 V / 950 mAh (lithium-ion)
- Dimensions: approx. 90 x 13 x 57 mm



ITEM NO	UNIT	MOC Kč S DPH
00415005 Premium Headphone Amp No.1	1 pc	7.830

HEADPHONE AMP

USB CHARGER

HEADPHONE AMP NO. 2



- Also suitable for high-impedance headphones
- Power supply via USB
- Compatible with Windows XP, Vista, Windows 7/8
- Output rating: maximum 2 x 300 mW
- Impedance: 8–300 ohms
- Signal-to-noise ratio: 96 dB
- Crosstalk attenuation: 60 dB
- Amplification: 10 dB
- Distortion factor: < 0.008% (10 mW)
- Frequency range: 22 Hz – 65 kHz

ITEM NO	UNIT	MOC Kč S DPH
00415006 Headphone Amp No.2	1 pc	3.540

USB AC CHARGER



- Universal use
- Intelligent overload protection
- Over-temperature protection
- Plug & Play
- Input: 100–240 V AC | 50–60 Hz | 0.2 A max.
- Output: 5 V–1.0 A
- Dimensions: 45.5 x 35.4 x 23.4 mm
- Conforms to CE
- RoHS conformity

ITEM NO	UNIT	MOC Kč S DPH
010450002 USB AC Power Adapter	1 pc	332

USB CAR CHARGER



- Charging time reduced by up to 60%
- Automatic device recognition
- Automatic adjustment of the output voltage
- Precise current limitation
- Overload protection
- Overtemperature protection
- Input voltage 12 V DC (cigarette lighter)
- Output 5 V – 1.5 A | 9 V – 1.5 A | 12 V – 1.2 A


ITEM NO	UNIT	MOC Kč S DPH
00415010 USB Car Power Adapter	1 pc	574



WIFI AUDIO STREAMING RECEIVER



A computer is a multimedia centre and has long been a link between a AV receiver, TV or home cinema system and in the meantime also has HDMI, USB, or CAT connections. We supply the cable for all current connections. Of course, at the highest level.



Compatible systems:

- Android 4.0 or higher
- Apple iOS7 or higher
- Mac OS10.7 or higher
- Windows XP or higher
- Windows Phone

Recommended app:

- EZcast

Technical data:

- High-Res Audio: 24 Bit/96 kHz
- Stereo output via 3.5 mm jack
- Optical digital output
- USB-A connection for external memory
- Frequency range: 20 – 20,000 Hz -0.5 dB
- Dynamic range: >92 dB
- Power supply: via micro USB
- Weight (approx. 60 g)
- Dimensions: approx. 78 x 78 x 18 mm

Standards/audio formats supported:

- DLNA (WAV, MP3)
- Airplay (MP3, AAC, WMA, WAV, PCM, m4a/ALAC/FLAC)
- USB (MP3, AAC, WMA, WAV, PCM, m4a/ALAC/FLAC)
- Internet radio

ITEM NO	UNIT	MOC KČ S DPH
00415007 WiFi Audio Streaming-Receiver	1 pc	3.440



AUDIO BLUETOOTH® RECEIVER




Enjoy your favourite music from your smart phone, tablet PC or laptop – as well as from your iPhone or iPad – conveniently and wirelessly on your high-end hi-fi system. Thanks to the special aptX technology, you can also enjoy first-class CD quality. The Premium Bluetooth Receiver supports all common standards such as A2DP and SBC and is compatible with almost all Bluetooth-capable devices regardless of brand. The Premium Bluetooth Receiver stores up to eight devices. Once these devices are paired with the receiver, they are automatically recognized again, allowing the connection to be more quickly reestablished. In addition to the usual analogue output (3.5 mm jack), the receiver also has an optical digital output that enables it to be connected to a new generation of amplifiers.



- Bluetooth® 3.0+EDR
- Audiocodex aptX®
- Supports A2DP
- Supports SBC Codex
- Range up to 10m
- Frequency range: 10 Hz – 22.000 Hz
- Dynamic range: >92 dB
- LED display
- Dimensions: 75,9 x 69,8 x 20,3 mm
- Weight: 56 g

ITEM NO	UNIT	MOC KČ S DPH
00415003 Premium Bluetooth Audio Receiver	1 pc	3.795

BLUETOOTH® AUDIO TRANSMITTER & SPLITTER



The Premium Bluetooth Audio Transmitter allows you to conveniently connect Bluetooth headphones or Bluetooth loudspeakers with audio sources such as the television, Hi-Fi system or PC that are not Bluetooth-capable. In combination with the Premium Bluetooth Audio Receiver, a wireless audio connection can be set up between the TV and the Hi-Fi system, for example. The Premium Bluetooth Transmitter can be connected to two Bluetooth receivers simultaneously (splitter function). This is a simple way to set up multi-room solutions. To power it, plug the USB connector into a free USB port on the devices or a USB power supply unit (not included).



- Supports aptX Audio Codec
- Supports aptX LL (Low Latency)
- Supports SBC & A2DP
- Up to 10 m range
- Power supply over USB
- Frequency range: 20 – 20,000 Hz
- Dynamic range: 95 dB
- Channel separation: 85 dB
- Distortion factor: 0.05 %
- Version 3.0+DER (Enhanced Data Rate) #00415012
- Input #00415009: Analog High Level 2V rms max
- Input #00415012: TOS Link

ITEM NO	UNIT	MOC KČ S DPH
00415012 Bluetooth Audio Transmitter TOS-Link	1 pc	3.092
00415009 Bluetooth Audio Transmitter 3,5 Phone Plug	1 pc	2.746



DLNA

DLNA STICK



- Operation in Access Point or Client Mode
- Compatible with Windows 7 Media Player 11 or higher
- Compatible with Samsung "Allshare"
- Compatible with HTC "Media Link"
- Compatible with Apple "iMediaShare"
- Compatible with Android "XY APP"
- Easy installation via web browser
- Dimensions: ca. 62,5 x 22 x 9,5mm

ITEM NO	UNIT	MOC KČ S DPH
00415100	Premium DLNA Audio-Receiver	1 pc 4.078

MHL

MHL-ADAPTER



MHL (Mobile High Definition Link) is a standard defined by Nokia, Toshiba and Silicon Image for connecting smartphones and tablet PCs to the TV. The MHL adapter is connected to the USB port of the mobile devices, and transmits video and audio signals in HD quality. In addition, the CEC function is supported.

ITEM NO	UNIT	MOC KČ S DPH
0044101	Premium MHL Adapter	1 pc 1.430

USB CABLE

HIGH SPEED USB 2.0 CABLE




The Referenz USB 2.0 cable has been designed especially for low-loss HD audio streaming. The data lines consist of fine, separately lacquer-insulated copper wires (high speed conductors). In combination with the high-quality materials, they reduce the jitter effects that particularly affect the sound quality when streaming audio data. Sensitive data is additionally protected by 4-fold shielding. Extremely generously proportioned cables for the power supply of e.g. external hard drives minimize voltage fluctuations. Even with particularly long cables, they ensure that the peripheral devices function perfectly and therefore data is transferred with low error rates. The product is rounded off by the high-quality Referenz USB plug and the precise manufacturing.




JITTER

During digital data transmission ones and zeros are transmitted by voltage impulses. The choice of one or zero is made by the length of the impulse. The Jitter effect changes the impulse length due to the cable properties. The receiver then has difficulties in recognising the data.



HIGH SPEED DATENLEITER

The Referenz USB cable has finely braided signal wires, with each individual wire having a lacquer coating. This lacquer coating insulates the wires from each other, preventing eddy current within the braid and increasing the effective conductor surface. This means digital signals can be quickly and precisely transmitted.



USB 2.0 A > B

ITEM NO	LENGTH	MOC KČ
007170075	0,75m	7.420
007170015	1,5m	8.347
00717003	3,0m	10.084
00717005	5,0m	11.814
00717075	7,5m	14.797
00717010	10,0m	17.447

USB 2.0 A > Mini B

ITEM NO	LENGTH	MOC KČ S DPH
0071710075	0,75m	7.420
007171015	1,5m	7.950
00717103	3,0m	9.604
00717105	5,0m	11.814
00717175	7,5m	14.797
00717110	10,0m	17.447



HIGH SPEED USB B



HIGH SPEED USB MICRO-B



The Excellence USB cable is specially designed for streaming HD audio and video formats. The three-fold shielded twisted pair data cable protects the sensitive data content against external interferences. The silver-plated signal conductor and the perfectly adjusted impedance ensure fast and smooth data transmission. Thick conductors enable a stable supply for stationary and fast charging mobile devices. The metal connectors with gold-plated contacts provide optimum contact and minimal contact resistance.

The Excellence USB cable is specially designed for streaming HD audio and video formats. The three-fold shielded twisted pair data cable protects the sensitive data content against external interferences. The silver-plated signal conductor and the perfectly adjusted impedance ensure fast and smooth data transmission. Thick conductors enable a stable supply for stationary and fast charging mobile devices. The metal connectors with gold-plated contacts provide optimum contact and minimal contact resistance.

- ABSCHIRMUNG SHIELDING (SF-FTP)
- VERSILBERT SILVER PLATED
- 26AWG LEITERLEITUNGSLEITER
- OFC COPPER HOCHREIN HOCHREINE HOCHREINE HOCHREINE
- VERLUSTARME PE-ISOLATION
- VERGOLDET GOLD-PLATED
- 480 Mbit/s Übertragungsrate
- LOW JITTER
- METALLSTECKER METAL PLUG
- HIGH SPEED USB 2.0
- HD AUDIO STREAMING
- TEXTILE JACKET
- RoHS Compliant

- ABSCHIRMUNG SHIELDING (SF-FTP)
- VERSILBERT SILVER PLATED
- 26AWG LEITERLEITUNGSLEITER
- OFC COPPER HOCHREIN HOCHREINE HOCHREINE HOCHREINE
- VERLUSTARME PE-ISOLATION
- DATEN SYNC.
- VERGOLDET GOLD-PLATED
- 480 Mbit/s Übertragungsrate
- LOW JITTER
- METALLSTECKER METAL PLUG
- HIGH SPEED USB 2.0
- HD AUDIO STREAMING
- TEXTILE JACKET
- LADEN CHARGING
- RoHS Compliant

ITEM NO		LENGTH	MOC KČ S DPH
006700005	Exzellenz High Speed USB 2.0 A > B	0,5m	1.121
00670001	Exzellenz High Speed USB 2.0 A > B	1,0m	1.323
006700015	Exzellenz High Speed USB 2.0 A > B	1,5m	1.525
00670003	Exzellenz High Speed USB 2.0 A > B	3,0m	2.186

ITEM NO		LENGTH	MOC KČ S DPH
006701005	Exzellenz High Speed USB 2.0 A > Micro B	0,5m	1.121
00670101	Exzellenz High Speed USB 2.0 A > Micro B	1,0m	1.323
006701015	Exzellenz High Speed USB 2.0 A > Micro B	1,5m	1.525
00670103	Exzellenz High Speed USB 2.0 A > Micro B	3,0m	2.186

HIGH SPEED USB B



HIGH SPEED USB MINI-B



HIGH SPEED USB MINI-A



HIGH SPEED USB MICRO-B | -A



- ABSCHIRMUNG SHIELDING
- HOCHFLEXIBEL
- USB
- RoHS Compliant

- ABSCHIRMUNG SHIELDING
- HOCHFLEXIBEL
- USB
- RoHS Compliant

- ABSCHIRMUNG SHIELDING
- HOCHFLEXIBEL
- USB
- RoHS Compliant

- ABSCHIRMUNG SHIELDING
- HOCHFLEXIBEL
- USB
- RoHS Compliant

ITEM NO	LENGTH	MOC KČ S DPH
01070001	1,0m	310
01070002	2,0m	383
01070003	3,0m	415
01070005	5,0m	521

ITEM NO	LENGTH	MOC KČ S DPH
01070011	1,0m	295
01070012	2,0m	365
01070013	3,0m	396
01070015	5,0m	497

ITEM NO	LENGTH	MOC KČ S DPH
01070021	1,0m	310
01070022	2,0m	383
01070023	3,0m	415
01070025	5,0m	521

ITEM NO	LENGTH	MOC KČ S DPH
Micro B		
01070041	1,0m	291
01070042	2,0m	324
01070043	3,0m	367
01070045	5,0m	480
Micro A		
01070031	1,0m	277
01070032	2,0m	309
01070033	3,0m	350
01070035	5,0m	457

HIGH END NETWORK CABLE CAT 7



The CAT7 Referenz cable is a LAN cable for high-end network connections. Because of the high production quality, it well surpasses the specifications required by EN50288-4-2 / IEC61156-6 (600 MHz), and reaches band widths of over 1200 MHz. This makes it equipped for high-speed networks with 10 Gbps (10 Giga bits per second). It was however, through exacting maintaining the impedance of its data lines, especially conceived for low-loss HD audio and HD video streaming. The PE-Network Jacket also prevents disturbing microvibrations, while the high-grade CAT Referenz plug rounds off the product.



ITEM NO		LENGTH	MOC KČ S DPH
007150075	RJ45 <> RJ45; SF-UTP	0,75m	4.945
00715015	RJ45 <> RJ45; SF-UTP	1,5m	5.283
0071503	RJ45 <> RJ45; SF-UTP	3m	5.962
0071505	RJ45 <> RJ45; SF-UTP	5m	6.808
00715075	RJ45 <> RJ45; SF-UTP	7,5m	7.882
0071510	RJ45 <> RJ45; SF-UTP	10m	8.956
0071515	RJ45 <> RJ45; SF-UTP	15m	11.166
0071520	RJ45 <> RJ45; SF-UTP	20m	13.284

NETWORK CABLE CAT 6



The Excellence CAT cable is specially designed for high speed gigabit networks and streaming from HD audio and UHD video formats. The threefold shielded twisted pair cables (SF-FTP) protect the sensitive data content against external interferences. The thick silver-plated signal conductors and the perfectly adapted impedance ensure fast and smooth data transmission. The metal plugs with gold-plated contacts ensure optimum contact and minimal contact resistance.




ITEM NO		LENGTH	MOC KČ S DPH
006711005	RJ45 <> RJ45; SF-UTP	0,5m	1.121
00671101	RJ45 <> RJ45; SF-UTP	1,0m	1.323
00671102	RJ45 <> RJ45; SF-UTP	2,0m	1.698
00671103	RJ45 <> RJ45; SF-UTP	3,0m	2.186
00671105	RJ45 <> RJ45; SF-UTP	5,0m	3.021
006711075	RJ45 <> RJ45; SF-UTP	7,5m	4.085
00671110	RJ45 <> RJ45; SF-UTP	10,0m	5.148

NETWORK CABLE CAT 6



ITEM NO		LENGTH	MOC KČ S DPH
004803005	RJ45 <> RJ45; SF-UTP	0,5m	248
00480301	RJ45 <> RJ45; SF-UTP	1,0m	295
00480302	RJ45 <> RJ45; SF-UTP	2,0m	399
00480303	RJ45 <> RJ45; SF-UTP	3,0m	462
00480305	RJ45 <> RJ45; SF-UTP	5,0m	741
00480308	RJ45 <> RJ45; SF-UTP	8,0m	1.039

NETWORK CABLE CAT 6



- Separating cross between the twisted pairs
- SF-UTP (separate braided and foil shielding)
- 4 twisted pairs
- Cable diameter: 6,8 mm

ITEM NO		LENGTH	MOC KČ S DPH
004803000	CAT6; AWG24; SF-UTP; Price/m	100m	113
004890000	RJ-45 CAT5/6 Stecker; 8P8C	bulk	25
00489022;3;4	CAT5/6 insulation grommet; red; yellow; blue	bulk	16
00489025;7;8	CAT5/6 insulation grommet; green; black; anthracite	bulk	16



NETWORK CABLE CAT 7

INSTALLATION



High-quality network cable with CAT7 cable and compact CAT6A RJ45 plugs for professional installations. The cables have been designed for high-speed networks of up to 10 gigabits. The plugs are fitted with latching lever protection and have gold-plated contacts. Each cable has been individually tested on the basis of ISO/IEC11801.

- Cable: CAT7 AWG26 S/FTP
- Plug: RJ45 CAT6A with latching lever protection
- Diameter: approx. 6mm
- Bandwidth: 500 MHz
- Utilization: 10/100/1000BASE-T, 10 GBASE-T
- Configuration: 1:1
- Item check on the basis of CAT6A ISO/IEC11801
- 24c gold-plated contacts
- Functional packaging
- Construction fully compliant to CE and RoHS regulation

ITEM NO		LENGTH	MOC KÇ S DPH
009250005	RJ45 <-> RJ45; SF-UTP	0,5m	144
009250001	RJ45 <-> RJ45; SF-UTP	1,0m	170
009250002	RJ45 <-> RJ45; SF-UTP	2,0m	222
009250003	RJ45 <-> RJ45; SF-UTP	3,0m	275
009250005	RJ45 <-> RJ45; SF-UTP	5,0m	373
009250008	RJ45 <-> RJ45; SF-UTP	8,0m	535
00925010	RJ45 <-> RJ45; SF-UTP	10,0m	641
00925015	RJ45 <-> RJ45; SF-UTP	15,0m	901
00925020	RJ45 <-> RJ45; SF-UTP	20,0m	1.150

QUALITY MANAGEMENT



FIREWIRE CABLE

PREMIUM



The Firewire cable (also IEEE 1394, DV or i-link cable) for data rates of up to 400 Mbit/s is ideal for connecting peripheral devices, such as cameras and hard disks etc, to the DVD recorder, TV or PC.



ITEM NO		LENGTH	MOC KÇ S DPH
01071003	Premium Firewire Cable 4p <-> 4p	3,0m	553
01071101	Premium Firewire Cable 4p <-> 6p	1,0m	297
01071103	Premium Firewire Cable 4p <-> 6p	3,0m	553
01071105	Premium Firewire Cable 4p <-> 6p	5,0m	793
01071201	Premium Firewire Cable 6p <-> 6p	1,0m	297
01071202	Premium Firewire Cable 6p <-> 6p	2,0m	417

HIGHEST POSSIBLE PRECISION


In our product design we do everything to ensure excellent Quality from the outset. We subject our products to intense scrutiny and continuously carry out quality controls during the production process. For example, we inspect all materials for compliance with the acceptable quality level (AQL), the standard for "imported" materials and finished products. We check the tolerances of each individual part, the print quality, the colours and the construction. We investigate chemical and hazardous substances in accordance with RoHS and REACH. We test the electrics for short circuits and configuration at each production step. We carry out both functional and mechanical tests. And, of course, we test the live performance. This is what we mean by maximum precision



DIRECTIVES


All our products comply with the stringent RoHS directive. RoHS (Restriction Of Hazardous Substances) is an EU directive (2011/65/EG) aimed at reducing the use of substances in electronic devices that are harmful to health and the environment.

The European REACH ordinance is intended to protect people and the environment from harmful chemicals. Among other things, REACH specifies the obligation to provide information on substances of particular concern in order to minimise their use.




MULTI-4 HIGH SPEED USB

WHITELINE



4 way Multi USB Cable to connect devices with different USB jacks, such as Smartphone, Tablet, Laptop, PC or charger. A high data rate of up to 10 Gbps allows a fast data synchronization. The cable is equipped on both sides with adapters for various plug combinations.

- 4 way Multi USB Cable for highest flexibility
- Modern design
- Braided jacket for extra protection
- Robust plugs with metal housing
- Adapters are fixed by a ring noose



ITEM-NO	LENGTH	Special Offer POA
010422010 Multi-4 High Speed USB	1,0m	Special Offer POA

USB 3.1 SUPERSPEED + GENERATION 2

WHITELINE



USB 3.1 cable for ultra-fast synchronisation and charging. Future-proof thanks to support for high data speeds (10 Gbit/s). Fast charging mode (FAST): Use the quick charging mode when using suitable chargers (> 3A)

Standard mode: If you connect your mobile device to a PC or laptop, use the standard mode to protect your devices from excessive charging currents.

- New reversible USB Type-CTM plug
- Latest USB 3.1 standard
- Charging function up to 3 ampere (switchable)
- Data exchange / synch up to 10 Gbit/s
- Moulded plugs

ITEM-NO	LENGTH	Special Offer POA
010423075 USB 3.1G2 Cm<->Am SWITCH	0,75m	Special Offer POA

USB A <-> MICRO B KABEL LED | HIGH SPEED

WHITELINE



High Speed USB cable for quick synchronisation and charging of smartphones, tablets, power banks, etc. Also suitable for tablets with higher power consumption. The illumination effect in the plug is a special feature. Green indicates USB power supply. Red means the connected device is charging or is consuming electricity. For technical reasons, it is possible that at the end of a charging cycle, the LED flashes green and red and the green lamp (= charged) lights up already at 95%.

- LED light in the plug
- charging function
- data synchronisation
- gold plated contacts
- fully shielded

ITEM-NO	LENGTH	Special Offer POA
0104230810 Whiteline USB-A <-> Micro USB-B LED	1,0m	Special Offer POA

USB A <-> MICRO B KABEL | HIGH SPEED

WHITELINE



High Speed USB cable for quick synchronisation and charging of smartphones, tablets, powerbanks, etc. Also suitable for tablets with higher power consumption. particular highlight is the design of the braiding.

- charging function
- data synchronisation
- gold plated contacts
- fully shielded
- high quality braid in „wave optics“

ITEM-NO	LENGTH	Special Offer POA
010424011 Whiteline USB-A <-> Micro USB-B	1,0m	Special Offer POA



USB A <>
LIGHTNING-ADAPTER

WHITELINE



USB cable for connecting devices with Lightning (Apple) to a computer or laptop etc. For quick syncing and charging. Also suitable for tablets with high power consumption.

- USB-A <> Apple Lightning
- Charging function
- Data synchronisation

ITEM-NO	LENGTH
010392120	1,2m Special Offer POA

STEREO KLINKEKABEL
HOCHFLEXIBEL &
SUPER SOFT

WHITELINE



Highly flexible and super soft audio cable for connecting portable devices such as smartphones, tablets, MP3 players to amplifiers, AV receivers and car radios etc. The gold plated contacts minimize contact resistance, protect against corrosion and improve the signal transmission.

- Super soft
- Highly flexible
- Gold plated contacts
- Stereo

ITEM-NO	LENGTH
01043001	1,0m Special Offer POA

STEREO KLINKEKABEL
HOCHFLEXIBEL | 90°

WHITELINE



Highly flexible phone plug audio cable with additional foil shield against external interference for the connection of portable devices (tablet PCs, MP3 players, etc.) to AV receivers. The gold-plated contacts also improve signal transmission and minimize contact resistance.

- Gold-plated contacts
- Additional foil shielding
- Stereo
- Highly flexible
- 90° angled plug

ITEM-NO	LENGTH
0104310752 Rot	0,75m Special Offer POA

HIGH SPEED HDMI CABLE

WHITELINE



The High Speed HDMI cable from the in-akustik WHITE LINE-series supports all HD audio formats and resolutions up to 2160p (4K).

- Ethernet Network (up to 100 Mbit)
- Audio Return Channel
- Additional Color Spaces
- 0,08mm² data line
- Data rate: up to 18 Gbit/s (340 MHz bandwidth)
- 4K-Support (2160p)
- 3D-compatible
- Content Type
- Supports HD Audio
- Lip Sync: automatic synchronisation
- CEC-, HDCP-, EDID- compatible
- Supports x.v. Color und Deep Color multibit (up to 48 Bit)
- Audio: up to 8 channels (24Bit/192kHz)

ITEM-NO	LENGTH
010527502	1,75m Special Offer POA
010527503	3,0m Special Offer POA

ANTENNA CABLE

WHITELINE



This HDTV antenna cable is especially designed for the requirements of high resolution television formats (HDTV). The 4-fold 120 dB shielding protects the sensitive signal content. It is suitable for installing BK, SAT and cable TV systems as well as for connecting DVB-T/-S/-C receivers. The space-saving angle plugs round off the product.

- 4 fold shielding
- DVB-T/C/S compatible
- 120 dB shielding
- HDTV compatible
- 24c gold plated contacts
- 3 GHz Bandwidth
- Ferrite cores against interference
- 75 Ohm Impedance

ITEM-NO	LENGTH
01044015	1,5m Special Offer POA

OPTICAL CABLE

WHITELINE



The optical cable from the in-akustik White-Line Series is equipped with Toslink connectors for connecting digital audio sources such as CD, DVD, Blu-ray players or game consoles to AV receivers, etc. A high quality nylon fiber ensures unobstructed signal transport. A triple shielding reduces external interference to a minimum.

- High Quality TOS LINK Plugs
- Nylon Optical Fiber
- Threefold protected
- Metal Plug
- With protection cap

ITEM-NO	LENGTH
01041318	1,75m Special Offer POA

USB AC POWER ADAPTER

WHITELINE



High-quality, universal USB power adapter for mobile devices such as smartphones, tablets, cameras or power banks etc. Optimum travel companion due to its wide voltage range of 100–240 V.

- Universal use
- Intelligent overload protection
- Over-temperature protection
- Plug & Play
- Input: 100–240 V AC | 50–60 Hz | 0.2 A max.
- Output: 5 V–1.0 A
- Dimensions: 45.5 x 35.4 x 23.4 mm
- Conforms to CE
- RoHS conformity

USB CAR POWER ADAPTER

WHITELINE




High-quality, universal USB power adapter for the convenient and time-saving charging of mobile devices such as smartphones, tablets, cameras or power banks etc. during car journeys.

- Universal use
- Intelligent overload protection
- Over-temperature protection
- Plug & Play
- Input: 12–24 V DC (cigarette lighter)
- Output: 5 V–1.0 A
- Conforms to CE
- RoHS conformity

ITEM-NO	UNIT
010450002 White Line USB AC Adapter 5V/1A	1 pc Special Offer POA

ITEM-NO	UNIT
010450001 White Line USB Car Adapter 5V/1A	1 pc Special Offer POA


BLU-RAY HIGHLIGHT | INCOGNITO



Incognito – far more than just a band. It was a fantastic night: with their blend of soul and jazz, funk and fusion almost 30 musicians, with several surprise guest appearances, electrified the audience. Thanks to the contagious energy and the virtuoso solo numbers, each song became something special. And as if this band hadn't given us enough variety already, the strings of the Millenia Ensemble provided a delightful additional interplay of sound. Incognito didn't just celebrate 30 years of first-rate music and continued success with this performance – they also gave their fans an unforgettable gift.

FORMAT	ITEM NO	ARTIST ALBUM
Blu-ray	0167184	Incognito : Live In London - The 30th Anniversary Concert


BLU-RAY HIGHLIGHT | AL DI MEOLA



A high point of the Moroccan music festival is without doubt the Mawazine Festival in Rabat, Morocco. Al Di Meola's fantastic appearance in 2009 also represented a summit of different cultures and religions – Al Di Meola (guitar), Peo Alfonsi (2nd guitar), Fausto Beccalossi (accordion), Gumbi Ortiz (percussion), Victor Miranda (bass), Peter Kaszas (drums), and with special guests from Morocco, Said Chraïbi (oud), Abdellah Meri (violin) and Tarik Ben Ali (percussion).

FORMAT	ITEM NO	ARTIST ALBUM
Blu-ray	0167004	Al Di Meola: Morocco Fantasia

BLU-RAY HIGHLIGHT | MICHAEL SCHENKER



in-akustik presents the World's premiere Music 4K Ultra HD Blu-ray with On A Mission – Live In Madrid. Recorded during their world tour of 2015/2016. All musical phases of Michael Schenker's career were included.



FORMAT	ITEM NO	ARTIST ALBUM
UHD Blu-ray	0164193	Michael Schenker: On A Mission - Live In Madrid


From the famous German video Laboratories
For 2D and 3D



ITEM-NO.: 0198003

PICTURE OPTIMIZER

TV Picture Optimizer is a one of a kind video reference Blu-ray that will turn your living room in to a world class theater. It upgrades contrast, sharpness, and color based on a proven and tested 11 step process developed in the laboratories of the famous German videophile magazine ,Video'. It is suitable for all flat TVs, and is full HD and HD ready.



- Suitable for TV and Beamer
- Perfect TV picture in only 11 easy steps
- Presets, picture format, color temperature, brightness, contrast, color saturation, sharpness, gamma, viewingdistance, motion compensation, audio sync
- Exclusive test patterns, combining natural pictures with measurement zones
- For the first time available both in 2D and 3D
- Interactive manual for every step of optimization
- Booklet including all important basics and support for users

PROFESSIONAL HDMI MICRO 2.0 OPTICAL FIBRE CABLE
HDMI 2.0 WITH 24GBPS | UP TO 100M



HDMI cable with professional fibre optic technology. This technology facilitates data rates of up to 24 Gbps on a transmission path of up to 100 m. The cable therefore supports high-resolution 4K formats with 50 or 60 Hz as well as HDR and is the solution for connecting devices with an HDMI 2.0 interface over great distances. The compact micro HDMI plugs are another special feature of this cable. They can be conveniently pushed through almost any empty conduit. The scope of delivery includes the corresponding adapters to type A HDMI or DVI-D. The plugs and adapters are made of metal, have a precise guide rail and can be fastened together so they form a solid mechanical unit after installation. The plug is 14.5 mm wide (diagonal) and fits through so-called M20 tubes (hoses with an inner diameter of around 17mm). Important: The running direction must be complied with!




ITEM NO	LENGTH	MOC Kč S DPH
0092431010	10m	9.335
0092431015	15m	10.194
0092431020	20m	10.730
0092431030	30m	11.911
0092431050	50m	14.164
0092431070	70m	16.954
0092431100	100m	19.529

ITEM NO	LENGTH	MOC Kč S DPH
0092432010	10m	9.872
0092432015	15m	10.730
0092432020	20m	11.267
0092432030	30m	12.447
0092432050	50m	14.701
0092432070	70m	17.490
0092432100	100m	20.066

VERSION 1



VERSION 2




Variante:





- Fibre optic technology
- Micro HDMI plugs for installing in empty conduits
- The plug is 14.5 mm wide (diagonal) and fits through so-called M20 tubes (hoses with an inner diameter of around 17mm)
- Supports HDMI 2.0 with 24 Gbps
- Supports HDCP 2.2
- EDID compatible
- High Dynamic Range (HDR)
- 4K@50/60 Hz 4:4:4 to 100 m
- ACR up to 50m
- Solid metal plug
- Including an HDMI or DVI-D adapter
- Plug & play
- Power supply via the HDMI interface
- No separate power supply unit required
- Running direction marked
- Cable diameter of just 4 mm
- Easy to lay
- CE, REACH, RoHS compliant

PROFESSIONAL HDMI MICRO 2.0 OPTICAL FIBRE CABLE
HDMI 2.0 WITH 24GBPS | UP TO 100M | ARMoured



Professional HDMI cable with fibre optic technology for data rates of up to 18 Gbps with a transmission distance of up to 100 m. The cable therefore supports high-resolution 4K formats with 50 or 60 Hz, 4:4:4 chroma subsampling as well as HDR, and is the solution for connecting devices with an HDMI 2.0 interface over large distances. Thanks to the solid armoring made of a steel helix and Kevlar threads, the cable is very resistant and can withstand tensile loads of up to 100 kg and even 200 kg for a short time. In addition, the solid metal connectors are protected by a plastic sleeve with a screw cap during transport and assembly/disassembly. The cable is therefore suitable for rough use with recurring assembly and disassembly cycles, e.g. in show and stage applications.

Special feature: Reinforcement made of Stend coil and Kevlar threads



ITEM NO	LENGTH	MOC Kč S DPH
009244001	1 m	6.545
009244002	2 m	7.082
009244003	3 m	7.297
009244005	5 m	8.155
009244008	8 m	9.335
009244010	10 m	9.872
009244015	15 m	11.589
009244020	20 m	12.125
009244030	30 m	14.379
009244050	50 m	18.349
009244070	70 m	22.641
009244100	100 m	27.684

CONNECTIONS



- Fibre optic technology
- Robust design
- Reinforcement made of a steel helix and Kevlar threads
- Plastic sleeve with screw cover to protect the plugs
- Supports HDMI 2.0B up to 24 Gbps
- Supports HDCP 2.2
- Supports EDID
- Supports High Dynamic Range (HDR)
- Supports 4K@50/60 Hz 4:4:4 up to 100 m
- Solid metal connectors
- Plug & play
- Power supply via the HDMI interface
- Low power consumption (<0.25 watts)
- No separate power supply unit required
- Transmission direction marked
- Cable diameter: approx. 5.8 mm
- CE, REACH, RoHS compliant



PROFESSIONAL HDMI 2.0 OPTICAL FIBRE-CABLE
HDMI 2.0 WITH 18GBPS | BIS 100M



INAKUSTIK PROFI HDMI LWL € 440+
Testurteil: überragend
Preis/Leistung: befriedigend
VIDEO Magazin | 12-2017

HDMI cable with professional fibre optic technology. This technology facilitates data rates of up to 18 Gbps on a transmission path of up to 100 m. It therefore supports high-resolution 4K formats with 50 or 60 Hz and is the solution for connecting devices with an HDMI 2.0 interface over great distances.

- Fibre optic technology
- 4K@50/60 Hz up to 100 m
- Supports HDMI 2.0 with 18 Gbps
- Supports HDCP 2.2
- Supports EDID
- Supports HDR
- Solid metal plug
- Plug&Play
- Power supply via the HDMI interface
- No separate power supply unit required
- Running direction marked
- Cable diameter of just 4 mm
- Easy to lay
- CE, REACH, RoHS conformant

ITEM NO		LENGTH	MOC KČ S DPH
009241001	High Speed HDMI <=> High Speed HDMI	1m	5.043
009241002	High Speed HDMI <=> High Speed HDMI	2m	5.365
009241003	High Speed HDMI <=> High Speed HDMI	3m	5.902
009241005	High Speed HDMI <=> High Speed HDMI	5m	6.545
009241008	High Speed HDMI <=> High Speed HDMI	8m	7.082
009241010	High Speed HDMI <=> High Speed HDMI	10m	7.619
009241015	High Speed HDMI <=> High Speed HDMI	15m	8.799
009241020	High Speed HDMI <=> High Speed HDMI	20m	9.013
009241030	High Speed HDMI <=> High Speed HDMI	30m	10.194
009241050	High Speed HDMI <=> High Speed HDMI	50m	12.662
009241070	High Speed HDMI <=> High Speed HDMI	70m	14.915
009241100	High Speed HDMI <=> High Speed HDMI	100m	17.490

PROFESSIONAL HDMI 2.0 CABLE



High-quality HDMI cable with stable and compact HDMI plugs for professional installation. The cables up to 5 m in length support HDMI2.0 and are suitable for applications up to the 18 Gbps (e.g. 4K60Hz 4:4:4 HDR). The 8- and 10-metre cables support HDMI1.4 and are suitable for applications up to 10.2 Gbps (e.g. 4K30Hz 4:4:4 or 4K60Hz 4:2:2). All cables are downwards compatible and support the widely used 1080p full-HD formats. Each cable is checked individually according to the corresponding specifications.

- **0,75m - 5m:** HDMI2.0 Cable
- Data rate: 18 Gbps
- Supports 4K60Hz 4:4:4 HDR
- AWG28 Cable
- Diameter: 7mm
- **8,0m - 10,0m:** HDMI1.4 Cable
- Data rate: 10.2 Gbps
- Supports 4K30Hz 4:4:4 bzw. 4K60Hz 4:2:2
- AWG26 Cable
- Diameter: 8mm

ITEM NO		LENGTH	MOC KČ S DPH
0092420075	High Speed HDMI <=> High Speed HDMI	0,75m	402
009242015	High Speed HDMI <=> High Speed HDMI	1,5m	460
00924203	High Speed HDMI <=> High Speed HDMI	3,0m	575
00924205	High Speed HDMI <=> High Speed HDMI	5,0m	719
00924208	Standard HDMI <=> Standard HDMI	8,0m	1.412
00924210	Standard HDMI <=> Standard HDMI	10,0m	1.596

PROFESSIONAL HIGH SPEED CABLE & HDMI PLUG



CABLE

- Supports HDMI 2.0a with 18 Gbps
- Ultra HD 2160p (4K@50/60 Hz x 2K Video)
- High Dynamic Range (HDR)
- Conductors made of high-purity OFC copper
- 24 AWG solid conductors
- HEC (HDMI Ethernet Channel) |
- ARC (Audio Return Channel)

PLUG

- Simple, solderless IDC method of termination
- Suitable for AWG26 and AWG24 cables
- Metal housing
- Strain-relief
- 24c gold-plated contacts

ITEM NO		UNIT	MOC KČ S DPH	
0062443000	High Speed HDMI cable with Ethernet	Price/m	50m	497
00924001	HDMI Plug	bulk		411

HDMI CABLE TESTER



The Exzellenz HDMI Cable Tester (HDMI = High Definition Multimedia Interface) is designed to check the pin connections of HDMI cables, and to correct any errors. It is ideal for checking the passage of the individual wires of an HDMI cable before it is connected to the equipment.

- Separate main and remote unit
- Review of the signals of all pins of HDMI cable
- Auto power on, ease of use
- LED indicator on both the main unit and on the remote
- Incl. carrying case

ITEM NO		UNIT	MOC KČ S DPH	
009920001	Exzellenz HDMI Cabletester	1 pc		5.900

ANTENNA

HDTV ANTENNA CABLE A++ DIN EN 50117-2-4



- Recommended and approved by Deutschen Telekom
- Suitable for return channel (Internet)
- Expanded PE dielectric
- Inner conductor: 1.0 mm bare copper
- Exterior diameter: 6.8 mm +/-0.2 mm
- Bonded film -> suitable for compression connectors etc.
- Small bending radius (50 mm)
- Capacitance: (pF/m) 55
- Velocity factor (v/c): 0.85
- Low signal attenuation
- Weight: 52 kg/km
- Descending metre imprint



ITEM NO	LENGTH	MOC KČ S DPH
006260036 Professional Antenna Cable A++ Price/m	250m	55

PROFESSIONAL ANTENNA PLUG & COAX TOOL




Professional high end F-Plug. Easy mounting without screws or crimping. The connector is simply plugged onto the prepared cable and locks itself automatically.

- Professional F-Plug
- Very short and space-saving design
- Easy mounting without screws or crimping
- Suitable for cable #006260036 or other 4.9 / 6.8mm coaxial cable with bonded foil
- Coax tool: suitable for cable #006260036 and plug #00652123
- Coax tool: with wrench to tighten the plug on the devices. Coax-Tool: passend für Cable #006260036 und Stecker #00652123

ITEM NO	UNIT	MOC KČ S DPH
00652123 Professional Antenna F-Plug	Bulk	49
00652124 Coax-Tool	Bulk	833

CAT CABLE

NETWORK CABLE CAT 6



- Separating cross between the twisted pairs
- SF-UTP (separate braided and foil shielding)
- 4 twisted pairs
- Cable diameter: 6,8 mm

ITEM NO	LENGTH	MOC KČ S DPH
004803000 CAT6; AWG24; SF-UTP; Price/m	100m	113
004890000 RJ-45 CAT5/6 Stecker; 8P8C	bulk	25
00489022;3;4 CAT5/6 insulation grommet; red; yellow; blue	bulk	16
00489025;7;8 CAT5/6 insulation grommet; green; black; anthracite	bulk	16

NETWORK CABLE CAT 7



High-quality network cable with CAT7 cable and compact CAT6A RJ45 plugs for professional installations. The cables have been designed for high-speed networks of up to 10 gigabits. The plugs are fitted with latching lever protection and have gold-plated contacts. Each cable has been individually tested on the basis of ISO/IEC11801.

- Cable: CAT7 AWG26 S/FTP
- Plug: RJ45 CAT6A with latching lever protection
- Diameter: approx. 6mm
- Bandwidth: 500 MHz
- Utilization: 10/100/1000BASE-T, 10 GBASE-T
- Configuration: 1:1
- Item check on the basis of CAT6A ISO/IEC11801
- 24c gold-plated contacts
- compliant to CE and RoHS

ITEM NO	LENGTH	MOC KČ S DPH
009250005	0,5m	144
00925001	1,0m	170
00925002	2,0m	222
00925003	3,0m	275
00925005	5,0m	373
00925008	8,0m	535
00925010	10,0m	641
00925015	15,0m	901
00925020	20,0m	1.150

SPEAKER CABLE

SPEAKER CABLE FLAME RETARDANT



- Cross section: 1,5mm² & 2,5mm²
- Structure 30 x 0.25 mm CU & 50 x 0.25 mm CU
- High flexibility due to transposed wires
- Extruded sheathing simplifies removal of the insulation
- Insulation: PVC
- Diameter: approx. 6,5mm & 9,5mm
- Flame-retardant, conforms to IEC 60332-1-2 Class E
- Conforms to RoHS Directive 2011/65/EU



FLEXIBLE PIN



- Cable cross-section: up to 6 mm²
- For safe and easy connections on clip terminals
- For crimping or soldering
- 24c gold plated

CABLE CONDUIT

CABLE CONDUIT



Hi-fi, TV and computer devices have to be connected with a great many signal and power cables. These cables can often impair the appearance or become trip hazards. This high-quality fabric cable conduit allows cables to be bundled together in an attractive manner. The conduit has been designed so that it can accommodate power cables with large (Schuko) plugs. It can be cut to the required length conveniently with a pair of scissors. One notable feature is that the fabric at the ends does not fray as easily as other conduits.

- Simple to cut
- Stabilised braid
- Reduced fraying at the ends
- Diameter: 25-38 mm

ITEM NO	LENGTH	MOC KČ S DPH
00402709	2x1,5mm ² Price/m 150m	95
00402718	2x2,5mm ² Price/m 100m	138

ITEM NO	UNIT	MOC KČ S DPH
008155	bulk	88
0081551	Set of 4	438

ITEM NO	LENGTH	MOC KČ S DPH
009210032	25-38mm Price/m 38m	278

AV PANEL TERMINALS

AV PANELS



With the Premium installation terminals, audio and video connections can be easily integrated into known switch systems and into the AmbientTrack cabling run system. Inside a terminal area, two half AV covers can be installed so that various connections and interfaces can be combined. Suitable for standard switch systems with cutout dimensions 56 x 56 mm and 71 x 71 mm. The installation or connection terminals can be replaced or extended at any time. Then you will be ideally-equipped for future needs. Stainless-steel optic.

ITEM NO	UNIT	MOC KČ S DPH
00980037016	Premium AV Panel HDMI 70	bulk 1.058
00980035016	Premium AV Panel HDMI 56	bulk 1.013
00980127016	Premium AV Panel VGA 70	bulk 1.037
00980125016	Premium AV Panel VGA 56	bulk 990

ITEM NO	UNIT	MOC KČ S DPH
00980105026	Premium AV Panel Speaker Terminal 56	bulk 1.255
00980107026	Premium AV Panel Speaker Terminal 70	bulk 1.287
00980005006	Premium AV Panel blind 56	bulk 681
00980007006	Premium AV Panel blind 70	bulk 693
00980085016	Premium AV Panel Video / Digital 56	bulk 792
00980087016	Premium AV Panel Video / Digital 70	bulk 793
00980087026	Premium AV Panel Stereo Audio 70	bulk 907
00980085026	Premium AV Panel Stereo Audio 56	bulk 869
00980085036	Premium AV Panel YUV 56	bulk 990
00980087036	Premium AV Panel YUV 70	bulk 1.034

HDMI DOUBLE COUPLING



- 24c gold-plated contacts
- HDMI (f) <-> HDMI (f)
- With assembly straps
- Angled at 90° or straight

ITEM NO		MOC KČ S DPH
0090201001	HDMI (f) <-> HDMI (f)	333
0090201000	HDMI (f) <-> HDMI (f) 90°	333

HDMI DOUBLE COUPLING WITH CABLE (ROUND)



- 24c gold-plated contacts
- HDMI (f) <-> HDMI (f)
- With 25 cm cable
- For round assembly openings (Ø 23 mm)

ITEM NO		MOC KČ S DPH
0090203025	HDMI (f) <-> HDMI (f) round	443
0090202025	HDMI (f) <-> HDMI (f)	420

VGA (SUB-D) PANEL JACK



- 24c gold-plated contacts
- 15-pin
- 3 rows
- Soldered connection

ITEM NO		MOC KČ S DPH
0090601000	VGA SUB-D 15p. (f) solderable	186

VGA (SUB-D) DOUBLE COUPLING WITH CABLE



- 24c gold-plated contacts
- 15-pin
- 3 rows
- With 25 cm cable

ITEM NO		MOC KČ S DPH
0090602025	VGA (f) <-> (f); 25 cm	159

SPEAKER TERMINAL



- 24c gold-plated contacts
- Fully-insulated
- Banana and spade lugs compatible
- For cables up to 6.0 mm²

ITEM NO		MOC KČ S DPH
0091001002	red	338
0091001007	black	338

RCA PANEL JACK



- 24c gold-plated contacts
- Soldered connection
- Grommets
- For 8 / 9.5 mm drill holes

ITEM NO		MOC KČ S DPH
0090801005	green	139
0090801003	yellow	139
0090801002	red	139
0090801007	black	139
0090801004	blue	139

RCA DOUBLE COUPLING



High-quality RCA mounting double coupling with screw thread for installing in front panels, etc. Solid design with gold-plated contacts. Allows the use of prefabricated RCA cable inside the installation. Colour coding available in five different colours.

ITEM NO		MOC KČ S DPH
0090802004	blue	150
0090802005	green	150
0090802002	red	150
0090802003	yellow	150
0090802007	black	150

AV PANEL HDMI



Premium AV cover with HDMI double coupling (round) for quick and easy installation with a HDMI cable. Stainless steel optic.

ITEM NO		MOC KČ S DPH
00980027256	25 cm round; 70x35	1.073
00980025256	25 cm round; 56x28	1.005

AV PANEL VGA



Premium AV cover with VGA double coupling for quick and easy installation with a VGA connection cable. Stainless steel optic.

ITEM NO		MOC KČ S DPH
00980125256	25 cm round; 56x28	859
00980127256	25 cm round; 70x35	906




SUPPORT RING



The support ring forms the base for all applications. It is screwed to a standard in-wall socket or surface socket. In contrast to the support ring for the AmbienTrack System #0098000, the new version #0098001 will fix the frame of the switch system by screwing the AV panels. The new support ring is suitable for all AV panels except for the version with 3 RCA jacks.

ITEM NO		MOC Kč S DPH
0098000	AV Tragering AmbienTrack	563
0098001	AV Tragering	563

IP-RAHMEN



When the the Premium AV-terminals are installed in a plaster wall, this frame forms an elegant seam to the wall.

ITEM NO		MOC Kč S DPH
009800001	Single model	451
009800002	Double model	676
009800003	Triple model	1.127

HDMI IP INSTALLATION BOX



Inexpensive HDMI wall socket for 65 mm flushmounted sockets. With a 90° angled HDMI dual coupling and white plastic frame.

ITEM NO		MOC Kč S DPH
00980018016	HDMI (f) HDMI (f) 90°	519

YOU MIGHT ALSO BE INTERESTED IN

AMBIENTECH

AmbienTech gets more out of buildings, houses and rooms where people live, work, eat and shop. It is a spatial concept that is ideal for private homes and commercial use. It offers new dimensions for interior design. You can look forward to more style, flair and personal space.

AMBIENTRACK

There is more than meets the eye – more style! Combining flexibility with design this cable conduit system ensures that switches and sockets are exactly where you need them.

AMBIENTONE

The sound coming from the walls: these flat-membrane loudspeakers can be invisibly slotted into walls and ceilings. Large box-loudspeakers are no longer necessary.



AMBIENART

The unlimited facets of light open up brand new opportunities for interior design. It requires only few technical components, which you can combine in any way you want.

Further information on AmbienTech can be found on page 64




HDMI SPLITTER 1 -> 2 HIGH SPEED



- Bandwidth up to 3 x 2.25 Gbps / 225 MHz
- Operating voltage: 230VAC / 5V or via HDMI
- Dimensions: 62 x 54 x 18 mm
- Cable length OUT: 20m

ITEM NO	MOC KČ S DPH
003247012	3.197

HDMI 2.0 SPLITTER 1 >2 HIGH SPEED | 4K



- Supports uncompressed audio formats like LPCM
- Supports HD audio formats such as DTS-HD or Dolby True HD
- Supports compressed audio formats such as DTS, Dolby Digital
- Compact size: 80 x 50 x 20 mm
- Weight: 100 g

ITEM NO	MOC KČ S DPH
004245012	4.627

PICTURE OPTIMIZER



TV Picture Optimizer is a one of a kind video reference Blu-ray that will turn your living room in to a world class theater. It upgrades contrast, sharpness, and color based on a proven and tested 11 step process developed in the laboratories of the famous German videophile magazine „Video“.

- Suitable for TV and Beamer
- Presets, picture format, color temperature, brightness, contrast, color saturation, sharpness, gamma, viewingdistance, motion compensation, audio sync
- Exclusive test patterns, combining natural pictures with measurement zones
- For the first time available both in 2D and 3D
- Interactive manual for every step of optimization
- Booklet including all important basics and support for users

ITEM NO	MOC KČ S DPH
0198003	TV/Beamer Picture Optimizer

HDMI SPLITTER 1 -> 8 HIGH SPEED




- Data rate: 10,2 Gbps
- Dimensions: 257 x 25 x 120mm
- Operating voltage: 230VAC; 5V / 16W
- Cable length IN:20m; OUT:20m

ITEM NO	MOC KČ S DPH
004245118	11.589

HDMI SPLITTER 1->2 SCALER HIGH SPEED



The integrated scaler allows older and newer devices to be combined and makes the suitable format available to each device. This ensures that a new 4K-capable TV receives a 4K format even if an older Full HD TV is being operated on the splitter at the same time. The EDID management system (EDID Engine) generates the necessary EDID data for the source automatically. Overall, the splitter ensures that the connected devices can provide the maximum performance.



ITEM NO	MOC KČ S DPH
0042451142	5.936

HDMI SWITCH




HDMI 2.0 SWITCH 3 > 1 HIGH SPEED | 4K



- Output with HDMI cable (50 cm)
- Automatic switching
- Downwardly compatible
- Supports uncompressed audio such as LPCM
- Supports compressed audio such as DTS Digital, Dolby Digital
- Supports HD audio formats such as DTS-HD and Dolby True HD
- Dimensions: 82x72x17mm
- Weight: 100 g

ITEM NO	MOC KČ S DPH
0032450314	2.052

HDMI 2.0 SWITCH 3 > 1 HIGH SPEED | 4K



- Supports uncompressed audio formats like LPCM
- Supports HD audio formats such as DTS-HD or Dolby True HD
- Supports compressed audio formats such as DTS, Dolby Digital
- Compact size: 80 x 50 x 20 mm
- Weight: 100 g

ITEM NO	MOC KČ S DPH
0042450313	3.217

HDMI SWITCH 4 > 1 HIGH SPEED | MHL



A PIP (picture-in-picture) function is provided for easier use. It shows a preview of all the connected sources on the TV or projector.



ITEM NO	MOC KČ S DPH
0042450413	4.030

HDMI MATRIX

MHL-HDMI SWITCH 3 -> 1



- 1 MHL and 3 HDMI inputs
- Range up to 750MHz / 7,5Gbps (HDMI)

ITEM NO	MOC KČ S DPH
00424505	4.668


HDMI SWITCH 4 > 1 HIGH SPEED



- EDID management (Extended Display Identification Data)
- LED display
- Operated from the device or by remote control
- 24c gold-plated contacts

ITEM NO	MOC KČ S DPH
0042450412	

HDMI MATRIX 4 X 2 HIGH SPEED | SP-DIF | 4K



- EDID Generator
- Digital audio output
- Remote control
- HDMI input on the front for mobile devices
- Bandwidth: 10.2 Gbps (340 MHz)
- Optical and coaxial S/P-DIF audio output in parallel to output A
- Eight different EDID modes

ITEM NO	MOC KČ S DPH
0062450424	8.061



MANUFACTURING OF CABLES AND ASSEMBLIES


As a medium-sized, owner-managed company with flat hierarchies, we respond quickly to market changes and especially to your individual requirements.

Profit from the wide spectrum of manufacturing possibilities of our Ballrechten-Dottingen location, our cable plant in the group and our international network of manufacturers and suppliers.



Benefit from our employees' many years of experience. Their areas of expertise cover materials procurement, logistics, product development, craftsmanship in production and goods shipping. Our employees all handle resources sparingly and have a high affinity for quality and reliability. You can find out more about our OEM solutions and our entire range of services on our website www.in-akustik.de

Some partners that we are allowed to mention:



HD BASE-T TRANSMITTER

HD BASE-T RECEIVER



HD-BASE-T TRANSMITTER IP-WALL SOCKET | POE



Converter with one HDMI input and one HD-BaseT output as well as additional Ethernet port and IR channel (forward or back). This unit powers the connected receiver via the CAT cable (PoE). For installation in mounting boxes (double boxes). Suitable for the HD-BaseT receivers with PoE power supply.

- Data rate: 10,2 Gbps
- Dimensions: 145 x 84,5mm
- Operating voltage: 100-240VAC bzw. 5VDC
- Cable length IN: 20m; OUT: 80m

HD-BASE-T RECEIVER IP-WALL SOCKET



Converter with one HD-BaseT input and one HDMI output as well as additional Ethernet port and IR channel (forward or back). For installation in mounting boxes (double boxes). Suitable for the HD-BaseT transmitters, splitters and matrix.

- Data rate: 10,2 Gbps
- Dimensions: 145 x 84,5mm
- Operating voltage: 100-240VAC bzw. 5VDC
- Cable length IN: 80m; OUT: 20m

ITEM NO	MOC KČ S DPH
009120403 Exzellenz HD-BaseT Transmitter P-wall Socket POE	15.808

ITEM NO	MOC KČ S DPH
009120304 Exzellenz HD-BaseT Receiver IP-wall Socket	12.653

HD BASE-T RECEIVER



Converter with one HD-BaseT input and one HDMI output as well as additional Ethernet port and IR channel (forward or back). Suitable for the HD-BaseT transmitters, splitters and matrix..

- Data rate: 10,2 Gbps
- Dimensions: 110 x 23,5 x 75mm
- Operating voltage: 100-240VAC bzw. 5VDC
- Cable length IN: 80m; OUT: 20m

HD BASE-T RECEIVER | POE



Converter with one HD-BaseT input and one HDMI output as well as additional Ethernet port and IR channel (forward or back). This unit is powered via the CAT cable (PoE). Suitable for the HD-BaseT transmitters, splitters and matrix with PoE support.

- Data rate: 10,2 Gbps
- Dimensions: 110 x 23,5 x 75mm
- Operating voltage: 100-240VAC bzw. 5VDC
- CableLength IN: 80m; OUT: 20m

ITEM NO	MOC KČ S DPH
009120302 Exzellenz HD-BaseT Receiver	11.540

ITEM NO	MOC KČ S DPH
009120402 Exzellenz HD-BaseT Receiver POE	14.704



HD BASE-T EXTENDER

HDMI / CAT6 EXTENDER SET



The excellent HDMI CAT Extender Set converts and transmits HDMI signals using just one CAT cable. The cable length can be up to 100 m*. This extender can be used with existing network cables in the building. Time consuming and expensive cable extensions are not necessary. In addition, standard CAT cables and plugs can be used to make and install individual cable lengths. The set consists of two converter modules (HDMI CAT / CAT HDMI) sender /receiver and two power supply units.

- HDMI via just one CAT cable
- Supports 10,2 Gbps (High Speed)
- Cable length HDMI IN/OUT: 20m
- Cable length CAT: 100m

ITEM NO	MOC KČ S DPH
009120012 HDMI / CAT6 Extender 3D	22.128

HD BASE-T MATRIX

HD BASE-T MATRIX 4 X 4



Matrix with four HDMI inputs and four HD-BaseT outputs. Each output can be routed independently to each input. It is controlled using a button on the device, by remote control or via the RS-232 interface. Supports Ethernet (2 ports) and the IR channel (forward or back) for each source. Suitable for the HD-BaseT receivers.

- Data rate: 6,75 Gbps
- 440 x 44 x 200mm
- Operating voltage: 100-240VAC bzw. 12VDC
- Cable length IN: 20m; OUT: 80m

ITEM NO	MOC KČ S DPH
009120344 Exzellenz HD-BaseT Matrix 4x4	109.851

HDMI REPEATER

HDMI 2.0 REPEATER



The Pro HDMI 2.0 repeater amplifies and improves the HDMI signal so that HDMI cables can be extended and larger distanced bridged with it. Thanks to state-of-the-art technology, the repeater supports the current 4K 60 Hz 4:4:4 formats (18 Gbps) and is backwards compatible. Using plug & play, it is simply plugged between the HDMI cables and supplied with power automatically via the HDMI port (no extra power supply unit required). The longer HDMI cable is installed between the source and the repeater and the shorter HDMI cable between the repeater and the TV/projector.

- 4K@60Hz 4:4:4 up to 25m
- 4K@30Hz up to 30m
- 1080p up to 50m
- supports HDCP2.2 & 1.4
- downwardly compatible to HDMI1.4 & 1.3
- Power supply via HDMI

ITEM NO	MOC KČ S DPH
00912004 Professional HDMI 2.0 Repeater 18 Gbps	2.746

CAT CABLE

NETWORK CABLE CAT 6



- Separating cross between the twisted pairs
- SF-UTP (separate braided and foil shielding)
- 4 twisted pairs
- Cable diameter: 6,8 mm

ITEM NO	LENGTH	MOC KČ S DPH
004803000 CAT6; AWG24; SF-UTP; Price/m	100m	113
004890000 RJ-45 CAT5/6 Stecker; 8P8C	bulk	25
00489022;3;4 CAT5/6 insulation grommet; red; yellow; blue	bulk	16
00489025;7;8 CAT5/6 insulation grommet; green; black; anthracite	bulk	16



AUDIO CONVERTER



- 16 Mbps max.
- Operating voltage: 100-240VAC bzw. 5VDC

ITEM NO		MOC KČ S DPH
01040101	Coax > Toslink; 230V AC	1.639
01040102	Toslink > Coax; 230V AC	1.780

DAC | USB POWER



- Audio: 44 / 48 / 96kHz | 24 Bit
- Dimensions: 79 x 24 x 49mm
- Operating voltage: 100-240VAC bzw. 5VDC

ITEM NO		MOC KČ S DPH
00315002		1.814

AUDIO CONVERTER ANALOG > DIGITAL



- Audio out: 48kHz | 24Bit
- Dimensions: 50 x 34 x 40mm
- Operating voltage: 100-240VAC bzw. 5VDC

ITEM NO		MOC KČ S DPH
009120502		1.977

HDMI CONVERTER HDMI > HDMI + AUDIO



- The converter extracts the audio signal from the HDMI signal and provides it to an analogue output (stereo 3.5 mm jack) and a digital output (coaxial and optical).
- The audio format can be switched between 2-channel and 5.1-channel
- 6,75 Gbps
- Dimensions: 70 x 20,5 x 66,6mm
- Operating voltage: 100-240VAC bzw. 5VDC

ITEM NO		MOC KČ S DPH
009120601		3.874

HDMI CONVERTER HDMI > FBAS + AUDIO



- The converter changes the HDMI signal to a standard analogue signal (FBAS). The output format can be switched between PAL and NTSC. An analogue audio output is also available.
- PAL (576) / NTSC (480i)
- Dimensions: 100 x 25 x 100mm
- Operating voltage: 100-240VAC bzw. 5VDC

ITEM NO		MOC KČ S DPH
009120602		5.534

HDMI CONVERTER VGA + AUDIO > HDMI



- changes the analogue VGA and stereo audio signal to an HDMI signal.
- VGA in: 800x600 / 1024x768 / 1360x768 / 1600x1200
- HDMI out: 800x600 / 1024x768 / 1360x768 / 1600x1200
- Audio out: 24 Bit / 48kHz (HDMI)
- Dimensions: 88 x 25,5 x 68mm
- Operating voltage: 100-240VAC bzw. 5VDC

ITEM NO		MOC KČ S DPH
009120603		3.557

HDMI CONVERTER VGA/AUDIO > HDMI WITH SCALER



- changes the analogue VGA and stereo audio signal to an HDMI signal
- The output format can be witched between 720p and 1080p.
- VGA in: 800x600 / 1024x768 / 1360x768 / 1600x1200
- HDMI out: 720p / 1080p
- Audio out: 24 Bit / 48kHz (HDMI)
- Dimensions: 88 x 25,5 x 68mm
- Operating voltage: 100-240VAC bzw. 5VDC

ITEM NO		MOC KČ S DPH
009120604		3.557

CONVERTER HDMI A | MINI C | MICRO D > VGA



- HDMI in: 480/576/720/1080p
- Audio in: 2 Channel 32/44.1/48kHz; 16/20/24Bit (HDMI)
- VGA out: 480/576/720/1080p
- Operating voltage: 100-240VAC bzw. 5VDC

ITEM NO		MOC KČ S DPH
009120605	HDMI A > VGA	1.587
009120606	HDMI Mini C > VGA	1.587
009120607	HDMI Micro D > VGA	1.587

IR RX/TX SET | HDMI ADAPTER



The set consists of an infrared receiver and an infrared transmitter, each with a 1.5 m cable, and is required for using the IR channels. Compatible with all Exzellenz products with an IR channel.

Using this adapter, an IR channel can be set up via an HDMI cable in conjunction with the Exzellenz IR RX/TX set. Suitable for the Exzellenz 4x4 HDMI Matrix.

ITEM NO		MOC KČ S DPH
009129901	IR RX/TX Set	1.113
009129902	IR HDMI Adapter	465

WALL PILLAR | BASIC PROFILE



The AmbienTrack wall pillar is made of aluminium and can be installed at half room height or at full room height. The wall pillar is used for guiding cables and for fitting installation components. The fixed installation of main circuits into the rooms ends in the wall pillar. The transition from a classic installation to flexible cabling is therefore effected in the wall pillar. It can be installed both surface-mounted and flush-mounted in the wall.

ITEM NO	LENGTH	MOC KČ S DPH
0011002 wall pillar high; alu optic	900 mm	-
0011004 wall pillar high; alu optic	1.800 mm	-

CORNER PILLAR | BASIC PROFILE



The corner pillar is also fully made of aluminium and can be installed at half-height or room height in corner spaces. It boasts the same installation options as the wall pillar, and is also well suited for vertical installation over several floors. The same cover panels are used as for the wall pillar.

ITEM NO	LENGTH	MOC KČ S DPH
0011201 corner pillar; alu optic	900 mm	-
0011203 corner pillar; alu optic	1.800 mm	-

WALL PILLAR FLAT | BASIC PROFILE



The flat wall pillar is made of aluminium and can be installed at half room height or at room height, and is solely for cable routing. It can be installed both surface-mounted and flush-mounted in the walls.

ITEM NO	LENGTH	MOC KČ S DPH
0010803 wall pillar flat; alu optic; anodized	900 mm	-

SKIRTING BOARD | BASIC PROFILE + COVER



The AmbienTrack skirting board is used for horizontal distribution of cables in a room, which generally lead out of an AmbienTrack pillar. It is however also possible to feed into an AmbienTrack skirting board directly from the wall.

ITEM NO	LENGTH	MOC KČ S DPH
0010004 skirting board; alu optic	1.800 mm	-
0010005 skirting board; alu optic	1.800 mm	-

SKIRTING BOARD DUCT | BASIC PROFILE



- No need for earthing when using the tool box
- special geometry for integration in drywall constructions
- Replaces the floor skirting board
- Can be installed directly on screed flooring (replacement of the flooring without removing the duct).
- Variable positioning of sockets and installation devices along the wall
- Shadow gaps on both sides create a free-floating impression
- Screwless clip cover assembly
- Complete camouflaging of the baseboard by the cover (no longitudinal joint)
- Option of indirect LED lighting (light lines on both sides)

The AmbienTrack skirting board duct is installed on the floor and is a horizontal guide for cables, as well as a fitting for installation components near floor level. Combined with drywall construction, it is possible to partially integrate the skirting board duct into the wall.

ITEM NO	LENGTH	MOC KČ S DPH
0010202 skirting board duct; Basic profile; alu optic; anodized	625 mm	-
0010204 skirting board duct; Basic profile; alu optic; anodized	1.875 mm	-





COVER



The same aluminium covers are used for the wall duct, corner duct, skirting board duct and the flat wall duct baseboard. There are two standard surface finishes (natural anodised and stainless steel). The covers are clipped onto the baseboard without screws. To match the various installation products and light modules, there are covers with the corresponding perforations. A special design feature is the frame-free installation of standard switch systems.

ITEM NO		LENGTH	MOC KČ S DPH
00114501	Cover System 56 alu optic / 1 cutout	900 mm	-
00114503	Cover System 56 alu optic / 2 cutout	900 mm	-
00114505	Cover System 56 alu optic / 3 cutout	900 mm	-
00114507	Cover System 56 alu optic / 4 cutout	900 mm	-
00114508	Cover System 56 alu optic / 5 cutout	900 mm	-
00114504	Cover System 56 alu optic / 2 cutout	2.250 mm	-
00114506	Cover System 56 alu optic / 2+1 cutout	2.250 mm	-

ITEM NO		LENGTH	MOC KČ S DPH
00114601	Cover System 65 alu optic / 1 cutout	900 mm	-
00114603	Cover System 65 alu optic / 2 cutout	900 mm	-
00114604	Cover System 65 alu optic / 3 cutout	900 mm	-
00114605	Cover System 65 alu optic / 4 cutout	900 mm	-
00114606	Cover System 65 alu optic / 5 cutout	900 mm	-

ITEM NO		LENGTH	MOC KČ S DPH
00114701	Cover System 71 alu optic / 1 cutout	900 mm	-
00114703	Cover System 71 alu optic / 2 cutout	900 mm	-
00114704	Cover System 71 alu optic / 3 cutout	900 mm	-
00114705	Cover System 71 alu optic / 4 cutout	900 mm	-
00114706	Cover System 71 alu optic / 5 cutout	900 mm	-

ITEM NO		LENGTH	MOC KČ S DPH
00114003	Cover without cutout alu optic	900 mm	-

TOOL BOX



The tool box allows installation components such as switches, sockets, computer and speaker connections, sensors, operating elements and so on to be installed modularly in any combination in the AmbienTrack wall ducts, corner ducts and skirting board ducts. Furthermore, the tool box can be used as a distributor and branching box. The installation of power supply units and electronic components, e.g. for building automation, is also possible.

ITEM NO		UNIT	MOC KČ S DPH
0013051	A-Track Tool Box; 56mm 1 cutout	1 Set	-
0013052	A-Track Tool Box; 56mm 2 cutout	1 Set	-
0013053	A-Track Tool Box; 56mm 3 cutout	1 Set	-
0013054	A-Track Tool Box; 56mm 4 cutout	1 Set	-
0013055	A-Track Tool Box; 56mm 5 cutout	1 Set	-

ITEM NO		UNIT	MOC KČ S DPH
0013061	A-Track Tool Box; 65mm 1 cutout	1 Set	-
0013062	A-Track Tool Box; 65mm 2 cutout	1 Set	-
0013063	A-Track Tool Box; 65mm 3 cutout	1 Set	-
0013064	A-Track Tool Box; 65mm 4 cutout	1 Set	-
0013065	A-Track Tool Box; 65mm 5 cutout	1 Set	-

ITEM NO		UNIT	MOC KČ S DPH
0013071	A-Track Tool Box; 71mm 1 cutout	1 Set	-
0013072	A-Track Tool Box; 71mm 2 cutout	1 Set	-
0013073	A-Track Tool Box; 71mm 3 cutout	1 Set	-
0013074	A-Track Tool Box; 71mm 4 cutout	1 Set	-
0013075	A-Track Tool Box; 71mm 5 cutout	1 Set	-

ITEM NO		UNIT	MOC KČ S DPH
0013001	A-Track Tool Box blind size like 1 cutout	1 Set	-
0013002	A-Track Tool Box blind size like 2 cutout	1 Set	-
0013003	A-Track Tool Box blind size like 3 cutout	1 Set	-
0013004	A-Track Tool Box blind size like 4 cutout	1 Set	-
0013005	A-Track Tool Box blind size like 5 cutout	1 Set	-





DEVICE SUPPORT



The AmbienTrack device support is installed on the skirting board and allows you to vary the position of sockets, a computer or multimedia connections. It can also be easily added to at a later date.

ITEM NO		UNIT	MOC KČ S DPH
0013200	Device support SET without cutout ALU	1 Set	-
0013251	Device support SET System 56 ALU	1 Set	-
0013261	Device support SET System 65 ALU	1 Set	-
0013271	Device support SET System 71 ALU	1 Set	-


COVER WITH CABLE OUTLET



Cover panel for wall and corner pillar with universal outlet. For example, for wiring the flat screen or the surround speakers.

ITEM NO		UNIT	MOC KČ S DPH
0011490	Cover alu optic; with cable outlet	1 pc	-

MOULDINGS FOR WALL PILLAR



The mouldings allow any combination of transitions between the wall or corner columns and the skirting board or skirting duct. Each moulding consists of a half base profile (left and right), and is plugged onto the respective baseboard of the wall or corner column using coupling pins (included in the set).

Example: A transition between a wall column and a skirting board on the left, and an on-wall skirting duct on the right is assembled as follows:
1 x 0011017 A-Track wall column, high moulding transition SL LEFT
1 x 0011018 A-Track wall column, high moulding transition SK on-wall RIGHTS

ITEM NO		MOC KČ S DPH
0011014	wall pillar high; moulding closed right / left	-
0011016	wall pillar high; moulding transition skirting board right	-
0011017	wall pillar high; moulding transition skirting board left	-

ITEM NO		MOC KČ S DPH
0011018	wall pillar high; moulding transition skirting board duct on-wall right	-
0011019	wall pillar high; moulding transition skirting board duct on-wall left	-
0011020	wall pillar high; moulding transition skirting board duct in-wall right	-
0011021	wall pillar high; moulding transition skirting board duct in-wall left	-

MOULDING FOR CORNER PILLAR



SKIRTING BOARD OUTSIDE CORNER 90°



ITEM NO		UNIT	MOC KČ S DPH
0011208	corner pillar high; moulding closed right / left	1 pc	-
0011210	corner pillar high; moulding transition skirting board right	1 pc	-
0011211	corner pillar high; moulding transition skirting board left	1 pc	-

ITEM NO		UNIT	MOC KČ S DPH
0010008	skirting board; alu optic	1 pc	-



SKIRTING BOARD END SECTIONS



ITEM NO	UNIT	MOC KČ S DPH
0010010	A-Track skirting board; alu optic; left	1 pc -
0010009	A-Track skirting board; alu optic; right	1 pc -

END SECTION FOR CORNER PILLAR



ITEM NO	UNIT	MOC KČ S DPH
0011205	A-Track corner pillar; alu optic	1 pc -

END SECTION FOR WALL PILLAR AND FLAT WALL PILLAR



ITEM NO	UNIT	MOC KČ S DPH
0011009	wall pillar high; alu optic (old version)	1 pc -
0010804	wall pillar flat; alu optic	1 pc -

STRAIN RELIEF FOR TOOL BOX



ITEM NO	UNIT	MOC KČ S DPH
00190003	A-Track strain relief (M5861)	1 pc -

AMBIENART

LED STRIP



For installation in the shadow gap of the AmbientTrack ducts (wall duct, corner duct, skirting board, skirting duct, device support, TV wall duct) there are LED strips in a variety of designs. Monochrome strips in the colours white, warm white and blue can be clipped into the profiles – no need for tools. They are supplied directly using appropriate 24 volt power supply units from the AmbientTrack range, or using the AmbientTrack controller/dimmer. In addition, the LED strip is also available in a RGB version. This allows the light lines to be realised in any imaginable colour and even with dynamic changes of

colour. The RGB strip is clipped into the AmbientTrack profile together with a small retaining profile and activated using the AmbientTrack controller/dimmer. A comprehensive range of accessories, such as connector or coupling pieces, is available for the LED strips. A flexible LED strip with the three base colours red, green and blue for individual and variable colour palettes. Dust and water proof, moulded with a self-adhesive rear side for universal use. The short LED intervals of just 25 mm provide a high luminosity and evenly distribute the illumination. The strips are easy to combine by joining together.

ITEM NO	LENGTH	MOC KČ S DPH
0015201	LED strip RGB 24V (447x10/2xPCB connector/ESD)	450 mm -
0015202	LED strip RGB 24V (897x10/2xPCB connector/ESD)	900 mm -

ITEM NO	LENGTH	MOC KČ S DPH
0015021	LED strip WP 24V / white	450 mm -
0015031	LED strip WP 24V / warm white	450 mm -
0015022	LED strip WP 24V / white	900 mm -
0015032	LED strip WP 24V / warm white	900 mm -




LED CUBE



The LED cubes have an edge length of just 30 mm, can be rotated by 360°, can be individually combined and can be placed and replaced on the AmbienTrack profiles anytime. The matching jacks with the LED circuit electronics are installed ready to connect to the AmbienTrack tool boxes. The focused light beam from the cube, with an illumination angle of 20°, is generated using power LED technology. The power is supplied and the cube activated using the 24-volt power supply unit and the controller/dimmer from the AmbienTrack range. Ceilings, walls, accessories and even entire rooms can now be accentuated with cool or warm light colours according to pReferenz

ITEM NO		UNIT	MOC KČ S DPH
0015401	LED cube monochrom 350mA/1W 90° white	1 pc	-
0015402	LED cube monochrom 350mA/1W 90° warm white	1 pc	-
0015405	LED cube monochrom 350mA/1W 90° green	1 pc	-

LED CUBE | PLUG-IN BASE



The AmbienArt plug-in base performs both the electrical adjustment as well as the mechanical adaptation of the LED cubes. They fit into the AmbienTrack tool box perfectly, where an adapter fitting guides the pluggable connections out of the tool box. In combination with the in-wall covers, available separately, the plug-in base and the LED cube can be installed in standard in-wall sockets independently of the AmbienTrack system. There are three different base modules:

1) AMBIENART PLUG-IN BASE MASTER MONOCHROME

The Master plug-in base contains the constant current converter required for the LED cube (24 volt / 350 mA) and can be dimmed by PWM. A DIP switch allows you to decide which system channel the LED cube reacts to. The Master plug-in base can power up to four further LED cubes using Slave plug-in bases.

ITEM NO		UNIT	MOC KČ S DPH
0015510	plug in base monochrome; 1 gang Master	1 pc	-
0015511	plug in base monochrome; 1 gang Slave	1 pc	-
0015513	plug in base monochrome; 2 gang Master/Slave	1 pc	-
0015514	plug in base monochrome; 2 gang Master/Master	1 pc	-
0015551	plug in base RGB 1 gang Master	1 pc	-
0015552	plug in base RGB 2 gang Master	1 pc	-
0015593	LED cube plug base connecting adapter for toolbox	1 pc	-

2) AMBIENART PLUG-IN BASE SLAVE MONOCHROME

The Slave plug-in base is for extending the Master plug-in base (see above). It can also be used as a purely mechanical plug-in base for activating the LED cubes using other systems. CAUTION: In this case, it must be activated using 350 mA constant current!

3) AMBIENART PLUG-IN BASE RGB

This plug-in base has been designed especially for the LED cubes RGB. It contains a separately-dimable constant current converter for every colour channel (red, green and blue). It is activated using PWM.

ITEM NO		UNIT	MOC KČ S DPH
0015603	plug in base; BOX 2 gang Master/Slave	1 pc	-
0015604	plug in base; BOX 2 gang Master/Master	1 pc	-
0015607	plug in base; BOX 3 gang Master/Master/Master	1 pc	-
0015651	plug in base; BOX 1 gang; RGB	1 pc	-
0015652	plug in base; BOX 2 gang; RGB	1 pc	-



LED WALL SPOTLIGHT



A powerful LED spotlight in monochrome and RGB versions which is integrated into the end sections of the wall and corner pillars, as well as the device support. The beam of light emerging from the front face of the profile is generally directed towards the ceiling, and produces a fascinating light reflection on the wall – in particular during the dynamic colour changes. The power is supplied and the cube activated using the 24-volt power supply unit and the controller/dimmer from the AmbientTrack range.

ITEM NO		UNIT	MOC KČ S DPH
0015802	wall pillar ALU 350mA/1W white	1 Set	-
0015821	corner pillar ALU 350mA/1W blue	1 Set	-

LED-RGB-CONTROLLER




The AmbienArt light system is controlled by a RGB controller, which takes care of the colour setting, changing the colour or dimming the light components. The controller is elegantly integrated into the wall pillars along with the tool box and can be easily operated by remote control. The power is supplied using the 24-volt system power supply unit. The controller's user interface is very high quality and has a clear layout, and can be combined with any switches and sockets..

ITEM NO		UNIT	MOC KČ S DPH
0016605	RGB Controller 2432 PWM / 12-24V/3x2A / 56	1 Set	-
0016606	RGB Controller 2432 PWM / 12-24V/3x2A / 65	1 Set	-
0016607	RGB Controller 2432 PWM / 12-24V/3x2A / 71	1 Set	-
0016600	RGB Controller 2432 PWM / 12-24V/3x2A / PCB	1 Set	-
0016620	RGB Repeater	1 Set	-
0017002	AC-Adapter 230V -> 350mA / 6W	1 pc	-
0017102	AC-Adapter 90-264V AC>24V DC/0,84A/20W	1 pc	-
0017103	AC-Adapter 90-264V AC>24V DC/2,5A/60W	1 pc	-
0017104	AC-Adapter 90-264V AC>24V DC/4A/96W	1 pc	-
0017105	AC-Adapter 90-280V AC>24V DC/6,3A /150W	1 pc	-
0017110	AC-Adapter 90-264V AC>24V DC/2,5 A/60W RGB	1 pc	-



AMBIENTONE NO.4 | NO.1



AmbienTone is a flat panel loudspeaker in a modified gypsum plasterboard. It is installed in drywall constructions. In very few work steps. Once connected, fitted and sealed, AmbienTone can be wallpapered over, painted and even plastered over. A coat with a thickness of up to 2 mm will result in only a minimal loss of sound quality.

- AmbienTone is a flat-membrane loudspeaker based on a bending wave convertor.
- Also suitable for wet rooms (bathroom, wellness, etc.).
- Ideal for multiroom and home cinema applications.
- Can be used in both private and public areas (restaurants, galleries, etc.).
- Large box-loudspeakers are no longer necessary.
- The speakers can be connected to any amplifier or hi-fi system.

	NO.4	NO.1 (100V)
- Power:	60 Watts	25 Watts (6/12/20/25 Watts adjustable)
- Impedance:	6 Ohm	
- Frequency range:	80–18.000 Hz	80–18.000 Hz
- Sensitivity:	92,5 dB	85 dB (1W/m)
- Overload protection	Yes	Yes
- Size:	625 x 500 x 44 mm	700 x 500 x 44 mm
- Weight:	5,5 kg	5,8 kg
- System:	2 ways	2 ways
- Dispersion angel:	H x V 180° x 180°	H x V 180° x 180°
- Connection:	10 m speaker cable	10m speaker cable
- Max. SPL:	108 dB	102 dB
- Plasterboard:	12,5 mm	12,5 mm



ITEM NO		UNIT	MOC Kč S DPH
0025004	AmbienTone No.4; 2 ways; 6 Ohm; 60 Watts	1 pc	53.115
0025004100	AmbienTone No.4; 2 ways; 100 Volt; 60 Watts	1 pc	57.836
0025001100	AmbienTone No.1; 2 ways; 100 Volt; 25 Watts	1 pc	53.544

AMBIENTONE NO.6



AmbienTone No.6 is a speaker module for invisible integration in solid walls. The flat-panel speaker constructed according to the principle of the bending wave converter. The module is embedded into a niche constructed in the wall and plastered over completely. Available as an option in a 100 V model. Note: the design of the AmbienTone No.6 module ensures an extremely high decoupling between the membrane surface and the surrounding surface of the wall. However, structure-borne sound which spreads through the walls can still occur, depending on the construction and workmanship of the masonry. Before installing the panel, check the static function of the wall you would like to use.

- Power:	40 Watt	- Weight:	ca. 3,5 kg
- Impedance:	4 Ohm	- System:	2 Wege
- Frequency range:	80–18.000 Hz	- Dispersion angel:	H x V 180° x 180°
- Sensitivity:	85 dB	- Connection:	10 m speaker cable
- Overload protection	Ja	- Carrier:	Foam membrane
- Size:	435 x 570 x 45 mm		

ITEM NO		UNIT	MOC Kč S DPH
0025006	AmbienTone No.6	1 pc	49.896

AMBIENTONE NO.2



The AmbienTone No. 2 universal modules blend in indiscernably with panelling materials such as MDF, wood or chipboard. Panelling materials such as parts of a multimedia wall, or wall or ceiling cladding sections, are prepared in a way which allows the self-adhesive AmbienTone No. 2 to be installed on the back of these and the front side of the panelling material is used as a surface membrane. This means the AmbienTone No. 2 surface loudspeaker can be integrated into wood panelling, furnishings, etc., remaining out of sight and without visible joints.

- Power:	40 Watts	- Weight:	ca. 3,5 kg
- Impedance:	4 Ohm	- System:	2 ways
- Frequency range:	80–18.000 Hz	- Dispersion angel:	H x V 180° x 180°
- Sensitivity:	85 dB (1 Watt/1m)	- Connection:	10 m speaker cable
- Overload protection	Yes	- Version:	Self-adhesive membrane
- Size:	435 x 570 x 45 mm		

ITEM NO		UNIT	MOC Kč S DPH
0025002	AmbienTone No.2	1 pc	43.887



AMBIENTONE SUB NO.2



This speaker is specialized for deep bass reproduction and can be perfectly combined with the Ambientone panels No.4, No.2, and No.1. This hi-tech in-wall subwoofer features a very low structure-borne sound thanks to its special design. Wall vibrations and the transmission of noise to neighbouring rooms are therefore reduced to a minimum, even without additional decoupling. The front of the subwoofer consists of a gypsum plasterboard. In the same way as Ambientone No.4, it is screwed onto the substructure of drywall constructions and plastered over flush with the surrounding plasterboard. A 10 mm narrow slit acts as a sound outlet and can be positioned inconspicuously above the skirting board or close to the ceiling. The integrated special switch enables a direct connection to a standard amplifier.

- Power: 2 x 100 Watts max.
- Impedance: 2 x 6 Ohm
- Frequency range: 38–100Hz
- Sensitivity: 85 dB
- Size: 500 x 625 x 86 mm
- Installation depth: 73 mm
- Cutout: 435 x 570 mm
- Weight: 9 kg
- System: Passive stereo system
- Crossover: Integrated special cross switch
- Connection: 2 x 10 m speaker cable
- Max. SPL: 108 dB
- Carrier: 12,5 mm plasterboard

ITEM NO	UNIT	MOC KČ S DPH
0025202 Ambientone Sub No.2	1 pc	81.228

AMBIENTONE NO.8



- Möbellautsprecher
- Für Plattenwerkstoffe wie MDF-Holz-/Spanplatten
- Inkl. 10m Speaker Cable
- Abstrahlwinkel: HxV 180°x180°
- Gewicht: ca. 1,2 kg
- Überlastschutz
- 2-Wege
- 320 x 360 x 45 mm
- Sonderanfertigungen auf Anfrage

ITEM NO	UNIT	MOC KČ S DPH
0025008 Ambientone No.8	1 pc	48.179

AMBIENTONE Q1



The Ambientone Q1 is a high-quality 2-way built-in loudspeaker with outstanding sound properties. The quick-lock system facilitates, and saves a lot of time during, assembly. The speaker can be used in stereo applications, as complete home cinema systems or as multi-room installations. The loudspeakers can be used everywhere: in the kitchen, bath and living room, as well as in all other living areas. They can also be used in conference rooms, restaurants, hotel facilities, shops or health spas etc.

- Power: 50 Watts
- Impedance: 8 Ohms
- Frequency range: 61 Hz–20 kHz
- Sensitivity: 87 dB
- Dimensions: 310 x 196 x 79,3 mm
- Cutout: 286 x 172 mm
- Installation depth: 72,3 mm
- Sub-woofer/mid-range driver: 6 1/2" (16,5 cm)
- Tweeter: 20 mm Soft Dome
- Tuneable: Tweeter 0/-3/-6 dB
- Weight: ca. 1,4 kg
- System: 2 ways
- Locking: Quick-lock, operated from the front
- Membrane material: PP (Polypropylen)
- Conform to CE

ITEM NO	UNIT	MOC KČ S DPH
0024201 50 Watts; rectangular; 310 x 196 x 80 mm	pair	3.745

AMBIENTONE R1




The Ambientone R1 is a high-quality 2 way built in ceiling and wall loudspeaker. It can be used in stereo applications, as complete home cinema systems or as multi-room installations. The loudspeakers can be used everywhere: in the kitchen, bath and living room, as well as in all other living areas. They can also be used in conference rooms, restaurants, hotel facilities, shops or health spas etc.

- Power: 50 Watts
- Impedance: 8 Ohms
- Frequency range: 72 Hz–20 kHz
- Sensitivity: 86 dB
- Dimensions: Ø 240 mm
- Cutout: Ø 205 mm
- Installation depth: 68 mm
- Sub-woofer/mid-range driver: 6 1/2" (16,5 cm)
- Tweeter: 13 mm Dome
- Weight: ca. 1 kg
- System: 2 ways
- Locking: Hooks with screws accessible from the front
- Membrane material: PP (Polypropylen)
- Conform to CE

ITEM NO	UNIT	MOC KČ S DPH
0024001 50 Watts; round; 240 x 68 mm	pair	2.886






REFERENZ SELECTION - AIR TECHNOLOGY

The AIR technology is a milestone in our more than 40-year company history and is causing a worldwide sensation in the hi-fi industry. The approach sounds relatively banal: Physical losses must be minimized in order to transmit the original music signal as unchanged and neutral as possible. And AIR technology comes closer than ever to lossless transmission. It leads to significantly better sound reproduction, which is not only subjectively audible, but also objectively measurable.

The insulation or dielectric of the AIR cables is almost perfect thanks to the air insulation and hardly influences the sound any more. The construction, dimensions and arrangement of the conductors are optimized and fully exploit what is physically feasible.

The air-helix construction is wholly unique. We have developed a special clip to ensure air insulation that is as close to perfection as possible. A large number of these clips form the supporting structure on the inside of the cable. This holds the signal conductor free in the air in a helix form and guides it through the cable at defined intervals.

The flexibility of this construction is attained with two bridges that hold the clips together evenly and at exact intervals. The Cross Link Super Speed waveguides are threaded and fitted with clips by hand with extreme care in our own manufacturing unit. Afterwards the air-helix created in this manner is given its PE network jacket – again by hand. Finally the rhodium-coated plugs are fitted and the cable function is tested



„A STROKE OF GENIUS“ | AUDIO 12-2018



LS-4004 AIR



LS-4004 AIR



LS-2404 AIR



LS-1204 AIR



NF-1204 AIR



NF-2404 AIR

„This cable has what it takes to lift the performance of my chain into the next class! [...] The music flowed effortlessly into my ear and from there coursed right into my stomach. My goodness - that was fun!“
Fidelity 38-2018 | LS-4004 AIR

„This cable carries a lot of consideration and manual work. The LS-4004 AIR is one of the finest cables we've ever heard. It is gifted with a phenomenal analysis.“ stereoplay 01-2018 | LS-4004 AIR

„It's difficult to describe – you have to experience it yourself. Or to put it in terms of money, a hi-fi combination worth €20,000 can be improved by 20% simply with the LS-2404 AIR. That amounts to an extraordinary value.“
stereoplay 01-2017 | LS-2404 AIR

LS-4004 AIR PURE SILVER



LENGTH
1,0m Stereo
1,5m Stereo
2,0m Stereo
2,5m Stereo
3,0m Stereo*
3,5m Stereo
4,0m Stereo

*standard length +/- 0,5m Stereo
MOC Kč s DPH : 4.290 EUR

BFA & SPADE | SW ANGLE ADJUSTABLE

MOC Kč s DPH
327.811
440.479
553.147
665.815
776.873
891.151
1.003.819

*2x3,0m # 007714038

BFA & SPADE | SBW ANGLE ADJUSTABLE

MOC Kč s DPH
342.833
455.501
568.169
680.837
791.896
906.174
1.018.842

*2x3,0m #0077140381



„This is a cable with the license to thrill: The LS-4004 Air Pure Silver is as thick as your forearm and a real statement piece that’s very hard to beat in terms of appearance, workmanship and sound quality. The serpent destined to entice high end users who enjoy lingering in the garden of good listening [...] but rather one of the best speaker cables money can buy.“ Fidelity | 43

LS-4004 AIR



LENGTH
1,0m Stereo
1,5m Stereo
2,0m Stereo
2,5m Stereo
3,0m Stereo*
3,5m Stereo
4,0m Stereo

*standard length +/- 0,5m Stereo
MOC Kč s DPH : 924 EUR

BFA | SW ANGLE ADJUSTABLE

MOC Kč s DPH
71.464
96.251
121.038
145.825
160.954
195.399
220.186

*2x3,0m # 007714032

BFA | SBW ANGLE ADJUSTABLE

MOC Kč s DPH
81.658
106.445
131.232
156.019
170.612
205.592
230.379

*2x3,0m #0077140321

SPADE | SW ANGLE ADJUSTABLE

MOC Kč s DPH
71.464
96.251
121.038
145.825
160.954
195.399
220.186

*2x3,0m # 007714033

SPADE | SBW ANGLE ADJUSTABLE

MOC Kč s DPH
81.658
106.445
131.232
156.019
170.612
205.592
230.379

*2x3,0m #0077140331



„This cable carries a lot of consideration and manual work. The LS-4004 AIR is one of the finest cables we’ve ever heard. It is gifted with a phenomenal analysis.“ stereoplay 01-2018

LS-2404 AIR PURE SILVER



LENGTH
1,0m Stereo
1,5m Stereo
2,0m Stereo
2,5m Stereo
3,0m Stereo*
3,5m Stereo
4,0m Stereo

*standard length +/- 0,5m Stereo
MOC Kč s DPH : 2.640 EUR

BFA & SPADE | SW ANGLE ADJUSTABLE

MOC Kč s DPH
185.527
254.630
323.733
392.836
460.330
531.042
600.145

*2x3,0m #007712438

BFA & SPADE | SBW ANGLE ADJUSTABLE

MOC Kč s DPH
199.905
269.009
338.112
407.215
474.708
545.421
614.524

*2x3,0m #0077124381



LS-2404 AIR



LENGTH
1,0m Stereo
1,5m Stereo
2,0m Stereo
2,5m Stereo
3,0m Stereo*
3,5m Stereo
4,0m Stereo

*standard length +/- 0,5m Stereo
MOC Kč s DPH : 531 EUR

BFA | SW | MK II ANGLE ADJUSTABLE

MOC Kč s DPH
52.149
66.099
80.048
93.997
101.294
122.003
135.953

*2x3,0m # 007712436

BFA | SW | MK II ANGLE ADJUSTABLE

MOC Kč s DPH
60.197
74.254
88.203
102.152
109.020
130.051
144.108

*2x3,0m # 0077124361

SPADE | SW | MK II ANGLE ADJUSTABLE

MOC Kč s DPH
52.042
65.991
79.941
93.890
101.294
121.896
135.846

*2x3,0m #007712437

SPADE | SBW | MK II ANGLE ADJUSTABLE

MOC Kč s DPH
60.197
74.254
88.203
102.152
109.020
130.051
144.108

*2x3,0m #0077124371



LS-2404 AIR



BFA 45° SW	
MOC Kč s DPH	
47.321	
61.270	
75.219	
89.169	
96.680	
117.175	
131.124	

*2x3,0m #007712435

BFA 45° SBW	
MOC Kč s DPH	
51.613	
65.562	
79.511	
93.461	
100.757	
121.467	
135.416	

*2x3,0m #0077124351

BFA SW	
MOC Kč s DPH	
45.496	
59.446	
73.395	
87.452	
94.963	
115.351	
129.300	

*2x3,0m #007712432

BFA SBW	
MOC Kč s DPH	
48.823	
62.880	
76.829	
90.778	
98.182	
118.677	
132.734	

*2x3,0m #0077124321

LENGTH	
1,0m Stereo	
1,5m Stereo	
2,0m Stereo	
2,5m Stereo	
3,0m Stereo*	
3,5m Stereo	
4,0m Stereo	

*standard length
+/- 0,5m Stereo
MOC Kč s DPH :
531 EUR



LS-2404 AIR



SPADE SW	
MOC Kč s DPH	
47.321	
61.270	
75.219	
89.169	
96.680	
117.175	
131.124	

*2x3,0m #007712433

SPADE SBW	
MOC Kč s DPH	
51.613	
65.562	
79.511	
93.461	
100.757	
121.467	
135.416	

*2x3,0m #0077124331

SCREW TYPE SW	
MOC Kč s DPH	
48.072	
62.021	
75.970	
90.027	
97.431	
117.926	
131.875	

*2x3,0m #007712434

SCREW TYPE SBW	
MOC Kč s DPH	
52.686	
66.635	
80.692	
94.641	
101.831	
122.540	
136.489	

*2x3,0m #0077124341

LENGTH	
1,0m Stereo	
1,5m Stereo	
2,0m Stereo	
2,5m Stereo	
3,0m Stereo*	
3,5m Stereo	
4,0m Stereo	

*standard length
+/- 0,5m Stereo
MOC Kč s DPH :
531 EUR



LS-2404 AIR



„It's difficult to describe – you have to experience it yourself. Or to put it in terms of money, a hi-fi combination worth €20,000 can be improved by 20% simply with the LS-2404 AIR. That amounts to an extraordinary value.“ stereoplay 01-2017

EASY PLUG SW	
MOC Kč s DPH	
42.492	
56.441	
70.391	
84.340	
92.066	
112.346	
126.296	

*2x3,0m #007712431

EASY PLUG SBW	
MOC Kč s DPH	
44.209	
58.266	
72.215	
86.164	
93.783	
114.063	
128.120	

*2x3,0m #0077124311

LENGTH	
1,0m Stereo	
1,5m Stereo	
2,0m Stereo	
2,5m Stereo	
3,0m Stereo*	
3,5m Stereo	
4,0m Stereo	

*standard length
+/- 0,5m Stereo
MOC Kč s DPH :
531 EUR



LS-1204 AIR



„A stroke of genius that shows the competitors the limits | precious finish: outstanding“ AUDIO 12-2018

BFA SW	
MOC Kč s DPH	
22.856	
30.367	
37.985	
45.496	
48.930	
60.626	
68.137	

*2x3,0m #007701332

SPADE SW	
MOC Kč s DPH	
24.680	
32.191	
39.702	
47.321	
50.647	
62.343	
69.962	

*2x3,0m #007701333

LENGTH	
1,0m Stereo	
1,5m Stereo	
2,0m Stereo	
2,5m Stereo	
3,0m Stereo*	
3,5m Stereo	
4,0m Stereo	

*standard length
+/- 0,5m Stereo
MOC Kč s DPH :
289 EUR



LS-804 AIR



LENGTH	BFA SW	SPADE SW	EASY PLUG SW
	MOC Kč s DPH	MOC Kč s DPH	MOC Kč s DPH
1,0m Stereo	18.778	20.280	11.374
1,5m Stereo	23.499	25.002	16.095
2,0m Stereo	28.328	29.830	20.924
2,5m Stereo	33.049	34.552	25.645
3,0m Stereo*	36.161	37.663	28.757
3,5m Stereo	42.599	44.102	35.195
4,0m Stereo	47.321	48.823	39.917

*standard length +/- 0,5m Stereo
MOC Kč s DPH : 182 EUR

*2x3,0m #007710832

*2x3,0m #007710833

*2x3,0m #007710831



"There's no getting away from it: €1000 is a lot of money for a loudspeaker cable. But in our listening room we tested much more expensive cables that couldn't do what the LS-804 manages. The concept is fantastic, the sound is finely balanced and exceeds our expectations in every respect. In all honesty a masterpiece." AUDIO 06-2019

LS-2404



LENGTH	SPADE SW	SPADE SBW
	MOC Kč s DPH	MOC Kč s DPH
1,0m Stereo	41.848	44.853
1,5m Stereo	52.900	56.012
2,0m Stereo	63.953	67.064
2,5m Stereo	75.112	78.117
3,0m Stereo*	80.558	83.374
3,5m Stereo	97.216	100.328
4,0m Stereo	108.269	111.380

*standard length +/- 0,5m Stereo
MOC Kč s DPH : 439 EUR

*2x3,0m #007702433

*2x3,0m #0077024331



LS-1603 SILVER



LENGTH	BFA 45° SW	BFA 45° SBW	BFA SW	BFA SBW
	MOC Kč s DPH	MOC Kč s DPH	MOC Kč s DPH	MOC Kč s DPH
1,0m Stereo	32.298	36.054	30.152	32.298
1,5m Stereo	41.097	44.853	38.951	41.097
2,0m Stereo	49.896	53.651	47.750	49.896
2,5m Stereo	58.695	62.343	56.549	58.695
3,0m Stereo*	62.772	66.206	60.733	62.772
3,5m Stereo	76.292	79.941	74.146	76.292
4,0m Stereo	85.091	88.740	82.945	85.091

*standard length +/- 0,5m Stereo
MOC Kč s DPH : 336 EUR

*2x3,0m #007701735

*2x3,0m #0077017351

*2x3,0m #007701732

*2x3,0m #0077017321

LS-1603 SILVER



LENGTH	SPADE SW	SPADE SBW	SCREW TYPE SW	SCREW TYPE SBW
	MOC Kč s DPH	MOC Kč s DPH	MOC Kč s DPH	MOC Kč s DPH
1,0m Stereo	31.547	34.015	32.298	36.054
1,5m Stereo	40.346	42.814	41.097	44.853
2,0m Stereo	49.145	51.613	49.896	53.651
2,5m Stereo	57.836	60.412	58.695	62.343
3,0m Stereo*	61.914	64.274	62.772	66.206
3,5m Stereo	75.434	77.902	76.292	79.941
4,0m Stereo	84.233	86.701	85.091	88.740

*standard length +/- 0,5m Stereo
MOC Kč s DPH : 336 EUR

*2x3,0m #007701733

*2x3,0m #0077017331

*2x3,0m #007701734

*2x3,0m #0077017341



LS-1603 SILVER



EASY PLUG | SW

MOC Kč s DPH
28.650
37.449
46.248
55.046
59.231
72.644
81.443

*2x3,0m #007701731

EASY PLUG | SBW

MOC Kč s DPH
29.616
38.414
47.213
56.012
60.197
73.610
82.409

*2x3,0m #0077017311

LENGTH
1,0m Stereo
1,5m Stereo
2,0m Stereo
2,5m Stereo
3,0m Stereo*
3,5m Stereo
4,0m Stereo

*standard length
+/- 0,5m Stereo
MOC Kč s DPH :
336 EUR



LS-1603



BFA 45° SW
MOC Kč s DPH
25.753
32.513
39.166
45.926
48.488
59.231
65.991

*2x3,0m #007701635

BFA 45° SBW
MOC Kč s DPH
28.650
35.410
42.063
48.716
51.325
62.128
68.889

*2x3,0m #0077016351

BFA SW
MOC Kč s DPH
24.465
31.118
37.878
44.531
47.208
57.944
64.596

*2x3,0m #007701632

BFA SBW
MOC Kč s DPH
25.645
32.405
39.058
45.711
48.447
59.124
65.884

*2x3,0m #0077016321

LENGTH
1,0m Stereo
1,5m Stereo
2,0m Stereo
2,5m Stereo
3,0m Stereo*
3,5m Stereo
4,0m Stereo

*standard length
+/- 0,5m Stereo
MOC Kč s DPH :
264 EUR



LS-1603



SPADE | SW

MOC Kč s
25.109
31.869
38.522
45.282
47.884
58.587
65.348

*2x3,0m #007701633

SPADE | SBW

MOC Kč s DPH
26.933
33.586
40.346
46.999
49.687
60.412
67.064

*2x3,0m #0077016331

LENGTH
1,0m Stereo
1,5m Stereo
2,0m Stereo
2,5m Stereo
3,0m Stereo*
3,5m Stereo
4,0m Stereo

*standard length
+/- 0,5m Stereo
MOC Kč s DPH :
264 EUR





NF-2404 AIR



	RCA	XLR
LENGTH	MOC Kč s DPH	MOC Kč s DPH
0,75m Stereo*	39.096	42.701
1,00m Stereo*	43.715	47.433
1,25m Stereo	57.192	60.948
1,50m Stereo*	61.967	65.573
1,75m Stereo	76.292	80.155
2,00m Stereo	85.842	89.705
2,25m Stereo	95.500	99.255
*standard length +/- 0,25m Stereo MOC Kč s DPH : 304 EUR	*0,75m #007187007 *1,00m #007187010 *1,50m #007187015	*0,75m #0071870073 *1,00m #0071870103 *1,50m #0071870153



„The NF-2404 Air RCA cable has magical cubic metres more than a competitor model. A clear vote for the in-akustik alternative.“ stereoplay 01-2017

“The authentically innovative structure of in-akustiks new interconnect Referenz NF-2404 has propelled it right to the top of the class. Listening to this air cable will take your breath away!” stereo 09-2015

NF-1204 AIR



	RCA	XLR
LENGTH	MOC Kč s DPH	MOC Kč s DPH
0,75m Stereo*	17.276	25.860
1,00m Stereo*	20.173	28.757
1,25m Stereo	25.753	33.264
1,50m Stereo*	25.860	34.552
1,75m Stereo	31.762	39.058
2,00m Stereo	34.766	41.955
2,25m Stereo	37.771	44.853
*standard length +/- 0,25m Stereo MOC Kč s DPH : 116 EUR	*0,75m #007185107 *1,00m #007185110 *1,50m #007185115	*0,75m #0071851073 *1,00m #0071851103 *1,50m #0071851153



NF-1603



	RCA	XLR
LENGTH	MOC Kč s DPH	MOC Kč s DPH
0,75m Stereo*	16.664	18.647
1,00m Stereo*	18.782	20.753
1,25m Stereo	24.358	26.397
1,50m Stereo*	25.148	27.120
1,75m Stereo	30.259	32.298
2,00m Stereo	33.264	35.303
2,25m Stereo	36.268	38.307
*standard length +/- 0,25m Stereo MOC Kč s DPH : 117 EUR	*0,75m #007186007 *1,00m #007186010 *1,50m #007186015	*0,75m #0071860073 *1,00m #0071860103 *1,50m #0071860153





DIGITAL 2404 AIR



RCA		XLR	
MOC Kč s DPH		MOC Kč s DPH	
19.315		21.031	
21.675		23.285	
29.294		31.011	
30.796		32.727	
39.166		40.882	
40.561		42.170	
49.145		50.862	
*1,00m #007187110		*1,00m #0071871103	
*1,50m #007187115		*1,50m #0071871153	
*2,00m #007187120		*2,00m #0071871203	

LENGTH
0,75m Mono
1,00m Mono*
1,25m Mono
1,50m Mono*
1,75m Mono
2,00m Mono*
2,25m Mono

*standard length
+/- 0,25m Mono
MOC Kč s DPH :
182 EUR



PHONO 2404 AIR



RCA -> RCA	RCA -> SME 90°	RCA -> SME	XLR -> SME 90°
MOC Kč s DPH	MOC Kč s DPH	MOC Kč s DPH	MOC Kč s DPH
22.641	24.358	24.358	25.967
24.358	25.967	25.967	27.577
32.298	34.015	34.015	35.732
33.586	35.410	35.410	36.805
41.955	43.672	43.672	45.389
43.243	44.638	44.638	46.569
51.720	53.330	53.330	55.046
*1,00m #0071872010	*1,00m #0071872110	*1,00m #0071872210	*1,00m #0071872310
*1,50m #0071872015	*1,50m #0071872115	*1,50m #0071872215	*1,50m #0071872315
*2,00m #0071872020	*2,00m #0071872120	*2,00m #0071872220	*2,00m #0071872320

*standard length
+/- 0,25m Stereo
MOC Kč s DPH :
178 EUR



PHONO-2404 AIR



XLR -> SME
MOC Kč s DPH
25.967
27.577
35.732
36.805
45.389
46.569
55.046

*1,00m #0071872410
*1,50m #0071872415
*2,00m #0071872420

LENGTH
0,75m Stereo
1,00m Stereo*
1,25m Stereo
1,50m Stereo*
1,75m Stereo
2,00m Stereo*
2,25m Stereo

*standard length
+/- 0,25m Stereo
MOC Kč s DPH :
178 EUR





AC-2404 AIR HIGH QUALITY



LENGTH	SCHUKO -> C19	SCHUKO -> C15
	MOC Kč s DPH	MOC Kč s DPH
1,0m Stereo*	41.634	41.634
1,5m Stereo*	47.643	47.643
2,0m Stereo*	53.544	53.544
3,0m Stereo*	65.455	65.455
3,5m Stereo	73.073	73.073
4,0m Stereo	78.975	78.975

*standard length
+/- 0,5m
MOC Kč s DPH :
220 EUR

*1,0m #007626310
*1,5m #007626315
*2,0m #007626320
*3,0m #007626330

*1,0m #007626210
*1,5m #007626215
*2,0m #007626220
*3,0m #007626230



HIGH END Version C19



HIGH END Version C15 (C13)



HIGH END Version SCHUKO

AC-2404 AIR



LENGTH	SCHUKO -> C19	SCHUKO -> C13
	MOC Kč s DPH	MOC Kč s DPH
1,0m Stereo*	29.723	29.723
1,5m Stereo*	35.732	35.732
2,0m Stereo*	41.634	41.634
3,0m Stereo*	53.544	53.544
3,5m Stereo	61.163	61.163
4,0m Stereo	67.064	67.064

*standard length
+/- 0,5m
MOC Kč s DPH :
220 EUR

*1,0m #007626110
*1,5m #007626115
*2,0m #007626120
*3,0m #007626130

*1,0m #007626010
*1,5m #007626015
*2,0m #007626020
*3,0m #007626030



Basic Version C19



Basic Version C15



Basic Version SCHUKO



HANDMADE

We have long set the bar very high in regard to quality, because cables and connections are extremely sensitive. Physical phenomena that arise during the transmission of signals can only be controlled with technical finesse and the best materials.

For this reason all cables are manufactured in a German cable mill and finished by us in Ballrechten-Dottingen in elaborate manual work. Some production steps are carried out in close cooperation with the Caritas workshops in our neighboring town Heitersheim.



For our Referenz Selection cables, we also offer an after sales service. For technical questions regarding the product or the right cable connection, please contact our support team directly. You can contact our experts Monday to Friday from 9–12 a.m. and 13–17 p.m. on the telephone number +49 (0) 7634 5610-70. In addition, we grant to all Referenz Selection cables extended warranty to 5 years. Please follow the instructions on the warranty card supplied with the product.



STOIC WALL MOUNTS & BASES (FREE-STANDING)

Vinyl on the turntable is a sensitive passion, nothing disturbs the enthusiasm for music more than an impaired sound. Every vibration, however delicate is annoying, unless the fundament is right. HighStandArt delivers it: with the STOIC-Wallmount and the STOIC-Base.

Every STOIC combines all the features it needs for a perfect music reproduction. It decouples Hi-Fi devices completely and securely from vibrating floors, furniture or HiFi-racks and thereby from annoying vibrations and resonances. For all HiFi-components. Be it analogue or digital.

The metal frame filled with sand, kills vibrations by its enormous mass, as well as the use of low-resonance materials such as natural slate or plywood.

A hard, unsprung coupling between the frame and the support ensures that no swinging is produced.



And last but not least, STOIC showcases valuable devices in an equally valuable way: high-quality workmanship of classical, timeless beauty. Handcrafted in Germany.

In short: Hi-Fi components are just as good as their setup. Each background affects the sound staging. And just as music needs the silence as the basis, good sound needs a stoic calm. Ideal sound needs a STOIC.



„The wall mount Stoic is not cheap, but worth the price: despite the slim profile, it is the most stable wall mount known to us. It provides for record players in almost any living situation for a significantly increased playback quality.“ LP-Magazin 11-2018

VOLUME



stair





FRAME | WALL MOUNT

ITEM NO	EAN	VERSION		MOC Kč s DPH
00269001	4001985516469	Wall Mount black	40x55	39.809
00269011	4001985517862	Wall Mount white	40x55	39.809
00269003	4001985516483	Wall Mount steel	40x55	60.412
00269002	4001985516476	Wall Mount black	50x55	43.565
00269012	4001985057306	Wall Mount white	50x55	43.565
00269004	4001985516490	Wall Mount steel	50x55	64.060



FRAME | ABSORBER BASE

ITEM NO	EAN	VERSION		MOC Kč s DPH
00269013	4001985517879	Absorber Base black	40x55	35.303
00269014	4001985517886	Absorber Base white	40x55	35.303
00269015	4001985517893	Absorber Base steel	40x55	48.072
00269016	4001985517909	Absorber Base black	50x55	39.058
00269017	4001985517916	Absorber Base white	50x55	39.058
00269018	4001985517923	Absorber Base steel	50x55	55.583




PLATE 40X55

ITEM NO	EAN	VERSION		MOC Kč s DPH
00269021	4001985517954	Multiplex clear	40x55	18.027
00269022	4001985517961	Multiplex black	40x55	23.285
00269023	4001985517978	Multiplex white	40x55	23.285
00269024	4001985517985	Slate	40x55	63.094
00269025	4001985517992	Sandwich clear	40x55	27.040
00269026	4001985518425	Sandwich black	40x55	32.298
00269027	4001985518432	Sandwich white	40x55	32.298

PLATE 50X55

ITEM NO	EAN	VERSION		MOC Kč s DPH
00269028	4001985518449	Multiplex clear	50x55	21.031
00269029	4001985518456	Multiplex black	50x55	26.289
00269030	4001985518463	Multiplex white	50x55	26.289
00269031	4001985518470	Slate	50x55	66.850
00269032	4001985518487	Sandwich clear	50x55	30.045
00269033	4001985518494	Sandwich black	50x55	35.303
00269034	4001985518500	Sandwich white	50x55	35.303

PLATE 40X55 WITH CABLE OUTLET



ITEM NO	EAN	VERSION		MOC Kč s DPH
00269005	4001985516506	Multiplex clear	40x55	16.632
00269006	4001985516513	Multiplex black	40x55	24.358
00269019	4001985517930	Multiplex white	40x55	24.358
00269007	4001985516520	Slate	40x55	60.197

PLATE 50X55 WITH CABLE OUTLET







ITEM NO	EAN	VERSION		MOC Kč s DPH
00269008	4001985516537	Multiplex clear	50x55	510,00
00269009	4001985516544	Multiplex black	50x55	680,00
00269020	4001985517947	Multiplex white	50x55	680,00
00269010	4001985516551	Slate	50x55	1.450,00










SCOPE OF DELIVERY - ACCESSORIES













COMPARISON OF SIZES














in-akustik headquarters in Ballrechten-Dottingen

LEGAL NOTICE

Our general terms and conditions (GTC 03/2009) apply: -> www.in-akustik.de. Deliveries occur ex works (EXW) D - Ballrechten-Dottingen (Incoterms 2000). Place of performance for all deliveries and obligations is D - Ballrechten-Dottingen.

This in-akustik catalogue is valid from July 2019. All prices in EUR. The printed matter we designed to provide information and advice to the best of our knowledge. Any legal obligations, however, may not be derived from such printed matter. Images, particularly relating size and features of the products shown, are non-binding. We reserve the right to make technical and formal changes to our products in the interests of technical progress.



iPod®/iPhone®/iPad® are trademarks of Apple Inc., registered in the U.S. and other countries.



“© 2013 CSR plc and its group companies. The aptX® mark and the aptX logo are trade marks of CSR plc or one of its group companies and may be registered in one or more jurisdictions.”



“The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth® SIG, Inc. and any use of such marks by in-akustik is under license. Other trademarks and trade names are those of their respective owners.”



The Terms HDMI® and HDMI® High-Defintion Multimedia Interface, and the HDMI® Logo are trademarks or registered trademarks of HDMI® Licensing LLC in the United Stated and other countries.

in-akustik Mitgliedschaften:



in-akustik GmbH & Co. KG
Untermatten 12-14
79282 Ballrechten-Dottingen
Germany

Tel.: +49 (0) 7634 5610-70
Fax: +49 (0) 7634 5610-80
E-Mail: info@in-akustik.de
Web: www.in-akustik.de

All previous prices hereby lose their validity. All prices in EUR.
This in-akustik catalogue is valid from July 2019. The printed matter we designed to provide information and advice to the best of our knowledge. Any legal obligations, however, may not be derived from such printed matter. Images, particularly relating size and features of the products shown, are non-binding. We reserve the right to make technical and formal changes to our products in the interests of technical progress.

